



RT1272(12V7.2Ah)

Specification

Cells Per Unit	6
Voltage Per Unit	12
Nominal Capacity	7.2Ah@20hour-rate to 1.75V per cell @25°C
Weight	Approx. 1.95 Kg (Tolerance ±5.0%)
Internal Resistance	Approx. 35 mΩ
Terminal	F1/F2
Max. Discharge Current	72A (5 sec)
Short Circuit Current	360A
Design Life	6~8 years (Float charging)
Max. Charging Current	2.1 A
Reference Capacity	C3 5.51AH C5 6.20AH C10 6.73AH C20 7.20AH
Standby Use Voltage	13.7 V~13.9 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



RT series is a general purpose battery with 6~8 years design life in float service. It meets with IEC, JIS, BS, GB/T and YD/T standards. With advanced AGM valve regulated technology and high purity raw material, the RT series battery maintains high consistency for better performance and reliable standby service life. It is suitable for UPS/EPS, medical equipment, emergency light and security system applications.



ISO 9001



ISO 14001



OHSAS 18001







MH 28539



G4M20206-0910-E-16

Dimensions



F2 Terminal

Length	151±1.5mm (5.94 inches)
Width	65±1.5mm (2.56 inches)
Height	94±1.5mm (3.70 inches)
Total Height	100±1.5mm (3.94 inches)
Terminal	Value
M5	6~7 N·m
M6	8~10 N·m
M8	10~12 N·m

Unit: mm

Constant Current Discharge Characteristics : A (25°C)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	26.50	18.92	13.82	7.936	4.399	2.701	2.030	1.639	1.358	0.874	0.710	0.375
1.65V	24.64	17.88	13.21	7.619	4.248	2.615	1.968	1.595	1.323	0.864	0.701	0.369
1.70V	22.23	16.46	12.37	7.282	4.110	2.529	1.914	1.551	1.289	0.851	0.691	0.364
1.75V	19.92	15.07	11.51	6.960	3.960	2.440	1.857	1.512	1.256	0.839	0.682	0.360
1.80V	17.49	13.64	10.63	6.652	3.808	2.353	1.800	1.468	1.224	0.825	0.673	0.356
1.85V	13.88	11.15	8.822	5.730	3.416	2.156	1.664	1.365	1.141	0.774	0.633	0.338

Constant Power Discharge Characteristics : WPC (25°C)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	43.93	32.16	24.15	14.41	8.27	5.12	3.88	3.15	2.62	1.71	1.40	0.74
1.65V	41.32	30.98	23.43	13.98	8.03	4.98	3.77	3.07	2.56	1.69	1.38	0.73
1.70V	38.13	29.04	22.28	13.50	7.82	4.84	3.69	3.00	2.50	1.67	1.36	0.72
1.75V	34.92	27.06	21.03	13.04	7.58	4.69	3.59	2.94	2.45	1.65	1.35	0.71
1.80V	31.32	24.92	19.69	12.59	7.33	4.55	3.50	2.86	2.39	1.62	1.33	0.71
1.85V	25.38	20.73	16.58	10.95	6.61	4.19	3.25	2.67	2.24	1.53	1.25	0.67

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values. The battery must be fully charged before the capacity test. The C₂₀ should reach 95% after the first cycle and 100% after the third cycle.