



Video Intercom VL-SV74AZ

Model composition		Main Monitor(VL-MV74) x1, Door Station(VL-V524) x1
Maximum Connectable Units	Door Station	Up to 2 (1 included with VL-SV74)
	Monitor	Up to 3 extension monitors (not including the main monitor)
	Wireless Monitor	Wireless sub monitors NOT supported.
Connectable Devices	E-lock Release Support	Up to 2 (user supplied)
	PBX	Only Panasonic PBX
Convenience	Picture Recording	Internal memory: Up to 50 visitors/sessions (up to 4 still images per visitor/session)
	Night Vision	Yes (LED lights)
	Touch Panel / Pan & Tilt	- / -
	Voice Changer	Yes
	Intercom call	Yes (between main monitor and extension monitor)
Monitor	Power source	220-240 V AC, 50/60 Hz
	Power consumption	Standby: 2.3 W, Operating: 11.3 W * Measurement conditions: VL-V524 (1 pcs.) is connected to the Main Monitor
	Dimensions (H x W x D)	Approx. 158 x 201 x 25 mm
	Mass (weight)	Approx. 715 g *Including AC cable.
	Operating environment	Ambient temperature: Approx. 0 °C to +40 °C, Relative humidity (non-condensing): up to 90 %
	Display size	7-inch wide colour with touch sensor / WVGA (800 x 480 pixels)
	Display language	English, Arabic, Vietnamese
	Talking method	Hands-free
	Installation method	Wall mount (mounting bracket supplied)
	External material	Flame retardant ABS resin
Door Station	Power source	Power supplied by the main monitor

Dimensions (H x W x D)	Approx. 152 x 102 x 35.5 (21.5 *) mm *Excluding sections embedded into the wall.
Mass (weight)	Approx. 225 g
Operating environment	Ambient temperature: Approx. -15 °C to +55 °C, Relative humidity (non-condensing): up to 90 %
Talking method	Hands-free
Viewing angle	Horizontally: Approx. 85°, Vertically: Approx. 54°
Image sensor/ Camera (pixel)	1/3 inch CMOS sensor (Approx. 1.3 M pixels)
Minimum illuminance required	1 lx (within approx. 50 cm from the camera lens)
Lighting method	LED lights
IP rating (INGRESS PROTECTION)	IP44 *Water resistance is only assured if the doorstation is installed correctly according to the instructions in the Installation Guide, and appropriate water protection measures are taken.
Installation method	Surface mount (mounting base supplied), Flush mount (mount box sold separately)
External material	Flame retardant resin