



> [Video Intercom](#) > [Home Intercom Systems](#)

Slimline 7" Home Video Intercom Kit VL-SV75AZ

Model composition		Main Monitor(VL-MV754) x1, Door Station(VL-V524) x1, Power Supply Unit (VL-PS241) x 1
Maximum Connectable Units	Door Station	Up to 2 (1 included with VL-SV74)
	Monitor	Up to 3 extension monitors (not including the main monitor)
	Wireless Monitor	Wireless sub monitors NOT supported.
	Wireless Repeater	Up to 2 (sold separately)
Connectable Devices	E-lock Release Support	Up to 2 (user supplied)
	PBX	Only Panasonic PBX
Convenience	Picture Recording	Internal memory: Up to 50 visitors/sessions (up to 4 still images per visitor/session)
	Night Vision	Yes (LED lights)
	Touch Panel / Pan & Tilt	- / -
	Voice Changer	Yes
	Intercom call	Yes (between main monitor and extension monitor)
Monitor	Power source	Power supply unit (VL-PS241) 24 V DC, 0.6 A
	Power consumption	Standby:1.9 W, Operating:12.7 W *Measurement conditions: Monitor (1 pc.) with Door Station VL-V524 (1 pc.) is connected to VL-PS241
	Dimensions (H x W x D)	Approx. 158 x 201 x 25 mm
	Mass (weight)	Main monitor: 605 g Power supply unit: 215 g (VL-PS241)
	Operating environment	Ambient temperature: Approx. 0 °C to +40 °C, Relative humidity (non-condensing): up to 90 %
	Display size	7-inch wide colour / WVGA (800 x 480 pixels)(Touch sensor keys)
	Display language	English, Arabic
	Talking method	Hands-free
	Installation method	Wall mount (mounting bracket supplied)

	External material	Flame retardant ABS resin
Door Station	Power source	Power supplied by the main monitor
	Dimensions (H x W x D)	Approx. 152 x 102 x 35.5 (21.5 *) mm *Excluding sections embedded into the wall.
	Mass (weight)	Approx. 225 g
	Operating environment	Ambient temperature: Approx. -15 °C to +55 °C, Relative humidity (non-condensing): up to 90 %
	Talking method	Hands-free
	Viewing angle	Horizontally: Approx. 85°, Vertically: Approx. 54°
	Image sensor/ Camera (pixel)	1/3 inch CMOS sensor (Approx. 1.3 M pixels)
	Minimum illuminance required	1 lx (within approx. 50 cm from the camera lens)
	Lighting method	LED lights
	IP rating (INGRESS PROTECTION)	IP44 *Water resistance is only assured if the doorstation is installed correctly according to the instructions in the Installation Guide, and appropriate water protection measures are taken.
	Installation method	Surface mount (mounting base supplied), Flush mount (mount box sold separately)
	External material	Flame retardant resin