



> [Video Intercoms](#) > [Video Intercom Accessories](#)

## VL-V554BX/UBX

Model number and name	VL-V554 (Surface mount) VL-V554U (Flush mount) Door Station (Doorphone)
Power source	Supplied by the main monitor 20 V DC, 0.23 A
Power consumption	—
Dimensions(H × W × D)(Excluding protruding sections)	VL-V554: 169 × 118 × 30 mm VL-V554U: 169 × 118 × 16.5 mm (excluding sections embedded into the wall)
Weight	VL-V554: 405 g VL-V554U: 345 g
Operating environment	Ambient temperature: Approx. -15 °C to +55 °C Relative humidity (non-condensing): up to 90 % (tested up to -20 °C)
Display	—
Display language	—
Talking method	Hands-free
Frequency range	—
Transmitting range	—
Option output (A contact)	—
Viewing angle	Horizontally: Approx. 170° Vertically: Approx. 115°
Image sensor / camera (pixel)	CMOS sensor (Approx. 1.0 M pixels)
Minimum illuminance required	1 lx (within approx. 50 cm from the camera lens)
Lighting method	Warm white coloured LED lights
IP rating/ IK rating	IP54*1 / Compliant with IK07
Installation method	VL-V554: surface mount (mounting base supplied) VL-V554U: flush mount (flush mounting box supplied)
External material	Aluminium and flame retardant PC+PS resin