



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Preparation of safety data sheets for hazardous chemicals Code of Practice June 2023

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name BOSTIK 9210 PP PRIMER

Product Code(s)
30840329
30840329

Other means of identification

Proper shipping name Flammable liquid, n.o.s. (Toluene, Xylenes (o-, m-, p- isomers))

UN number or ID number UN1993

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Primers

Uses advised against

Illicit Drug Precursors/Reagents This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling, and storing these substances.

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Flammable liquids	Category 2 - (H225)
Aspiration hazard	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Reproductive toxicity	Category 1A - (H360)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

Label elements

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

Flame
Exclamation mark
Health hazard



Signal word
DANGER

Hazard statements

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H360 - May damage fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves, protective clothing, eye protection and face protection
Wash face, hands and any exposed skin thoroughly after handling
Use only outdoors or in a well-ventilated area
Do not breathe dust
Ground and bond container and receiving equipment
Use non-sparking tools
Take action to prevent static discharges
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Keep cool
Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)
IF ON SKIN: Wash with plenty of water and soap
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell
IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

May be harmful if inhaled.
In use, may form flammable/explosive vapor-air mixture.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 6

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

Label requirements in accordance with SUSMP

POISON

KEEP OUT OF REACH OF CHILDREN

READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No.	Weight-%
Toluene	108-88-3	40 - 70
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable extinguishing media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Vapors may form explosive mixture with air. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks).

Hazardous combustion products Carbon oxides. Hydrocarbons.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Eliminate all ignition sources if safe to do so. Residues which cannot be recycled are disposed of as chemical waste. Equipment cleaned with organic solvent, washings are collected and disposed of as solvent waste.

Section 7: Handling and storage, including how the chemical may be safely used

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

Recommended storage temperature

Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

Section 8: Exposure controls and personal protection

Control Parameters

Exposure Limits

Chemical name	Australia
Toluene 108-88-3	TWA: 50 ppm; TWA: 191 mg/m ³ ; STEL: 150 ppm; STEL: 574 mg/m ³ ;
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 80 ppm; TWA: 350 mg/m ³ ; STEL: 150 ppm; STEL: 655 mg/m ³ ;

OEL as published by Safe Work Australia

Biological occupational exposure limits

Appropriate engineering controls

Engineering controls

Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

Eyeface protection	Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Antistatic boots. Chemical resistant apron. Wear fire/flame resistant/retardant clothing.
Hand protection	For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Nitrile rubber.
Respiratory protection	Use appropriate respiratory protection. Organic gases and vapors filter conforming to EN 14387.
Environmental exposure controls	No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid	
Appearance	Liquid	
Color	Clear, colorless	
Odor	Solvent	
Odor threshold	No information available	
Property	Values	Remarks • Method
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	
Melting point / freezing point	Not applicable . °C	
Initial boiling point and boiling range	> 100 °C	
Flash point	4 °C	CC (closed cup) (Toluene)
Evaporation rate	No data available	
Flammability	No data available	Flammable liquid
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	<110 kPa	
Relative vapor density	No data available	
Relative density	0.87	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	10 mPa s	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other information		
Solid content (%)	No information available	
Liquid Density	No information available	
VOC content		No information available

Section 10: Stability and reactivity

Reactivity

Reactivity	No information available.
-------------------	---------------------------

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness. May be harmful if inhaled.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity - Product Information

The following ATE values have been calculated for the mixture

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	100,000.00 mg/kg
ATEmix (inhalation-gas)	>20000
ATEmix (inhalation-vapor)	552.80
ATEmix (inhalation-dust/mist)	241.20 mg/l

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Xylenes (o-, m-, p- isomers)	=3500 mg/kg (Rattus)	> 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus)	= 11 mg/L (ATE)

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Component Information					
Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.4	Rabbit	Dermal			Irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information		
Toluene (108-88-3)		
Method	Species	Results
Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)	Salmonella typhimurium	Not mutagenic
OECD Test No. 476: In Vitro Mammalian Cell Gene Mutation Tests using the Hprt and xprt genes	Mouse	Not mutagenic

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
Toluene 108-88-3			Group 3
Xylenes (o-, m-, p- isomers) 1330-20-7	Carc. 1B	Carc. 1B	Group 3

Legend

IARC (International Agency for Research on Cancer)
Group 3 - Not classifiable as to carcinogenicity in humans

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. May damage fertility or the unborn child.

Component Information
Toluene (108-88-3)

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Component Information					
Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.26	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat, male, female	Inhalation, vapor			NOAEL: 1.131 mg/l

Aspiration hazard May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)
Xylenes (o-, m-, p- isomers) 1330-20-7	EC50: =11mg/L (72h, Pseudokirchneriella subcapitata)	LC50 96 h 2.6 mg/L (Oncorhynchus mykiss) (OECD 203)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L (Daphnia magna)

Persistence and degradability

Persistence and degradability No information available.

Component Information			
Xylenes (o-, m-, p- isomers) (1330-20-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	biodegradation	87.8 % Readily biodegradable

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Toluene 108-88-3	2.73

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

Xylenes (o-, m-, p- isomers) 1330-20-7	3.15
---	------

Mobility

Mobility in soil After release, disperses through ground water.

Mobility The product is insoluble and floats on water.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products Should not be released into the environment. Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle contaminated packages in the same way as the product itself.

Section 14: Transport information

ADG

UN number or ID number UN1993
UN proper shipping name Flammable liquid, n.o.s.
Transport hazard class(es) 3
Packing group II
Environmental hazard No
Special Provisions 274
Limited quantity (LQ) 1 L
Description UN1993, Flammable liquid, n.o.s. (Toluene, Xylenes (o-, m-, p- isomers)), 3, II
Hazchem code •3YE

IATA

UN number or ID number UN1993
Transport hazard class(es) 3
Packing group II
ERG Code 3H
Special Provisions A3
Limited quantity (LQ) 1 L
Description UN1993, Flammable liquid, n.o.s. (Toluene, Xylenes (o-, m-, p- isomers)), 3, II

IMDG

UN number or ID number UN1993
Transport hazard class(es) 3
Packing group II
EmS-No. F-E, S-E
Limited Quantity (LQ) 1 L
Special Provisions 274
Marine pollutant NP
Description UN1993, Flammable liquid, n.o.s. (Toluene, Xylenes (o-, m-, p- isomers)), 3, II, (4°C c.c.)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 6

Illicit Drug Precursors/Reagents

This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling, and storing these substances.

Chemical name	Illicit Drug Precursors/Reagents
Toluene - 108-88-3	Category 3

Legend

Category 3 - Chemicals and apparatus that may be used in the illicit production of drugs. Purchases from this list should alert companies or organizations to seek further indicators of any suspicious orders or enquiries. No official reporting is required for items on this list unless considered warranted.

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids with flash points <61°C kept above their boiling points at ambient conditions

Threshold quantity (T)

200

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Toluene 108-88-3	10 tonne/yr Threshold category 1 VOC
Xylenes (o-, m-, p- isomers) 1330-20-7	10 tonne/yr Threshold category 1 VOC; including individual or mixed isomers

International Inventories

AIIC	Complies
NZIoC	Not Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Not Listed
PICCS	Not Listed

Legend:

AIIC - Australian Inventory of Industrial Chemicals

NZIoC - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

SAFETY DATA SHEET

BOSTIK 9210 PP PRIMER
Revision Number 2

Revision date 24-Sep-2025
Supersedes date 08-Oct-2020

KECL - Korean Existing Chemicals Inventory
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Directive 2011/65/EU (EU RoHS 2), as amended by the Delegated Directive (EU) 2015/863 (EU RoHS 3)

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 24-Sep-2025

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet