



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Preparation of safety data sheets for hazardous chemicals Code of Practice June 2023

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name BOSTIK PREP G PLUS

Product Code(s)
30602131
30603148; 30602131

Other means of identification

Proper shipping name Coating solution

UN number or ID number UN1139

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesives

Uses advised against Consumer use.
Illicit Drug Precursors/Reagents This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling, and storing these substances.

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

Manufacturer

Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Flammable liquids	Category 2 - (H225)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)

Label elements

Flame
Exclamation mark

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020



Signal word
DANGER

Hazard statements

H225 - Highly flammable liquid and vapor
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
Repeated exposure may cause skin dryness or cracking

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust, fume, gas, mist, vapors and spray
Use only outdoors or in a well-ventilated area
Ground and bond container and receiving equipment
Use non-sparking tools
Take action to prevent static discharges
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Wear protective gloves, protective clothing, eye protection and face protection
Keep cool
Use explosion-proof electrical/ ventilating/ lighting/ equipment
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

In use, may form flammable/explosive vapor-air mixture.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 5

Label requirements in accordance with SUSMP

CAUTION
KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

Chemical name	CAS No.	Weight-%
Methyl ethyl ketone	78-93-3	30 - 60
4,4'-Methylenediphenyl diisocyanate	101-68-8	0.1 - 1
Isophorone diisocyanate	4098-71-9	0.1 - 1
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable extinguishing media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂).

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Recommended storage temperature

Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

Section 8: Exposure controls and personal protection

Working area parameters, subject to mandatory control (MAC or TSEL)

Exposure Limits This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product.

Chemical name	Australia
Methyl ethyl ketone 78-93-3	TWA: 150 ppm; TWA: 445 mg/m ³ ; STEL: 300 ppm; STEL: 890 mg/m ³ ;
4,4'-Methylenediphenyl diisocyanate 101-68-8	TWA: 0.02 mg/m ³ ; STEL: 0.07 mg/m ³ ;
Isophorone diisocyanate 4098-71-9	TWA: 0.02 mg/m ³ ; STEL: 0.07 mg/m ³ ;

OEL as published by Safe Work Australia

Biological occupational exposure limits

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eyeface protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Hand protection Wear suitable gloves. Impervious gloves.

Respiratory protection Organic gases and vapors filter conforming to EN 14387.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Dispersion
Color Black
Odor Solvent
Odor threshold No information available

Property	Values	Remarks • Method
pH	No data available	Not applicable
pH (as aqueous solution)	No data available	Insoluble in water

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

Melting point / freezing point	No data available	
Initial boiling point and boiling range	80 °C	
Flash point	-10 °C	
Evaporation rate	No data available	
Flammability	No data available	Flammable liquid
Flammability Limit in Air		
Upper flammability or explosive limits	11.5 % (V)	
Lower flammability or explosive limits	0.8 % (V)	
Vapor pressure	<110 kPa	hPa
Relative vapor density	2.5	
Relative density	0.94	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	400 °C	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No information available	
Oxidizing properties	No information available	
<u>Other information</u>		
Solid content (%)	No information available	
Liquid Density	No information available	
VOC content		No information available

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization Hazardous polymerization may occur.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials None known based on information supplied.

Hazardous decomposition products

Hazardous decomposition Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Hydrogen cyanide.

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

products Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity - Product Information

The following ATE values have been calculated for the mixture

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000
ATEmix (inhalation-gas)	>20000
ATEmix (inhalation-vapor)	>20
ATEmix (inhalation-dust/mist)	6.33 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
4,4'-Methylenediphenyl diisocyanate	=31600 mg/kg (Rattus) = 9200 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	1.5 mg/L (Rattus) 4 h
Isophorone diisocyanate	=4814 mg/kg (Rattus)	LD50 > 2000 mg/kg	=0.135 mg/L (Rattus) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Component Information					
Methyl ethyl ketone (78-93-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

4,4'-Methylenediphenyl diisocyanate (101-68-8)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye	0.1 mL	24 hours	Non-irritant

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
4,4'-Methylenediphenyl diisocyanate 101-68-8	Carc. 2	Carc. 2	Group 3

Legend

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans Group 3 - Not Classifiable as to Carcinogenicity in Humans

Component Information		
4,4'-Methylenediphenyl diisocyanate (101-68-8)		
Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Limited evidence of a carcinogenic effect

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

Component Information					
Methyl ethyl ketone (78-93-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Experiences made in practice					May cause drowsiness or dizziness Causes central nervous system depression

STOT - repeated exposure Based on available data, the classification criteria are not met.

Component Information					
Methyl ethyl ketone (78-93-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Subchronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapor	1254, 2518, 5041 ppm/6h/d	90 days	NOAEC 5014 ppm

Aspiration hazard No information available.

Section 12: Ecological information

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)
4,4'-Methylenediphenyl diisocyanate 101-68-8	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l Danio rerio	-	EC50 (24H) >1000 mg/L Daphnia magna
Isophorone diisocyanate 4098-71-9	EC50: =118.7mg/L (72h, Desmodesmus subspicatus)	LC50: =1.8mg/L (48h, Leuciscus idus)	-	EC50: =83.7mg/L (24h, Daphnia magna)

Persistence and degradability

Persistence and degradability No information available.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

Isophorone diisocyanate (4098-71-9)			
Method	Exposure time	Value	Results
EU C.4-D	28 days	0%	Not readily biodegradable

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Methyl ethyl ketone 78-93-3	0.3
4,4'-Methylenediphenyl diisocyanate 101-68-8	4.51

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Section 14: Transport information

ADG

UN number or ID number	UN1139
UN proper shipping name	Coating solution
Transport hazard class(es)	3
Packing group	II
Environmental hazard	No
Limited quantity (LQ)	5 L
Description	UN1139, Coating solution, 3, II

Hazchem code	•3YE
--------------	------

IATA

UN number or ID number	UN1139
Transport hazard class(es)	3
Packing group	II
ERG Code	3L
Special Provisions	A3
Limited quantity (LQ)	1 L
Description	UN1139, Coating solution, 3, II

IMDG

UN number or ID number	UN1139
Transport hazard class(es)	3
Packing group	II
EmS-No.	F-E, S-E
Limited Quantity (LQ)	5 L
Marine pollutant	NP
Description	UN1139, Coating solution, 3, II, (-10°C c.c.)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 5

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

Illicit Drug Precursors/Reagents

This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling, and storing these substances.

Chemical name	Illicit Drug Precursors/Reagents
Methyl ethyl ketone - 78-93-3	Category 3

Legend

Category 3 - Chemicals and apparatus that may be used in the illicit production of drugs. Purchases from this list should alert companies or organizations to seek further indicators of any suspicious orders or enquiries. No official reporting is required for items on this list unless considered warranted.

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids with flash points <61°C kept above their boiling points at ambient conditions

Threshold quantity (T)
200

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Methyl ethyl ketone 78-93-3	10 tonne/yr Threshold category 1 VOC
4,4'-Methylenediphenyl diisocyanate 101-68-8	10 tonne/yr Threshold category 1

International Inventories

AIIC	Complies
NZIoC	Complies
ENCS	Complies
IECSC	Complies
KECL	Not Listed
PICCS	Complies

Legend:

- AIIC** - Australian Inventory of Industrial Chemicals
- NZIoC** - New Zealand Inventory of Chemicals
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing Chemicals Inventory
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SAFETY DATA SHEET

BOSTIK PREP G PLUS
Revision Number 1.01

Revision date 10-Mar-2025
Supersedes date 17-Mar-2020

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Directive 2011/65/EU (EU RoHS 2), as amended by the Delegated Directive (EU) 2015/863 (EU RoHS 3)

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 10-Mar-2025

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet