

Application

Weatherfold Window 35 system has been designed for exterior timber outward folding windows in residential or light commercial applications.

It has been specifically developed to suit smaller timber window stiles with up to six panels folding in one direction.

A low profile concealed bottom guide channel provides hassle-free installation and greater visual appeal.

Weatherfold Window hangers are cast 316 marine grade stainless steel with precision stainless steel bearings and nylon outer tyres.

Door Specification

Track System:	Weatherfold 4s Window 35
Max Panel Height	1800mm
Max Panel Weight	35kg
Max Panel Width	1000mm
Panel Thickness	35mm
Max Number of Panels	6 each way

Hardware Specification

Track:	120
Material	Aluminium
Finish	Clear Anodised
Standard Lengths	2000mm, 3000mm, 4000mm and 6000mm

Bottom Guide Channel:	96W
Recessed Channel	Aluminium
Material	Clear Anodised
Finish	2000mm, 3000mm, 4000mm and 6000mm
Standard Lengths	

Hanger Sets:	
End Hanger - Non-Mortice	Includes Hanger and Guide BWS2(L or R)-25SH
End Hanger - Mortice	Includes Hanger and Guide BWS2(L or R)-25SM
Intermediate Hanger Set	Includes Hanger, Guide and Hinge BWS4(L or R)-25SH

Pivot Set:	
Top and Bottom Pivots	BWS1F-25H

Hinge Sets:	
Hinge Handle Set	BW3-25H
Offset Hinge Handle Set	BW7-25H
Hinge Set	BW5-25H
Offset Hinge Set	BW6-25H

Accessories:	
Flush Pull	401
Flush Bolt Window Standard	360
Flush Bolt Window Lockable	360E
Flush Bolt Window Long	360L
Masonry Keeper	360RK
Frame Seal	AQ21
Window Seal	AQ48
Track Seal	PS13B

Finish options
Hardware: (SS) Satin Stainless, (PS) Polished Stainless
Flushbolts: (SN) Satin Nickel, (PN) Polished Nickel



