

IS7080, IS7080si



The IS7080 and IS7080si are aesthetically designed, compact perimeter seals, proven to be effective acoustic, cold smoke, light and weather seals. Both can be installed in lieu of a door stop on both steel and timber door frames (where frames are non fire-rated). The fixing holes are pre-drilled and slotted to allow the seal to be adjusted and positioned accurately. A decorative cover strip is supplied to conceal fixings.

The IS7080si version (silicone gasket) has been successfully tested on proprietary fire door assemblies (mounted on a 25mm frame stop). Also available in antimicrobial.

Gap size

- Min. 0mm / max. 10mm

Door set standard lengths

- Single: 1 x 1000mm, 2 x 2100mm
- Long Single: 1 x 1000mm, 2 x 2750mm
- Double: 3 x 2100mm
- Long Double: 1 x 2100mm, 2 x 2750mm

Standard lengths

- 1000mm
- 2250mm
- Also available in: 250mm increments from 1000mm to 5000mm

IS7080 standard colour

- Silver anodised aluminium with black gasket and grey cover strip

IS7080si standard colours

- Silver anodised aluminium with grey silicone gasket and grey cover strip
- Black anodised aluminium with black silicone gasket and black cover strip

Fixing

- When fixing IS7080 and IS7080si to rebated frames of single doors, specify a long back set door latch

Approval/s

- IS7080si fire tested to AS1530 Part 4 in accordance with AS1905 Part 1
-  Certifications GVI1.R26629, GVWZ.R26629, GWWZ7.R26629
- Medium temperature smoke leakage approvals to AS1530 Part 7, compliant with AS6905 on proprietary door assemblies (silicone version)
- Acoustically tested in accordance with AS1191, ISO140.3 and ISO10140-2

