

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium® Adhesive

Print date: 13.06.2014

Product code: 001415

Page 1 of 8

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Identium® Adhesive

#### Further trade names

Identium® Adhesive

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesive for Identium® impression materials (Vinylsiloxanether®). Adheres to metals and acrylics.  
For dental use.

### 1.3. Details of the supplier of the safety data sheet

Company name:	Kettenbach GmbH & Co. KG		
Street:	Im Heerfeld 7		
Place:	D-35713 Eschenburg		
Telephone:	+ 49(0) 2774/705-0	Telefax:	+49 (0)2774/705-87
e-mail:	info@kettenbach.de		
Contact person:	Regulatory Affairs Manager	Telephone:	+49 (0)2774/705-0
Internet:	www.kettenbach.de		
Responsible Department:	Regulatory Affairs		

### 1.4. Emergency telephone number:

+49 (0)30 30686790 (English/German)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Indications of danger: Xn - Harmful, Xi - Irritant  
R phrases:  
Flammable.  
Harmful by inhalation.  
Irritating to eyes.  
Repeated exposure may cause skin dryness or cracking.

#### GHS classification

Hazard categories:  
Flammable liquid: Flam. Liq. 3  
Skin corrosion/irritation: Skin Irrit. 2  
Serious eye damage/eye irritation: Eye Irrit. 2  
Specific target organ toxicity - single exposure: STOT SE 3  
Hazard Statements:  
Flammable liquid and vapour.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

### 2.2. Label elements

#### Hazardous components which must be listed on the label

ethyl acetate

Signal word: Warning

Pictograms: GHS02-GHS07

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium® Adhesive

Print date: 13.06.2014

Product code: 001415

Page 2 of 8



#### Hazard statements

- |      |                                    |
|------|------------------------------------|
| H226 | Flammable liquid and vapour.       |
| H315 | Causes skin irritation.            |
| H319 | Causes serious eye irritation.     |
| H336 | May cause drowsiness or dizziness. |

#### Precautionary statements

- |                |  |
|----------------|--|
| P210           | Keep away from heat/sparks/open flames/hot surfaces. - No smoking.   |
| P240           | Ground/bond container and receiving equipment.   |
| P243           | Take precautionary measures against static discharge.  |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |

#### 2.3. Other hazards

Highly flammable.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation based on silicone resin in organic solvents.

##### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
205-500-4	ethyl acetate	25-50%
141-78-6	F - Highly flammable, Xi - Irritant R11-36-66-67	
607-022-00-5	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
215-535-7	xylene	5-10%
1330-20-7	Xn - Harmful, Xi - Irritant R10-20/21-38	
601-022-00-9	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315	
202-849-4	ethylbenzene	0-5%
100-41-4	F - Highly flammable, Xn - Harmful R11-20	
601-023-00-4	Flam. Liq. 2, Acute Tox. 4; H225 H332	
227-006-8	Butyl titanate (IV)	0-5 %
5593-70-4	Xi - Irritant R10-38-41	

Full text of R and H phrases: see Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### After inhalation

Provide fresh air. Seek medical attention if problems persist.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium® Adhesive

Print date: 13.06.2014

Product code: 001415

Page 3 of 8

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

#### After ingestion

Rinse mouth immediately and drink large quantities of water. Immediately get medical attention.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>). Sand. Extinguishing powder.

#### Extinguishing media which must not be used for safety reasons

Water.

### 5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes. Vapours may form explosive mixtures with air.

### 5.3. Advice for firefighters

Extinguishing materials should be selected according to the surrounding area.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Wear personal protection equipment.

### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

### 6.3. Methods and material for containment and cleaning up

Wipe up with absorbent material (eg. cloth, fleece). Do not rinse down with water.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Keep container tightly closed and in a well-ventilated place.

#### Advice on protection against fire and explosion

Take precautionary measures against static discharges.

#### Further information on handling

Provide fresh air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

#### Further information on storage conditions

Protect against: heat.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium® Adhesive

Print date: 13.06.2014

Product code: 001415

Page 4 of 8

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-	-	TWA (8 h)	WEL
		400	-	-	STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441	-	TWA (8 h)	WEL
		125	552	-	STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220	-	TWA (8 h)	WEL
		100	441	-	STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

#### 8.2. Exposure controls

##### Protective and hygiene measures

Avoid contact with skin, eye and clothing. Change contaminated clothing. Wash hands before breaks and at the end of work. Protect skin by using skin protective cream.

##### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Provide adequate ventilation.

##### Hand protection

Type of chemical protective gloves to choose depends on the concentration and quantity of dangerous substances as well as on work place specifications.

Hand protection: Suitable material: Butyl rubber.

##### Eye protection

Framed glasses.

##### Skin protection

Wear suitable protective clothing.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	blue
Odour:	characteristic

#### Test method

##### Changes in the physical state

Boiling point:	>77 °C
Flash point:	> -4 °C
Lower explosion limits:	2,1 vol. %
Upper explosion limits:	11,5 vol. %
Ignition temperature:	> 400 °C
Vapour pressure: (at 20 °C)	< 102 hPa
Density (at 20 °C):	1,05 - 1,1 g/cm <sup>3</sup>

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium® Adhesive

Print date: 13.06.2014

Product code: 001415

Page 5 of 8

Water solubility:  
(at 20 °C) practically insoluble

#### 9.2. Other information

Formation of potentially explosive vapor/air mixtures is possible.

### SECTION 10: Stability and reactivity

#### 10.4. Conditions to avoid

None by intended use.

#### 10.5. Incompatible materials

none/none

#### 10.6. Hazardous decomposition products

none/none

#### Further information

Highly flammable. Vapours may form explosive mixtures with air.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

Irritant effect on the skin: Not an irritant.

Irritant effect on the eye: irritant.

Sensitization: no danger of sensitization.

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
1330-20-7	xylene				
	dermal	ATE	1100 mg/kg		
	inhalative vapour	ATE	11 mg/l		
	inhalative aerosol	ATE	1,5 mg/l		
100-41-4	ethylbenzene				
	oral	LD50	3500 mg/kg	Rat	GESTIS
	dermal	LD50 mg/kg	15400	Rabbit	GESTIS
	inhalative (4 h) vapour	LC50	17,2 mg/l	Rat	
	inhalative aerosol	ATE	1,5 mg/l		

#### Additional information on tests

Preparation not tested. No data available.

#### Further information

Harmful by inhalation and if swallowed.

Hazards identification: Nausea. Headache. Vapours may cause drowsiness and dizziness.

After skin contact: Has de-greasing effect on the skin.

Following eye contact: Irritant.

Harmful: may cause lung damage if swallowed.

### SECTION 12: Ecological information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium® Adhesive

Print date: 13.06.2014

Product code: 001415

Page 6 of 8

#### 12.1. Toxicity

CAS No	Chemical name				
	Aquatic toxicity	Method	Dose	h	Species
100-41-4	ethylbenzene				
	Acute algae toxicity	ErC50	3,6 mg/l	96	GESTIS

#### 12.3. Bioaccumulative potential

##### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-41-4	ethylbenzene	3,15

#### Further information

Leakage into the environment must be prevented.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Do not remove with domestic waste. Do not empty into drains or the aquatic environment. Waste disposal according to official state regulations.

##### Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances  
Classified as hazardous waste.

##### Waste disposal number of used product

200399 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; other municipal wastes; municipal wastes not otherwise specified

##### Contaminated packaging

Cleaned containers may be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number:** 1173  
**14.2. UN proper shipping name:** ETHYL ACETATE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Limited quantity: 1 L  
Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium® Adhesive

Print date: 13.06.2014

Product code: 001415

Page 7 of 8

#### Other applicable information (land transport)

Category of transportation: 2

Tunnelrestrictioncode: D1E

E2

#### Marine transport (IMDG)

**14.1. UN number:** 1173

**14.2. UN proper shipping name:** ETHYL ACETATE

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



Special Provisions: -

Limited quantity: 1 L

EmS: F-E, S-D

#### Other applicable information (marine transport)

E2

#### Air transport (ICAO)

**14.1. UN number:** 1173

**14.2. UN proper shipping name:** ETHYL ACETATE, mixture

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



Limited quantity Passenger: 1 L

IATA-packing instructions - Passenger: 305

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 307

IATA-max. quantity - Cargo: 60 L

#### Other applicable information (air transport)

Passenger-LQ: Y305

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulatory information

Water contaminating class (D): 2 - water contaminating

### SECTION 16: Other information

#### Full text of R phrases referred to under Sections 2 and 3

- |       |   |
|-------|---|
| 10    | Flammable.                                      |
| 11    | Highly flammable.                               |
| 20    | Harmful by inhalation.                          |
| 20/21 | Harmful by inhalation and in contact with skin. |
| 36    | Irritating to eyes.                             |

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Identium® Adhesive

Print date: 13.06.2014

Product code: 001415

Page 8 of 8

- |    |   |
|----|---|
| 38 | Irritating to skin.                                   |
| 41 | Risk of serious damage to eyes.                       |
| 66 | Repeated exposure may cause skin dryness or cracking. |
| 67 | Vapours may cause drowsiness and dizziness.           |

#### Full text of H statements referred to under Sections 2 and 3

- |      |                                     |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour.        |
| H312 | Harmful in contact with skin.       |
| H315 | Causes skin irritation.             |
| H319 | Causes serious eye irritation.      |
| H332 | Harmful if inhaled.                 |
| H336 | May cause drowsiness or dizziness.  |

#### Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*