



# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture Tru-Grit  
 Registration number -  
 Synonyms None.  
 Product Code 1200  
 Issue date 10-10-2014  
 Version number 02  
 Revision date 09-08-2015  
 Supersedes date 06-24-2015

**Distributor in New Zealand**

Pacer Car Clean Products NZ LTD  
 33 Ha Crescent Wiri  
 Auckland, New Zealand  
 Telephone: +64 9 25000 91  
 Fax: +64 9 25000 92  
 Web: :www.pacer.co.nz

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Compound, Polishing Creme  
 Uses advised against None known.

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

Company name Malco Products, Inc.  
 Address 361 Fairview Ave  
 Barberton, OH 44203  
 US

**24hr Emergency Assistance in New Zealand**

National Poison Control Center: 0800 Poison [764 766]

#### Division

Telephone Phone 800-253-2526  
 Fax 330-777-8317  
 e-mail msdsinfo@malcopro.com  
 Contact person Not available.

1.4. Emergency telephone number Phone 1-800-424-9300

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

#### Health hazards

Specific target organ toxicity - repeated exposure Category 1 H372 - Causes damage to organs through prolonged or repeated exposure.

Hazard summary Causes damage to organs through prolonged or repeated exposure. Occupational exposure to the substance or mixture may cause adverse health effects.

### 2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Solvent Naphtha (Petroleum), Medium Aliph.



#### Hazard pictograms

Signal word Danger

#### Hazard statements

H372 Causes damage to organs through prolonged or repeated exposure.

#### Precautionary statements

Prevention P260 Do not breathe mist or vapor.

P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
Response	
P314	Get medical advice/attention if you feel unwell.
Storage	Store away from incompatible materials.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental label information	None.
2.3. Other hazards	None known.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Solvent Naphtha (Petroleum), Medium Aliph.	10 - < 20	64742-88-7 265-191-7	-	649-405-00-X	
Classification:	Asp. Tox. 1;H304, STOT RE 1;H372				

Other components below reportable levels 90 - 100

##### List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

Composition comments The full text for all R- and H-phrases is displayed in section 16. The full text for all H-statements is displayed in section 16.

### SECTION 4: First aid measures

##### General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

##### 4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

##### 4.2. Most important symptoms and effects, both acute and delayed

Prolonged exposure may cause chronic effects.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

### SECTION 5: Firefighting measures

##### General fire hazards

No unusual fire or explosion hazards noted.

##### 5.1. Extinguishing media

Suitable extinguishing media Powder. Alcohol resistant foam. Carbon dioxide (CO2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

##### 5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

##### 5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures Move containers from fire area if you can do so without risk.

##### Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel Keep unnecessary personnel away. Do not breathe mist or vapor. For personal protection, see section 8 of the SDS.
- For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

### 6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

### 6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Provide adequate ventilation. Do not breathe mist or vapor. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	MAK	5 mg/m3	Respirable fraction.
		5 mg/m3	Respirable fume.
	STEL	10 mg/m3	Inhalable fraction.
		20 mg/m3	Inhalable fraction.
		10 mg/m3	Respirable fume.
10 mg/m3	Respirable fraction.		

Belgium. Exposure Limit Values.

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Mist.
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	Vapor.

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value	Form
Aluminum Silicate (CAS 66402-68-4)	TWA	6 mg/m3	Inhalable fraction.
		3 mg/m3	Respirable fraction.
KEROSENE (CAS 8008-20-6)	TWA	300 mg/m3	

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	MAC	4 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Glycerol (CAS 56-81-5)	MAC	10 mg/m3	

## Czech Republic. OELs. Government Decree 361

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	0,1 mg/m3	Respirable dust.
Glycerol (CAS 56-81-5)	Ceiling	15 mg/m3	Mist.
	TWA	10 mg/m3	Mist.

## Denmark. Exposure Limit Values

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TLV	5 mg/m3	Total
		2 mg/m3	Respirable.

## Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	

## Finland. Workplace Exposure Limits

Components	Type	Value	
Glycerol (CAS 56-81-5)	TWA	20 mg/m3	

## France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	VME	10 mg/m3	
Glycerol (CAS 56-81-5)	VME	10 mg/m3	Aerosol.

## Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	4 mg/m3	Inhalable dust.
		1,5 mg/m3	Respirable dust.
Glycerol (CAS 56-81-5)	TWA	50 mg/m3	Inhalable fraction.

## Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.

## Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	5 mg/m3	Inhalable
		10 mg/m3	Respirable.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	

## Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	6 mg/m3	Respirable.

## Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value	
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	10 mg/m3	

## Ireland. Occupational Exposure Limits

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Mist.

## Italy. Occupational Exposure Limits

Components	Type	Value	Form
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m <sup>3</sup>	Non-aerosol.

## Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	6 mg/m <sup>3</sup> 4 mg/m <sup>3</sup>	Decomposition aerosol.

## Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TLV	10 mg/m <sup>3</sup>	

## Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	2,5 mg/m <sup>3</sup>	Inhalable fraction.
Glycerol (CAS 56-81-5)	TWA	1,2 mg/m <sup>3</sup>	Respirable fraction.
KEROSENE (CAS 8008-20-6)	STEL	10 mg/m <sup>3</sup>	Inhalable fraction.
	TWA	300 mg/m <sup>3</sup>	
	TWA	100 mg/m <sup>3</sup>	

## Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	10 mg/m <sup>3</sup>	
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m <sup>3</sup>	Non-aerosol.

## Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	STEL	5 mg/m <sup>3</sup>	Aerosol.
	TWA	1,2 ppm	Aerosol.
		2 mg/m <sup>3</sup>	Aerosol.
		0,5 ppm	Aerosol.

## Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	4 mg/m <sup>3</sup>	Inhalable fraction.
		1,5 mg/m <sup>3</sup>	Respirable fraction.
		0,1 mg/m <sup>3</sup>	
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	

## Spain. Occupational Exposure Limits

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	10 mg/m <sup>3</sup>	
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	Mist.

## Sweden. Occupational Exposure Limit Values

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	5 mg/m <sup>3</sup>	Total dust.
		2 mg/m <sup>3</sup>	Respirable dust.

## Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	STEL	24 mg/m <sup>3</sup>	Fume and respirable dust.
	TWA	3 mg/m <sup>3</sup>	Respirable dust.

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
		3 mg/m <sup>3</sup>	Fume and respirable dust.
Glycerol (CAS 56-81-5)	STEL	100 mg/m <sup>3</sup>	Inhalable dust.
	TWA	50 mg/m <sup>3</sup>	Inhalable dust.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	TWA	4 mg/m <sup>3</sup>	Respirable dust.
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	Inhalable dust.
		10 mg/m <sup>3</sup>	Mist.

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no-effect level (DNEL) Not available.

Predicted no effect concentrations (PNECs) Not available.

## 8.2. Exposure controls

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

- Other Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls Environmental manager must be informed of all major releases.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Viscous.
Physical state	Liquid.
Form	Liquid. Cream.
Color	Yellow.
Odor	Vanilla
Odor threshold	Not available.
pH	8,2 - 9,2
Melting point/freezing point	Not available.
Initial boiling point and boiling range	3734,24 °F (2056,8 °C) estimated
Flash point	145,0 °F (62,8 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0,7 % estimated

Flammability limit - upper (%)	5 % estimated
Vapor pressure	0,06 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Solubility (other)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	594,01 °F (312,23 °C) estimated
Decomposition temperature	Not available.
Viscosity	150000 - 295000 cP
Viscosity temperature	68 °F (20 °C)
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
9.2. Other information	
Density	10,64 lbs/gal
Kinematic viscosity	156703 cSt
Kinematic viscosity temperature	68 °F (20 °C)
VOC (Weight %)	16,95 %

## SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidizing agents. Chlorine.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

## SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
Information on likely routes of exposure	
Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	Exposure may cause temporary irritation, redness, or discomfort.
11.1. Information on toxicological effects	
Acute toxicity	No data available.
Skin corrosion/irritation	Due to partial or complete lack of data the classification is not possible.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory sensitization	Due to partial or complete lack of data the classification is not possible.
Skin sensitization	Due to partial or complete lack of data the classification is not possible.
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.
Carcinogenicity	Due to partial or complete lack of data the classification is not possible.
Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard	Due to partial or complete lack of data the classification is not possible.
Mixture versus substance information	No information available.
Other information	Not available.

## SECTION 12: Ecological information

12.1. Toxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
12.2. Persistence and degradability	No data is available on the degradability of this product.
12.3. Bioaccumulative potential	No data available.
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	Not available.
12.6. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

Not regulated as dangerous goods.

### RID

Not regulated as dangerous goods.

### ADN

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

New Zealand ERMA Register of Hazardous Substances HSNO: HSR002525 Cleaning products (Combustible) Group Standard 2006
---

## SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended  
Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended  
Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended  
Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended  
Not listed.



Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended  
Not listed.  
Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended  
Not listed.  
Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended  
Not listed.  
Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA  
Not listed.

#### Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended  
Not listed.

#### Restrictions on use

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

#### Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances

Not listed.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended

Solvent Naphtha (Petroleum), Medium Aliph. (CAS 64742-88-7)

Directive 94/33/EC on the protection of young people at work, as amended

Solvent Naphtha (Petroleum), Medium Aliph. (CAS 64742-88-7)

#### Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

#### National regulations

Follow national regulation for work with chemical agents.

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

### SECTION 16: Other information

#### List of abbreviations

Not available.

#### References

Not available.

#### Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

#### Full text of any H-statements not written out in full under Sections 2 to 15

H304 May be fatal if swallowed and enters airways.  
H372 Causes damage to organs through prolonged or repeated exposure.

#### Revision information

This document has undergone significant changes and should be reviewed in its entirety.

#### Training information

Follow training instructions when handling this material.

#### Disclaimer

Presta Products cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.