SAFETY DATA SHEET



1. Identification

Product identifier Radiant VOC Compliant Dressing

Other means of identification

Product Code 1342 Recommended use Dressing Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Website

Company name Presta Products

Address 361 Fairview Ave

Barberton, OH 44203

United States

Phone **Telephone**

Fax 330-777-8317

www.prestaproducts.com

E-mail msdsinfo@malcopro.com

Technical Department Contact person

24hr Emergency Assistance in New Zealand National Poison Control Center: **Emergency phone number** Phone 1-800-424-9300

0800 Poison [764 766]

33 Ha Crescent, Wiri,

Tel:

Fax:

Email:

Web:

Auckland, New Zealand

DISTRIBUTOR IN NEW ZEALAND:

Pacer - Car Clean Products NZ Ltd

+64 9 25000 91

+64 9 25000 92

sales@pacer.co.nz

www.pacer.co.nz

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2 **Health hazards** Acute toxicity, oral Category 5

> Aspiration hazard Category 1

800-253-2526

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements





Signal word Danger

Hazard statement Highly flammable liquid and vapor. May be harmful if swallowed. May be fatal if swallowed and

enters airways.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary

measures against static discharge.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or Response

hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information 96.7% of the mixture consists of component(s) of unknown acute inhalation toxicity. 32.7% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 99.7% of

the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

1342 Version #: 04 Revision date: 08-04-2023 Issue date: 05-11-2018

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Light		64742-47-8	60 - < 70
Ethylene Glycol Monobutylether		111-76-2	3 - < 5
Other components below reportable	e levels		30 - < 40

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contactTake off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor. Will burn if involved in a fire.

Do not use water jet as an extinguisher, as this will spread the fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Value	
Ethylene Glycol Monobutylether (CAS 111-76-2)	PEL	240 mg/m3		
		50 ppm		
US. ACGIH Threshold Limit Value	ies			
Components	Туре	Value		
Ethylene Glycol Monobutylether (CAS 111-76-2)	TWA	20 ppm		
US. NIOSH: Pocket Guide to Ch	emical Hazards			
Components	Туре	Value		
Ethylene Glycol Monobutylether (CAS 111-76-2)	TWA	24 mg/m3		

5 ppm

Biological limit values

ACGIH Biological Exposure Indices						
Components	Value	Determinant	Specimen	Sampling Time		
Ethylene Glycol Monobutylether (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*		

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Ethylene Glycol Monobutylether (CAS 111-76-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Ethylene Glycol Monobutylether (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Ethylene Glycol Monobutylether (CAS 111-76-2)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene Glycol Monobutylether (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene Glycol Monobutylether (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear.
Physical state Liquid.
Form Liquid.
Color Blue
Odor Solvent.
Odor threshold Not available.

none none

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point 135.0 °F (57.2 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.
Explosive limit - upper (%) Not available.

Vapor pressure 0.11 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 460.4 °F (238 °C) estimated

Decomposition temperature Not available.

Viscosity 10 cP

Viscosity temperature 68 °F (20 °C)

Other information

Density 7.17 lb/gal **Explosive properties** Not explosive.

Flammability class Combustible IIIB estimated

Oxidizing properties Not oxidizing.

VOC 3 % by weight

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidAvoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Inhalation

Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and Skin contact

prolonged. These effects have not been observed in humans.

Eye contact Direct contact with eyes may cause temporary irritation.

May be harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or Ingestion

vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components Species **Test Results**

Ethylene Glycol Monobutylether (CAS 111-76-2)

Acute

Dermal

LD50 Rabbit 400 mg/kg

Oral

LD50 Rat 560 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylene Glycol Monobutylether (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Material name: Radiant VOC Compliant Dressing 1342 Version #: 04 Revision date: 08-04-2023 Issue date: 05-11-2018 Components **Species Test Results**

Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic Acute

LC50 Rainbow trout.donaldson trout 2.9 mg/l, 96 hours Fish

(Oncorhynchus mykiss)

Ethylene Glycol Monobutylether (CAS 111-76-2)

Aquatic Acute

LC50 Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours Fish

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

Ethylene Glycol Monobutylether 0.83

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN1993 **UN** number

UN proper shipping name Flammable Liquids, N.O.S (Contains Petroleum Products)

Transport hazard class(es)

3 Class Subsidiary risk Packing group Ш

Environmental hazards

Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN1993 **UN** number

UN proper shipping name

Transport hazard class(es)

Flammable Liquids, N.O.S (Contains Petroleum Products)

Class 3 Subsidiary risk Ш **Packing group Environmental hazards** No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1993

UN proper shipping name Transport hazard class(es)

Flammable Liquids, N.O.S (Contains Petroleum Products)

Class 3 Subsidiary risk Ш Packing group

Environmental hazards

Marine pollutant No. EmS Not assigned.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

NEW ZEALAND:

Cleaning Products Flammable Group

HSR002528

Standard 2020

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)One or more components of the mixture are not on the TSCA 8(b) inventory

or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

nical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Acute toxicity (any route of exposure)

Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

Material name: Radiant VOC Compliant Dressing

sps us 7 / 8

1342 Version #: 04 Revision date: 08-04-2023 Issue date: 05-11-2018

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethylene Glycol Monobutylether (CAS 111-76-2)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)*CanadaDomestic Substances List (DSL)YesUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 05-11-2018

 Revision date
 08-04-2023

Version # 04

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Presta Products cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or

expense due to improper use.

Revision information Hazard(s) identification: Response

Composition / Information on Ingredients: Ingredients Exposure controls/personal protection: Respiratory protection Transport Information: Material Transportation Information

HazReg Data: International Inventories

Material name: Radiant VOC Compliant Dressing

SDS US