



# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture Ultra 2-Step Finishing Polish  
Registration number -  
Synonyms None.  
Product Code 1394  
Issue date 06-30-2015  
Version number 05  
Revision date 01-22-2019  
Supersedes date 05-18-2017

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Compound, Polishing Creme  
Uses advised against None known.

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

Company name Presta Products  
Address 361 Fairview Ave  
Barberton, OH 44203  
US

#### Division

Telephone Phone 800-253-2526  
Fax 330-777-8317

e-mail msdsinfo@malcopro.com

Contact person Not available.

1.4. Emergency telephone number Phone 1-800-424-9300

#### Distributor in New Zealand:

Pacer Car Clean Products NZ LTD  
33 Ha Crescent Wiri,  
Auckland, New Zealand  
Telephone: +64 9 25000 91  
Fax: +64 9 25000 92  
Web: www.pacer.co.nz

#### 24hr Emergency Assistance in New Zealand:

National Poison Control Center:  
0800 Poison [764 766]

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Health hazards

Specific target organ toxicity - repeated exposure	Category 2	H373 - May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.

**Hazard summary** Combustible. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. Occupational exposure to the substance or mixture may cause adverse health effects.

#### Hazard Summary (according to Dangerous Substances Directive)

**Physical hazards** Not classified for physical hazards.  
**Health hazards** Not classified for health hazards.  
**Environmental hazards** Not classified for hazards to the environment.  
**Specific hazards** None known.  
**Main symptoms** Aspiration may cause pulmonary edema and pneumonitis. Prolonged exposure may cause chronic effects.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

**Contains:** Distillates (Petroleum), Hydrotreated Light, Solvent Naphtha (Petroleum), Medium Aliph.

## Hazard pictograms



### Signal word

Danger

### Hazard statements

H304  
H373

May be fatal if swallowed and enters airways.  
May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements

#### Prevention

P260

Do not breathe mist or vapor.

#### Response

P301 + P310  
P331  
P314

IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
Do NOT induce vomiting.  
Get medical advice/attention if you feel unwell.

#### Storage

P405

Store locked up.

#### Disposal

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Supplemental label information** None.

**2.3. Other hazards** Not a PBT or vPvB substance or mixture. Combustible.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (Petroleum), Hydrotreated Light	10 - < 20	64742-47-8 265-149-8	-	649-422-00-2	
<b>Classification:</b>	Asp. Tox. 1;H304				
Solvent Naphtha (Petroleum), Medium Aliph.	5 - < 10	64742-88-7 265-191-7	-	649-405-00-X	
<b>Classification:</b>	Asp. Tox. 1;H304, STOT RE 1;H372				
Other components below reportable levels	80 - < 90				

#### List of abbreviations and symbols that may be used above

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

#: This substance has been assigned Union workplace exposure limit(s).

#: This substance has been assigned Community workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### Composition comments

The full text for all R- and H-phrases is displayed in section 16. The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

#### General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 4.1. Description of first aid measures

##### Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

##### Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

##### Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

##### Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

#### 4.2. Most important symptoms and effects, both acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Prolonged exposure may cause chronic effects.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

<b>General fire hazards</b>	Combustible. No unusual fire or explosion hazards noted.
<b>5.1. Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>5.2. Special hazards arising from the substance or mixture</b>	During fire, gases hazardous to health may be formed.
<b>5.3. Advice for firefighters</b>	
<b>Special protective equipment for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Special fire fighting procedures</b>	Cool containers exposed to heat with water spray and remove container, if no risk is involved.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.

## SECTION 6: Accidental release measures

<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.
<b>For emergency responders</b>	Keep unnecessary personnel away.
<b>6.2. Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.
<b>6.3. Methods and material for containment and cleaning up</b>	Use water spray to reduce vapors or divert vapor cloud drift.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use.
<b>6.4. Reference to other sections</b>	Not available.

## SECTION 7: Handling and storage

<b>7.1. Precautions for safe handling</b>	Do not breathe mist or vapor. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>	Store locked up. Keep away from heat and sources of ignition. Store in original tightly closed container.
<b>7.3. Specific end use(s)</b>	Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	MAK	5 mg/m3	Respirable fraction.
		5 mg/m3	Respirable fume.
		10 mg/m3	Inhalable fraction.
	STEL	20 mg/m3	Inhalable fraction.
		10 mg/m3	Respirable fume.
		10 mg/m3	Respirable fraction.

##### Belgium. Exposure Limit Values.

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Mist.

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

Components	Type	Value	Form
Aluminum Silicate (CAS 66402-68-4)	TWA	6 mg/m <sup>3</sup>	Inhalable fraction.
		3 mg/m <sup>3</sup>	Respirable fraction.

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	MAC	4 mg/m <sup>3</sup>	Respirable dust.
		10 mg/m <sup>3</sup>	Total dust.
Glycerol (CAS 56-81-5)	MAC	10 mg/m <sup>3</sup>	

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	0,1 mg/m <sup>3</sup>	Respirable dust.
Glycerol (CAS 56-81-5)	Ceiling	15 mg/m <sup>3</sup>	Mist.
	TWA	10 mg/m <sup>3</sup>	Mist.

**Denmark. Exposure Limit Values**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TLV	5 mg/m <sup>3</sup>	Total
		2 mg/m <sup>3</sup>	Respirable.

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	4 mg/m <sup>3</sup>	Respirable dust.
		10 mg/m <sup>3</sup>	Total dust.
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	

**Finland. Workplace Exposure Limits**

Components	Type	Value	Form
Glycerol (CAS 56-81-5)	TWA	20 mg/m <sup>3</sup>	

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	VME	10 mg/m <sup>3</sup>	
Glycerol (CAS 56-81-5)	VME	10 mg/m <sup>3</sup>	Aerosol.

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	4 mg/m <sup>3</sup>	Inhalable fraction.
		1,5 mg/m <sup>3</sup>	Respirable fraction.
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m <sup>3</sup>	Respirable aerosol fraction
		350 mg/m <sup>3</sup>	Vapor.
Glycerol (CAS 56-81-5)	TWA	50 ppm	Vapor.
		200 mg/m <sup>3</sup>	Inhalable fraction.
White Mineral Oil (Petroleum) (CAS 8042-47-5)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value	Form
Glycerol (CAS 56-81-5)	AGW	200 mg/m <sup>3</sup>	Inhalable fraction.
White Mineral Oil (Petroleum) (CAS 8042-47-5)	AGW	5 mg/m <sup>3</sup>	Respirable fraction.

**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	5 mg/m <sup>3</sup>	Inhalable
		10 mg/m <sup>3</sup>	Respirable.
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	6 mg/m <sup>3</sup>	Respirable.

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value	
Calcined Alumina (CAS 1344-28-1)	TWA	10 mg/m <sup>3</sup>	

**Ireland. Occupational Exposure Limits**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	4 mg/m <sup>3</sup>	Respirable dust.
		10 mg/m <sup>3</sup>	Total inhalable dust.
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	Mist.

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	6 mg/m <sup>3</sup>	Decomposition aerosol.
		4 mg/m <sup>3</sup>	

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value	
Calcined Alumina (CAS 1344-28-1)	TLV	10 mg/m <sup>3</sup>	

**Poland. MACs. Regulation regarding maximum permissible concentrations and intensities of harmful factors in the work environment, Annex 1**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	2,5 mg/m <sup>3</sup>	Inhalable fraction.
		1,2 mg/m <sup>3</sup>	Respirable fraction.
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	Inhalable fraction.

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Components	Type	Value	
Calcined Alumina (CAS 1344-28-1)	TWA	10 mg/m <sup>3</sup>	
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	STEL	5 mg/m <sup>3</sup>	Aerosol.
	TWA	2 mg/m <sup>3</sup>	Aerosol.

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	4 mg/m <sup>3</sup>	Inhalable fraction.
		1,5 mg/m <sup>3</sup>	Respirable fraction.
		0,1 mg/m <sup>3</sup>	
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	

**Spain. Occupational Exposure Limits**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	10 mg/m <sup>3</sup>	
Glycerol (CAS 56-81-5)	TWA	10 mg/m <sup>3</sup>	Mist.

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	5 mg/m3	Total dust.
		2 mg/m3	Respirable dust.

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	STEL	24 mg/m3	Fume and respirable dust.
	TWA	3 mg/m3	Fume and respirable dust.
		3 mg/m3	Respirable dust.
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)	STEL	700 mg/m3	
	TWA	350 mg/m3	
Glycerol (CAS 56-81-5)	STEL	100 mg/m3	Inhalable dust.
	TWA	50 mg/m3	Inhalable dust.
White Mineral Oil (Petroleum) (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable dust.

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value	Form
Calcined Alumina (CAS 1344-28-1)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.
Glycerol (CAS 56-81-5)	TWA	10 mg/m3	Mist.

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**8.2. Exposure controls**

**Appropriate engineering controls** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**General information** Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Skin protection**

- **Hand protection** Wear appropriate chemical resistant gloves.

- **Other** Use of an impervious apron is recommended.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Environmental exposure controls** Environmental manager must be informed of all major releases.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid. Viscous.
<b>Color</b>	Light grey

<b>Odor</b>	Pina Colada
<b>Odor threshold</b>	Not available.
<b>pH</b>	8,5
<b>Melting point/freezing point</b>	2741 °F (1505 °C) estimated
<b>Initial boiling point and boiling range</b>	4185,5 °F (2307,5 °C) estimated
<b>Flash point</b>	145,0 °F (62,8 °C)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	0,00002 hPa estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	20000 cP
<b>Viscosity temperature</b>	68 °F (20 °C)
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>9.2. Other information</b>	
<b>Density</b>	8,67 lbs/gal
<b>Kinematic viscosity</b>	31853 cSt
<b>Kinematic viscosity temperature</b>	68 °F (20 °C)
<b>VOC</b>	5 % By Weight

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Acids. Strong oxidizing agents. Chlorine.
<b>10.6. Hazardous decomposition products</b>	No hazardous decomposition products are known.

## SECTION 11: Toxicological information

<b>General information</b>	Occupational exposure to the substance or mixture may cause adverse effects.
<b>Information on likely routes of exposure</b>	
<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
<b>Symptoms</b>	Aspiration may cause pulmonary edema and pneumonitis.
<b>11.1. Information on toxicological effects</b>	
<b>Acute toxicity</b>	May be fatal if swallowed and enters airways.
<b>Skin corrosion/irritation</b>	Due to partial or complete lack of data the classification is not possible.

<b>Serious eye damage/eye irritation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Respiratory sensitization</b>	Due to partial or complete lack of data the classification is not possible.
<b>Skin sensitization</b>	Due to partial or complete lack of data the classification is not possible.
<b>Germ cell mutagenicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Carcinogenicity</b>	Due to partial or complete lack of data the classification is not possible.

**Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)**

Not listed.

<b>Reproductive toxicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - single exposure</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Mixture versus substance information</b>	No information available.
<b>Other information</b>	Not available.

## SECTION 12: Ecological information

**12.1. Toxicity** Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

Components	Species	Test Results
Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)		
<b>Aquatic</b>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		2,9 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

<b>12.2. Persistence and degradability</b>	No data is available on the degradability of this product.
<b>12.3. Bioaccumulative potential</b>	
<b>Partition coefficient n-octanol/water (log Kow)</b>	Not available.
<b>Bioconcentration factor (BCF)</b>	Not available.
<b>12.4. Mobility in soil</b>	No data available.
<b>12.5. Results of PBT and vPvB assessment</b>	Not a PBT or vPvB substance or mixture.
<b>12.6. Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

14.1. - 14.6.: Not regulated as dangerous goods.



**RID**

14.1. - 14.6.: Not regulated as dangerous goods.

**ADN**

14.1. - 14.6.: Not regulated as dangerous goods.

**IATA**

14.1. - 14.6.: Not regulated as dangerous goods.

**IMDG**

14.1. - 14.6.: Not regulated as dangerous goods.

**14.7. Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code** Not established.

**NEW ZEALAND:**

Class 3.1D	Combustible Liquid
Class 6.1E	Aspiration Hazard
Class 6.9B	Target Organ – Repeat
HSR002525	Cleaning Products (Combustible)

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

**Authorizations****Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use****Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Not listed.

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended**

Not listed.

**Other EU regulations****Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

Not listed.

**Other regulations**

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended. The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended.

**National regulations**

Follow national regulation for work with chemical agents.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information****List of abbreviations**

Not available.

**References**

Not available.

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any H-statements  
not written out in full under  
Sections 2 to 15**

H304 May be fatal if swallowed and enters airways.  
H372 Causes damage to organs through prolonged or repeated exposure.

**Revision information**

GHS: Classification

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

Presta Products cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.