



SLIK™

PAINT PROTECTANT SPRAY (2640)

DESCRIPTION

SLIK™ SiO₂ Paint Protectant Spray is a quick and easy-to-use spray-on drying agent, paint protectant, and gloss amplifier that can be applied wet or dry to all exterior vehicle surfaces, leaving a water beading, ultra-slick, hydrophobic layer of protection and a shiny, lasting finish for up to 60 days. This quick detailer also protects paint from sun damage with UV inhibitors.

DIRECTIONS

Wash vehicle prior to product application. If necessary, clay the paint surface of the vehicle prior to application. Spray SLIK SiO₂ PAINT PROTECTANT SPRAY onto the paint surface. SLIK can be applied on both wet and dry surfaces. Once applied to the vehicle, fold a microfiber towel into quarters and work the product into the paint, flipping the towel to buff to a slick shine. Repeat the process if preferred. Allowing the product to cure for a minimum of eight hours will help to achieve maximum performance.

FEATURES & BENEFITS

Easy to Use

Quick easy on, easy off formula on wet and dry vehicles

Versatile Application

Can be applied to wet and dry vehicles

Stunning Finish

Leaves a water-beading, ultra-slick, hydrophobic surface

UV Protection

Guards against the sun's harsh rays

Safe for Many Surfaces

Safe to use on all exterior vehicle surfaces

VOC Compliant

Adheres to regulations regarding volatile organic compounds

PACKAGE SIZES

6 – 16 oz.

Part number: 264016

4 – 1 Gallon

Part number: 264001