

BRUNOX® Turbo-Spray®

The only 5-function-spray with TURBOLINE

NSF
55283 H2

Approved for
food
processing

- Lubricant
- Anti-Corrosion
- Contact-Spray
- Maintenance Spray
- Rusted-Parts-Loosener



**technical
data sheet**



THE ONLY LIQUID TOOL

WITH TURBOLINE

FOR EVERYBODY AND FOR EVERYTHING

Lubricant, film thickness: 1 - 2 µm

It is a long-term lubricant because of a mixture of hydrocarbons with the Additive Turboline and stops squeaks.

Anti-Corrosion Protection, up to 6 months

Gives guaranteed anti-corrosion protection as it penetrates into all small crevices and hollows. A unique mix of hydrocarbon which ensures complete surface contact, it also ensures that the coating is of sufficient thickness for maximum protection.

Contact-Spray, Dielectric strength: UD: 45 KV eff-ED: 182 KV eff/cm

A very low surface-tension and therefore when applied to metal disperses water immediately. This property is particularly useful for electrical contacts, where short circuits can be removed or prevented.

Rusted-Parts-Loosener, free of PTFE, silicone and graphite

Excellent penetration qualities, caused of the capillary effect it penetrates into finest hair-line cracks and spaces as a result loosens tight mechanic connection in a very short time such as screws, ball-bearings, chains etc..

Maintenance Spray, neutral on varnish, rubber, plastic etc..

Loosens mineral dirt and dissolves organic dirt, as a result nearly all kinds of stains can be easily removed and does not attack surfaces at all.

