



Car Clean Products NZ Limited
 Ph + 64 9 250 0091 - Fax + 64 9 250 0092 - www.pacer.co.nz
 33 Ha Crescent, Wiri - P O Box 97 948 - Manukau – Auckland 2241 - New Zealand

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: Chassis Black Paint
 Product Code: CBP
 Product Use: Paint that sets hard and glossy, providing a tough coating designed to withstand stone chips and weathering.

New Zealand Supplier: Car Clean Products NZ Limited
 Address: 33 Ha Crescent
 Wiri
 Auckland

Telephone: 09 250 0091
 Fax Number: 09 250 0092

Emergency Telephone: 0800 POISON (0800 764 766)

Date of MSDS Preparation: August 2023

Section 2. Hazards Identification

Contains flammable hydrocarbon solvents.

Potential Health Effects



WARNING

H226 Flammable liquid and vapour
H302 Harmful if swallowed
H319 Causes serious eye irritation

Swallowed

Over exposure may result in the following conditions: slight eye, skin and respiratory irritation, dizziness, nausea, and/or loss of consciousness

Eyes

Will cause severe eye irritation

Skin

May cause irritation and blistering of skin with long-term

Inhalation Exposure
dizziness, nausea, headaches

Section 3. Composition / Information on Ingredients

Ingredients	Proportion (% mass)	CAS Number
Petroleum Naphtha	>20	8032-32-4
High Aromatic White Spirit	<20	64742-88-7
Gilsonite Powder	<15	12002-43-6
Methyl benzene	<15	108-88-3
Bitumen	<10	8052-42-4
Bentone SD1	>1	97952-68-6
Butyl Ethanoate	>1	123-86-4
Pinerez 225	>1	Not available

Section 4. First Aid Measures

Routes of Exposure:

Eye	Flush thoroughly with water for at least 15 minutes. If persistent irritation occurs, obtain medical attention
Skin	Remove contaminated clothing. Wash contact areas with soap and water. Seek medical attention if irritation persists
Ingestion	Do not induce vomiting. Administer vegetable oil. Seek medical attention
Inhalation	Remove to fresh air. If rapid recovery does not occur, obtain medical attention

Section 5. Fire Fighting Measures

Treat as for hydrocarbon fire

Suitable Extinguishing media	Foam, Carbon Dioxide, Dry Chemical, Water Spray
Fire and Explosion hazards	Flammable liquid. Vapour accumulation could flash and/or explode if ignited
Fire Fighting Instructions	Fire fighters must use recommended protective equipment and self-contained breathing apparatus. Cool storage drums with water spray

Hazchem code 2X

Section 6. Accidental Release Measures

Land Spill or Leaks Remove all containers to a detached area. Bund material (e.g. sand, earth, etc.). Transfer remaining product and solid absorbent materials to separate container for disposal. Dispose of waste at an appropriate waste disposal facility or incinerate.

Section 7. Handling and Storage

Handling Advice: Use in well ventilated area away from all ignition sources. Flammable liquid. Vapour accumulation could flash and/or explode if ignited

Storing Procedures: Store away from excessive heat, vapour accumulation, sparks, flames, or a build up of static electricity. Avoid contact with strong oxidisers

Section 8 Exposure Controls / Personal Protection

Engineering Controls: Use in well ventilated area away from all ignition sources

Personal Protective Equipment: Wear gloves and goggles for bulk handling and transfer.

Section 9 Physical and Chemical Properties

Appearance	Black liquid
Odour:	petroleum odour
Odour threshold	Data not available
pH	Neutral
Melting/Freezing point	Data not available
Initial boiling point, °C :	150 - 193
Flash Point by PMCC:	36 °C (ASTN D56, PMCCO)
Flammability	Data not available
Upper/Lower flammability limits	Data not available
Vapour Pressure @ 25°C, mmHg:	0 < 5
Vapour density	Data not available
Relative density	Data not available
Solubilities	Solvents, alcohols
Partition coefficient	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Kinematic viscosity	Data not available
Particle characteristics	Data not available

Section 10. Stability and Reactivity

Chemical Stability	Chemically stable. Will not self react or polymerise.
Conditions to Avoid	Excessive heat (>40°C).
Incompatibility	Segregate from strong oxidizers (peroxides, nitrates etc)
Hazardous Decomposition Products	Toxic fumes in a fire

Section 11 Toxicological Information

This product is toxic by ingestion, and inhalation.

Acute Oral Toxicity	LD ₅₀ Rat (oral) > 2000 mg /kg bw
Acute Dermal Toxicity	Harmful
Toxicological data	Not known to be mutagenic or carcinogenic

Section 12. Ecotoxicological Information

Environmental Precautions

Ecological Toxicity *Extremely toxic to soil and water organisms.*

Environmental Fate ;

Soil *Not biodegradable. Long term persistent toxin*

Water *Not biodegradable. Long term persistent toxin*

Environmental Exposure Limits EEL_{water} Not available

Section 13. Disposal Considerations

Disposal of residues of this product can be burnt or sent to an approved landfill. They must be prevented from entering the sewer or stormwater.

Containers must be crushed or punctured so that they cannot be used for any other purpose or sent to an approved landfill or exported from New Zealand. (see www.ermanz.govt.nz – Group Standards – surface coatings and colourants (flammable) for a complete description of disposal requirements).

Section 14 Transport Information

Road, Rail, Marine and Air Transport

UN No	:	1263
Class-primary	:	3
Packing Group	:	III

Proper Shipping Name : Paint

Section 15 Regulatory Information

Classification	3.1C,
Subclasses	6.1D, 6.3B, 6.4A, 9.1B
Hazchem Code	3Y
Group Standard	Surface Coatings and Colourants (flammable)
ERMA Approval No	HSR002662

Section 16 Other Information

The HSNO Regulations require a Location Test Certificate for storage of more than 500 L in containers > 5 L or 1500 L if containers are < 5 L or 250 L continuously open.
 Site signage is required for site storage of more than 1000 L
 An Emergency Response Plan is required for site storage of more than 10,000 L

Supplied in 4lt, 20lt. Code: CBP4, CBP20.

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand proprietor, Car Clean Products NZ Limited
 Phone: 09 250 0091, if further information is required.



Car Clean Products NZ Limited
Ph + 64 9 250 0091 - Fax + 64 9 250 0092 - www.pacer.co.nz
33 Ha Crescent, Wiri - P O Box 97 948 - Manukau – Auckland 2241 - New Zealand

CHASSIS BLACK PAINT

PURPOSE

Chassis Black Paint is an economical black bituminous paint that sets hard and glossy, providing a tough coating designed to withstand stone chips and weathering. Chassis Black Paint is ideally suited for use as a final finish after section repairs, welding joints and rust repairs to restore a new car look to used vehicles. Best applied over primed surfaces it confers waterproofing and sound deadening properties to the coated surface.

DIRECTIONS

Shake Well. The surface should be clean and dry - free of wax, dirt, grease, loose paint, rust, silicone and any other contamination. Apply Chassis Black Paint with a spray gun or brush. Remove any overspray immediately with Mineral Turpentine. If applying with a brush then thin Chassis Black Paint with Mineral Turpentine to slow the drying process.

WARNING

Harmful if swallowed, inhaled or absorbed through the skin. May cause skin and eye irritation.

GIVES OFF A HIGHLY FLAMMABLE VAPOUR.

Keep well away from heat, sparks and an open flame. Keep the container closed when not in use.

KEEP OUT OF REACH OF CHILDREN.