

TECHNICAL DATA SHEET

Phone: (09) 25000 91

Fax: (09) 25000 92

Email: sales@pacer.co.nz

DESCRIPTION:

Graffiti Remover is a cleaning agent to clean graffiti from non-porous painted and unpainted surfaces. Excellent cleaning properties for removing recently applied aerosol paints, grease, lipstick, crayon, felt markers, pen inks and other problem substances. Always test an inconspicuous area first.

DIRECTIONS:

A TEST PATCH: A small test patch in an inconspicuous area should be performed to ensure product performance. This will indicate time required for project completion, suitability of the product for the paint, substrate etc. The product is ready for use and not to be diluted. Cover and protect areas not to be cleaned including where the spray may travel. Apply with a spray bottle or a clean cloth. There may be some dwell time needed to soften the graffiti. Do not allow the application to stay on more than 15 mins. Note that when completed wash the cleaned area down with soapy water to remove the chemical residue.

APPLICATIONS:

Removal of aerosol paints, grease, lipstick, crayon, felt markers, pen inks and other problem substances on metal, wood and concrete surfaces.

PROPERTIES:

Clear liquid with flash point of 12°C

Available Sizes:



GR4



GR20



DANGER



Solvent Cleaning

DANGER

H224 Extremely flammable liquid and vapour

H301 Toxic if swallowed

H312 Harmful in contact with skin

H332 Harmful if inhaled

H315 Causes skin irritation

H319 Causes serious eye irritation



Mask



Gloves



Goggles



Clothing

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOUR. Harmful if swallowed. The single lethal dose for humans is approx. 250ml, however 100ml can be fatal. Symptoms of overexposure include: flushing, pulse rate decrease, blood pressure lowering, anaesthesia, narcosis, headaches, dizziness, mental depression nausea. Irritating to the eyes and can cause corneal burns. Irritating to the skin with prolonged exposure. It may result in dryness and cracking. Irritating to the respiratory tract. In high doses, this product has narcotic effects.

FIRST AID:

Eye Hold eyes open and flush with water for at least 15 minutes. Seek medical attention immediately.

Skin Immediately remove contaminated clothing and wash skin and clothes thoroughly with running water.

Ingestion Do not induce vomiting. Rinse mouth with water. If victim not breathing begin artificial respiration. Obtain medical attention.

Inhalation Remove to fresh air. If breathing is difficult, seek medical attention immediately.

If medical advice is needed have the product container/label at hand. In an emergency phone the National Poison Centre. (24 hrs): 0800 POISON[764 766].

UN 1993. Class 3. PG II. Hazchem 2[Y/E]

OUR VISION AND MISSION

To be the leading value-based provider to the market. We have a dedicated team to achieve excellence for our customers and a philosophy of total quality. We conduct business and create relationships in an ethical and sustainable manner with customers, our community and the environment. The value we provide our customers is the opportunity to increase profit through lower cost solutions that do not sacrifice quality or service.

ENVIRONMENTAL POLICY

Pacer is committed to leading the industry in minimising the impact of its activities on the environment. The key points of our strategy to achieve this are: Purpose built premises utilising energy efficient technology and rain water collection. Actively promoting recycling both internally and amongst our customers and suppliers. To develop and promote a product range to minimise the environmental impact of our products. We are constantly evaluating and looking at substituting to a more environmentally friendly composition of raw materials for our products. To meet or exceed all the environmental legislation that relates to our industry.

DISCLAIMER

The technical data and information provided, including the recommendations for applying & using our products, is given in good faith based on our current knowledge and experience and is believed to be accurate when applied under 'normal' conditions. In practice, the materials, surfaces or conditions are so varied that no warranty regarding the working results or any liability or guarantee can be inferred either from this information nor from a verbal consultation. It is recommended that the user makes his or her own tests to determine the suitability of the product for their own requirements.