# **TECHNICAL DATA SHEET**

Phone: (09) 25000 91

Fax: (09) 25000 92

Email: sales@pacer.co.nz

# **DESCRIPTION:**

Pacesol™ Super Premium Engine Degreaser is a super strength high quality solvent degreaser for removing oil, grease and grime. It is water-soluble and ideal for degreasing machinery, parts, and engines and suitable for de-waxing vehicles, removing tar and cleaning oil from concrete.

# **DIRECTIONS:**

Do not use when engine is hot. Spray onto surface, allow to penetrate, scrub if necessary and rinse with hot or cold water.

# **APPLICATIONS:**

Degreaser. Removing oil, grease and grime.

### **PROPERTIES:**

Brown liquid with a flash point of 36.5°C

#### **Available Sizes:**







PSOL4 PSOL20

PSOL9

### DANGER

H304 May be fatal if swallowed and enters airways

H312 Harmful in contact with skin

H332 Harmful if inhaled









**DANGER** 



**Engine Cleaning** 









DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOUR. Harmful if swallowed. Acute oral LD50 (rat) expected to be above 2000 mg/kg. Aspiration into the lungs may cause chemical pneumonitis which can be fatal. Mild eye irritant. May cause transitory pain and redness. Acute dermal LD50 (rat) expected to be above 2000 mg/kg. Slight skin irritant. Acute inhalational LC50 (rat) expected to be > 5 mg/l. May cause headache, dizziness, nausea, and narcosis if inhaled.

SAFETY PRECAUTIONS: Dispose of empty container in a safe manner. Keep well away from heat, sparks and open flame. Keep closed when not in use. Wear protective gloves and eye/face protection. Wash hands thoroughly after handling.

### FIRST AID:

Eye Flush with cold water for at least 15 minutes. Seek medical attention if problems persists.

Skin If skin contact causes irritation remove contaminated clothing and wash thoroughly with soap and water.

Ingestion Do not induce vomiting. Give nothing by mouth. If patient continues to be distressed seek medical attention immediately.

Ingestion Do not induce vomiting. Give nothing by mouth. If patient continues to be distressed seek medical attention immediately.

Inhalation Remove to fresh air. If breathing is difficult seek medical attention immediately.

If medical advice is needed have the product container/label at hand. In an emergency phone the National Poison Centre. (24 hrs): 0800 POISON[764 766]. UN1993. Class 3. PG III. Flammable Liquid N.O.S. Hazchem 3[Y].

#### **OUR VISION AND MISSION**

To be the leading value-based provider to the market. We have a dedicated team to achieve excellence for our customers and a philosophy of total quality. We conduct business and create relationships in an ethical and sustainable manner with customers, our community and the environment. The value we provide our customers is the opportunity to increase profit through lower cost solutions that do not sacrifice quality or service.

### **ENVIRONMENTAL POLICY**

Pacer is committed to leading the industry in minimising the impact of its activities on the environment. The key points of our strategy to achieve this are: Purpose built premises utilising energy efficient technology and rain water collection. Actively promoting recycling both internally and amongst our customers and suppliers. To develop and promote a product range to minimise the environmental impact of our products. We are constantly evaluating and looking at substituting to a more environmentally friendly composition of raw materials for our products. To meet or exceed all the environmental legislation that relates to our industry.

#### **DISCLAIMER**

The technical data and information provided, including the recommendations for applying & using our products, is given in good faith based on our current knowledge and experience and is believed to be accurate when applied under 'normal' conditions. In practice, the materials, surfaces or conditions are so varied that no warranty regarding the working results or any liability or guarantee can be inferred either from this information nor from a verbal consultation. It is recommended that the user makes his or her own tests to determine the suitability of the product for their own requirements.