



Car Clean Products NZ Limited
 Ph + 64 9 250 0091 - Fax + 64 9 250 0092 - www.pacer.co.nz
 33 Ha Crescent, Wiri - P O Box 97 948 - Manukau – Auckland 2241 - New Zealand

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: Texture Coating Bumper Paint
 Product Code: TC
 Product Use: Textured bumper paint for application by spray gun.

New Zealand Supplier: Car Clean Products NZ Limited
 Address: 33 Ha Crescent
 Wiri
 Auckland

Telephone: 09 250 0091
 Fax Number: 09 250 0092

Emergency Telephone: 0800 POISON (0800 764 766)

Date of MSDS Preparation: March 2019

Section 2. Hazards Identification

Contains flammable hydrocarbon solvents.

Potential Health Effects



DANGER

H225 Highly flammable liquid and vapour
H304 May be fatal if swallowed and enters airways
H312 Harmful in contact with skin
H319 Causes serious eye irritation
H332 Harmful if inhaled

Swallowed

Over exposure may result in the following conditions: slight eye, skin and respiratory irritation, dizziness, nausea, and/or loss of consciousness.

Eyes	Will cause severe eye irritation
Skin	May cause irritation and blistering of skin with long-term Exposure
Inhalation	dizziness, nausea, headaches

Section 3. Composition / Information on Ingredients

Ingredients	Proportion (% mass)	CAS Number
2-Propanol	<10	67-63-0
Methyl Benzol	<50	108-88-3
n-Butyl Acetate	<20	123-86-4
Solvent 100	<5	64742-95-6
Dimethylbenzene	<10	1330-20-7
Carbon Black	<10	1333-86-4
Acrylic Polymers	<15	Not Hazardous

Section 4. First Aid Measures

Routes of Exposure:

Eye	Flush thoroughly with water for at least 15 minutes. If persistent irritation occurs, obtain medical attention
Skin	Remove contaminated clothing. Wash contact areas with soap and water. Seek medical attention if irritation persists
Ingestion	Do not induce vomiting. Administer milk or water.. Seek medical attention
Inhalation	Remove to fresh air. If rapid recovery does not occur, obtain medical attention

Section 5. Fire Fighting Measures

Treat as for hydrocarbon fire

Suitable Extinguishing media	Foam, Carbon Dioxide, Dry Chemical, Water Spray
Fire and Explosion hazards	Flammable liquid. Vapour accumulation could flash and/or explode if ignited

Fire Fighting Instructions

Fire fighters must use recommended protective equipment and self-contained breathing apparatus. Cool storage drums with water spray
 Hazchem code 3YE

Section 6. Accidental Release Measures

Land Spill or Leaks Remove all containers to a detached area. Bund material (e.g. sand, earth, etc.). Transfer remaining product and solid absorbent materials to separate container for disposal. Dispose of waste at an appropriate waste disposal facility or incinerate.

Section 7. Handling and Storage

Handling Advice: Use in well ventilated area away from all ignition sources. Flammable liquid. Vapour accumulation could flash and/or explode if ignited

Storing Procedures: Store away from excessive heat, vapour accumulation, sparks, flames, or a build up of static electricity. Avoid contact with strong oxidisers

Section 8 Exposure Controls / Personal Protection

Engineering Controls: Use in well ventilated area away from all ignition sources

Personal Protective Equipment: Wear gloves and goggles for bulk handling and transfer.

Section 9 Physical and Chemical Properties

Appearance	Black liquid
Odour:	petroleum odour
Odour threshold	Data not available
pH	N/A
Melting/Freezing point	Data not available
Initial boiling point/range	110°C
Flash point	4°C
Flammability	Data not available
Upper/Lower flammability limits	Data not available
Vapour pressure	Data not available
Vapour density	Data not available
Relative density	Data not available
Solubility in water, % mass:	Slightly soluble
Partition coefficient	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Kinematic viscosity	Data not available
Particle characteristics	Data not available

Section 10. Stability and Reactivity

Chemical Stability	Chemically stable. Will not self react or polymerise.
Conditions to Avoid	Excessive heat (>40°C).
Incompatibility	Segregate from strong oxidizers (peroxides, nitrates etc)
Hazardous Decomposition Products	Toxic fumes in a fire

Section 11 Toxicological Information

This product is toxic by ingestion, and inhalation.

Acute Oral Toxicity	LD ₅₀ Rat (oral) > 2000 mg /kg bw
Acute Dermal Toxicity	Harmful
Toxicological data	Not known to be mutagenic or carcinogenic

Section 12. Ecotoxicological Information

Environmental Precautions

Ecological Toxicity *Extremely toxic to soil and water organisms.*

Environmental Fate ;

Soil *Not biodegradable. Long term persistent toxin*

Water *Not biodegradable. Long term persistent toxin*

Environmental Exposure Limits EEL_{water} Not available

Section 13. Disposal Considerations

Disposal of residues of this product can be burnt or sent to an approved landfill. They must be prevented from entering the sewer or stormwater.

Containers must be crushed or punctured so that they cannot be used for any other purpose or sent to an approved landfill or exported from New Zealand. (see www.ermanz.govt.nz – Group Standards – surface coatings and colourants (flammable) for a complete description of disposal requirements).

Section 14 Transport Information

Road, Rail, Marine and Air Transport

UN No : 1263

Class-primary : 3
 Packing Group : III
 Proper Shipping Name : Paint

Section 15 Regulatory Information

Classification 3.1B,
 Subclasses 6.1D, 6.3B, 6.4A, 9.1B
 Hazchem Code 3YE
 Group Standard Surface Coatings and Colourants (flammable)
 ERMA Approval No HSR002662

Section 16 Other Information

The HSNO Regulations require a Location Test Certificate for storage of more than 500 L in containers > 5 L or 1500 L if containers are < 5 L or 250 L continuously open.

Site signage is required for site storage of more than 1000 L

An Emergency Response Plan is required for site storage of more than 10,000 L

Supplied in 1lt, . Code: TC1

Supplied in 4lt, . Code: TC4

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand proprietor, Car Clean Products NZ Limited

Phone: 09 250 0091, if further information is required.

.....



Car Clean Products NZ Limited
Ph + 64 9 250 0091 - Fax + 64 9 250 0092 - www.pacer.co.nz
33 Ha Crescent, Wiri - P O Box 97 948 - Manukau - Auckland 2241- New Zealand

TEXTURE COAT BUMPER PAINT

Pacer Texture Coat Bumper Paint products a flexible textured black satin finish on rigid plastic bumpers and plastic parts. Not to be applied over bare plastic but to be applied over an existing primer or a sound paint finish (not enamel) using a spay gun with a 1.2 – 2.0mm fluid tip at 250-350kPa.

DIRECTIONS

Stir thoroughly! Existing sound paint should be sanded with P320-P400 and cleaned before and after sanding with Pacer Prepare It. New surfaces have to be primed with a plastic adhesion promoter. Texture Coat is ready for use but can be thinned up to 25% with Pacer General Purpose Thinners. Apply 2-4 wet coats allowing a flash off of 5-10 mins between coats. Drying is approx 1-3 hours air dry at 20C but can be considerably shortened by force drying.

WARNING

Flammable Liquid and Vapour. Harmful if swallowed, inhaled or absorbed through the skin. May cause skin and eye irritation. Wear safety equipment. Keep well away from heat, sparks, open flame. Keep closed when not in use. Use only non sparking tools.

GIVES OFF A HIGHLY FLAMMABLE VAPOUR.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID

If swallowed do not induce vomiting. Give large quantities of milk or water. Seek medical attention immediately. If inhaled move victim to fresh air. If breathing is difficult, seek medical attention immediately. In case of eye contact, hold eyes open and flush with water for at least 15 minutes. Seek medical attention immediately. If skin contact occurs, wash thoroughly with soap and water. In case of emergency call National Poison Centre [24 hours] 0800 POISON [764 766]

Contains Toluene less than 150gms/lit. UN1263. Hazchem 3YE