

# TEXTURE BUMPER COATING BLACK

**TECHNICAL DATA SHEET** 

Phone: (09) 25000 91

Fax: (09) 25000 92

Email: sales@pacer.co.nz

#### **DESCRIPTION:**

Texture Bumper Coating Black is a flexible textured black satin finish on rigid plastic bumpers and plastic parts. It is not to be applied over bare plastic but to be applied over an existing primer or a sound paint finish (not enamel) using a spay gun with a 1.2 - 2.0mm fluid tip at 250 -350kPa.

# **DIRECTIONS:**

Stir thoroughly! Existing sound paint should be sanded with P320-P400 and cleaned before and after sanding with Pacer Prepare It. New surfaces have to be primed with a plastic adhesion promoter. Texture Bumper Coating Black is ready for use but can be thinned up to 25% to 40% with Pacer General Purpose Thinners. Apply 2-4 wet coats allowing a flash off of 5-10 mins between coats. Drying is approx 1-3 hours air dry at 20 °C but can be considerably shortened by force drying.

## **APPLICATIONS:**

Texture bumper paint applied through a spray gun

## **PROPERTIES:**

Black liquid with a petroleum odour.

## **Available Sizes:**







TC4

#### **DANGER**

Highly flammable liquid and vapour H225

May be fatal if swallowed and enters airways H304

H312 Harmful in contact with skin

H319 Causes serious eye irritation

H332 Harmful if inhaled







DANGER



Body Shop





DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOUR. May be fatal if swallowed and enters airways. Over exposure may result in the following conditions: slight eye, skin and respiratory irritation, dizziness, nausea, and/or loss of consciousness. Will cause severe eye irritation. May cause irritation and blistering of skin with long-term exposure. May cause dizziness, nausea and headaches if inhaled.

SAFETY PRECAUTIONS: Keep well away from heat sparks/open flame. Keep closed when not in use. Use only non-sparking tools.

## FIRST AID:

Flush thoroughly with water for at least 15 minutes. If persistent irritation occurs, obtain medical attention

Remove contaminated clothing. Wash contact areas with soap and water. Seek medical attention if irritation persists. Skin Do not induce vomiting. Administer milk or water. Seek medical attention.

Inhalation Remove to fresh air. If rapid recovery does not occur, obtain medical attention.

If medical advice is needed have the product container/label at hand. In an emergency phone the National Poison Centre.(24 hrs): 0800 POISON[764 766].

UN 1263. Class 3. PG III. Paint. Hazchem 3[Y]E

## **OUR VISION AND MISSION**

To be the leading value-based provider to the market. We have a dedicated team to achieve excellence for our customers and a philosophy of total quality. We conduct business and create relationships in an ethical and sustainable manner with customers, our community and the environment. The value we provide our customers is the opportunity to increase profit through lower cost solutions that do not sacrifice quality or service.

#### **ENVIRONMENTAL POLICY**

Pacer is committed to leading the industry in minimising the impact of its activities on the environment. The key points of our strategy to achieve this are: Purpose built premises utilising energy efficient technology and rain water collection. Actively promoting recycling both internally and amongst our customers and suppliers. To develop and promote a product range to minimise the environmental impact of our products. We are constantly evaluating and looking at substituting to a more environmentally friendly composition of raw materials for our products. To meet or exceed all the environmental legislation that relates to our industry.

#### DISCLAIMER

The technical data and information provided, including the recommendations for applying & using our products, is given in good faith based on our current knowledge and experience and is believed to be accurate when applied under 'normal' conditions. In practice, the materials, surfaces or conditions are so varied that no warranty regarding the working results or any liability or guarantee can be inferred either from this information nor from a verbal consultation. It is recommended that the user makes his or her own tests to determine the suitability of the product for their own requirements