

TECHNICAL DATA SHEET

Phone: (09) 25000 91 Fax: (09) 25000 92

Email: sales@pacer.co.nz

TOLUENE

DESCRIPTION:

Toluene is mainly used in applications where a solvent with fast evaporation is required.

DIRECTIONS:

Cleaning: Spray or wipe onto surface, agitate to clean and wipe off with a clean cloth or allow to evaporate.

APPLICATIONS:

Solvent cleaning.

PROPERTIES:

Clear liquid with a flash point of 4.4°C

Available Sizes:



TOL20















DANGER

H224 Extremely flammable liquid and vapour

H302 Harmful if swallowed

H332 Harmful if inhaled

H317 May cause an allergic skin reaction

DANGER: DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOUR. Harmful if swallowed. This material will cause irritation to the throat and tube to the stomach and may cause nausea. Vomiting may cause the product to be aspirated to the lungs resulting in chemical pneumonitis. Will cause eye redness and swelling with a burning sensation and blurred vision. Irritating to the skin with prolonged exposure. It may result in dryness and cracking. Harmful by inhalation. Vapours will cause dizziness and drowsiness. There is a possibility of organ damage over prolonged use or exposure. Central Nervous System depression includes nausea, dizziness and possibly loss of consciousness, coma and even death.

SAFETY PRECAUTIONS: Keep well away from heat, sparks and open flame. Keep container well closed. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protections. Do not eat, drink or smoke whilst using. Avoid breathing vapour. Use with adequate ventilation. Dispose empty container in a safe manner.

FIRST AID:

Hold eyes open and flush with water for at least 15 minutes

Skin

Immediately remove contaminated clothing and wash skin and clothes thoroughly with running water.

Do not induce vomiting. Give glass of water. If victim not breathing begin artificial respiration. Obtain medical attention.

Inhalation Remove to fresh air. If breathing is difficult, seek medical attention immediately.

If medical advice is needed have the product container/label at hand. In an emergency phone the National Poison Centre (24 hrs): 0800 POISON[764 766].

UN 1294. Class 3. PG II. Toluene. Hazchem Code 3[Y]E.

To be the leading value-based provider to the market. We have a dedicated team to achieve excellence for our customers and a philosophy of total quality. We conduct business and create relationships in an ethical and sustainable manner with customers, our community and the environment. The value we provide our customers is the opportunity to increase profit through lower cost solutions that do not sacrifice quality or service.

Pacer is committed to leading the industry in minimising the impact of its activities on the environment. The key points of our strategy to achieve this are: Purpose built premises utilising energy efficient technology and rain water collection. Actively promoting recycling both internally and amongst our customers and suppliers. To develop and promote a product range to minimise the environmental impact of our products. We are constantly evaluating and looking at substituting to a more environmentally friendly composition of raw materials for our products. To meet or exceed all the environmental legislation that relates to our industry.

The technical data and information provided, including the recommendations for applying & using our products, is given in good faith based on our current knowledge and experience and is believed to be accurate when applied under 'normal' conditions. In practice, the materials, surfaces or conditions are so varied that no warranty regarding the working results or any liability or guarantee can be inferred either from this information nor from a verbal consultation. It is recommended that the user makes his or her own tests to determine the suitability of the product for their own requirements