

Car Clean Products NZ Limited
Ph + 64 9 250 0091 - Fax + 64 9 250 0092 - www.pacer.co.nz
33 Ha Crescent, Wiri - P O Box 97 948 - Manukau - Auckland 2241 - New Zealand

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: Xylol/Xylene

Product Code: XYL

Product Use: Industrial chemical

New Zealand Supplier: Car Clean Products NZ Limited

Address: 33 Ha Crescent

Wiri

Auckland

Telephone: 09 250 0091 Fax Number: 09 250 0092

Emergency Telephone: 0800 POISON (0800 764 766)

Date of MSDS Preparation: August 2023

Section 2. Composition / Information on Ingredients

Ingredients	Proportion (% mass)	CAS Number
Xylene	1	1330-20-7
Contains: Ethyl Benzene	<10.0	100-41-4

Section 3. Hazards Identification

Harmful if swallowed. Harmful if inhaled. Causes eye irritation. May cause an allergic skin reaction. Extremely flammable liquid and vapour. Harmful to aquatic life. This product is classified as hazardous under HSNO criteria.

Potential Health Effects

DANGER H224 Extremely flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

H302 Harmful if swallowed H332 Harmful if inhaled

H317 May cause an allergic skin reaction

Product Name: Xylol/Xylene Date of SDS: August 2023





Swallowed If swallowed, may cause lung damage on vomiting. Will cause

central nervous system depression. May cause discomfort on swallowing. Vapours will cause drowsiness and dizziness and

ingestion may result in headaches and nausea.

Eyes Will cause redness and swelling with a burning sensation and

blurred vision.

Skin Irritating to the skin with prolonged exposure. It may result in

dryness and cracking.

Inhalation Harmful by inhalation. Vapours will cause dizziness and

drowsiness. There is a possibility of organ damage over

prolonged use or exposure. Central Nervous System depression includes nausea, dizziness and possibly loss of consciousness.

Section 4. First Aid Measures

Routes of Exposure:

Eye Hold eyes open and flush with water for at least 15 minutes.

Skin Immediately remove contaminated clothing and wash skin and

clothes thoroughly with running water.

Ingestion Do not induce vomiting. Give glass of water. If victim not

breathing begin artificial respiration. Obtain medical attention.

Inhalation Remove to fresh air. If breathing is difficult, seek medical

attention immediately

Section 5. Fire Fighting Measures

Fire and Explosion hazards Flammable liquid. Vapour accumulation could flash and/or

explode if ignited

Fire Fighting Instructions Fire fighters must use recommended protective equipment

and self-contained breathing apparatus.

Copyright© Car Clean Products NZ Ltd

Hazchem Code 3[Y]

Section 6. Accidental Release Measures

Product Name: Xylol/Xylene

Land Spill or Leaks Evacuate spill area and eliminate all ignition sources.

Report spill to fire brigade. If possible remove leaking containers to a detached area wearing approved respirator and personal protection equipment. Bund spill area with inert material. Avoid contact with skin and eyes. Do not breathe vapour. Extinguish naked flames. Remove ignition sources. No smoking. Evacuate the area of all non-essential personnel. Shut off leaks, if possible without personal risk. Wear full-face respirator with canister and

filter

Section 7. Handling and Storage

Handling Advice: Store away from heat and open flames. Store at ambient

temperatures. Keep containers tightly closed and in a well-

ventilated place

Storing Procedures: Store away from heat and open flames. Store at ambient

temperatures. Keep containers tightly closed and in a well-ventilated place. Do not store alongside food or feedstuffs.

Section 8 Exposure Controls / Personal Protection

Engineering Controls: Use only in well ventilated area. Eliminate sources of static

buildup. Earth bulk containers.

Personal Protective Equipment: Wear half face respirator with organic vapour cartridge

with built-in particulate filter NPF20 (gas only). Chemical monogoggles ,PVC gloves, chemical resistant safety shoes or boots and standard issue work clothes should be

worn

Section 9 Physical and Chemical Properties

Appearance Clear liquid
Odour: Characteristic
Odour threshold Data not available

pH N/A

Melting/Freezing point Data not available

Initial boiling point/range 137-143°C Flash point 25°C Flammability Liquid

Upper/Lower flammability limits Data not available

Vapour pressure 1.0 kPa Vapour density 3.7 kPa

Relative density Data not available Solubility in water, % mass: 0.175 kg/m3

Partition coefficient Data not available

Auto-ignition temperature: 432-530°C

Product Name: Xylol/Xylene Date of SDS: August 2023

Kinematic viscosity Data not available Particle characteristics Data not available

Section 10. Stability and Reactivity

Chemical Stability Stable at room temperature and pressure

Conditions to Avoid Sources of heat and ignition, open flames

Incompatibility Mixing with strong oxidizing agents causes violent

reactions.

Hazardous Decomposition

Products No decomposition products except in fire then carbon

dioxide and carbon monoxide.

Section 11 Toxicological Information

Acute Oral Toxicity >2000 mg/kg (rat)
Acute Dermal Toxicity >2000 mg/kg (rabbit)
Inhalation >20 mg/l for 4 hour (rat)

Long term Effects This product may contain 0.1 to 1% ethylbenzene. IARC

has evaluated ethylbenzene and classified it as a "possible human carcinogen" based on sufficient

evidence for cancer in exposed humans.

Section 12. Ecotoxicological Information

Environmental Precautions:

Ecological Toxicity Readily biodegradable. Oxidises rapidly by photo-chemical

reactions in the air.

Environmental Fate:

Soil Product is highly volatile and will rapidly evaporate to the

air.

Water As for soil

Section 13. Disposal Considerations

Dispose of waste at an appropriate waste disposal facility in accordance with local authority bylaws.

Empty and open containers can retain vapour residues for long periods of time risking unintended ignition or explosion. Puncture or crush before sending to a landfill.

Section 14 Transport Information

Product Name: Xylol/Xylene Copyright© Car Clean Products NZ Ltd Date of SDS: August 2023

Road, Rail, Marine and Air Transport

UN No : 1307
Class-primary : 3
Packing Group : III
Proper Shipping Name: : Xylene

Section 15 Regulatory Information

Primary HSNO Class 3.1B,

Subsidiary classes 6.1D, 6.3A, 6.4A, 6.8A, 6.9B, 9.1D, 9.3C

ERMA Approval No HSR001511

Section 16 Other Information

Packaged in 4lt, 20lt & 200lt containers. Codes XYL4, XYL20, XYL9.

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand proprietor, Car Clean Products NZ Limited, Phone: 09 250 0091, if further information is required.

Product Name: Xylol/Xylene Date of SDS: August 2023



Car Clean Products NZ Limited
Ph + 64 9 250 0091 - Fax + 64 9 250 0092 - www.pacer.co.nz
33 Ha Crescent, Wiri - P O Box 97 948 - Manukau - Auckland 2241 - New Zealand

XYLOL

PURPOSE:

Pacer Xylol is a clear colourless liquid with a mild hydrocarbon odour and medium volatility. Xylol is excellent for use with many synthetic and natural resins, fats and waxes.

DIRECTIONS:

Cleaning: Spray or wipe on to surface, agitate to clean and wipe off with a clean cloth or allow to evaporate.

DANGER: GIVES OFF HIGHLY FLAMMABLE VAPOUR.

Keep well away from heat, sparks and open flame. Keep closed when not in use.

WARNING:

Do not eat, drink or smoke whilst using. Avoid breathing vapour, Use with adequate ventilation. When using wear nitrile gloves, goggles and mask. Store in original container away from food. Dispose of empty container in a safe manner.

KEEP OUT OF REACH OF CHILDREN

Product Name: Xylol/Xylene Date of SDS: August 2023