

**Tire Information**

| | |
|-----------------------|-----------------|
| Inventory Code | 6H04511 |
| Size | ST175/80R13 |
| Tread Pattern | Radial Trail HD |
| Load Range | C |
| Load Index | 91 |
| Speed Symbol | M |

Dimensional Data

| | | |
|-------------------------|-----------|--------|
| Mounted Diameter | 24.10 in. | 612 mm |
| Mounted Width | 7.00 in. | 178 mm |
| Rim Width | 5.00 in. | 127 mm |
| Rim Diameter | 13.00 in. | 330 mm |
| Tire Weight | 17.90 lbs | 8.1 kg |
| Tread Depth | 8 /32" | 6 mm |

Comments or Special Conditions

Approved Rim Contours: 4.5J, 5J, 5.5J

Inflation and Load Data

| | | |
|-----------------------|--------|--------------------|
| Rated Speed | 81 mph | 130.4 km/h |
| Rated Pressure | 50 psi | 345 kPa |
| Rated Load | Single | 1360 lbs 617 kg |
| | Dual | 1200 lbs 544 kg |

Performance Data @ Rated Pressure, Load, and Speed

| | | |
|-------------------------------------|----------|---------|
| Rolling Circ. | 71.6 in. | 1818 mm |
| Static Load Rad. | 10.7 in. | 273 mm |
| Revolutions | 885 /mi | 550 /km |
| Deflection (@ Rated Load) | 1.3 in. | 33 mm |