According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revision: 20 May 2021 Page 1 of 11

IMI - STS Tire Sealant

SECTION 1: Identification

Product identifier

Product name: IMI - STS Tire Sealant **Product code:** IMI - STS Tire Sealant

Recommended use of the product and restriction on use

Relevant identified uses: Not determined or not applicable. **Uses advised against:** Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer: United States

IMI 3183 Black Gap Road Chambersburg, PA. 17202 1-800-233-7086 info@imiproducts.com **NZ Distributor:**

Patch Rubber Tyre & Tube 21 Aetna Place, Henderson, Auckland

Ph: 098372481

Emergency telephone number:

Infotrac

1-800-535-5053 North America 1-352-323-3500 International

SECTION 2: Hazard(s) identification

GHS classification:

Eye irritation, category 2A
Skin irritation, category 2
Skin sensitization, category 1
Respiratory sensitization, category 1
Specific target organ toxicity - repeated exposure, category 1

Label elements

Hazard pictograms:





Signal word: Danger Hazard statements:

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements:

P264 Wash skin and eyes thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revision: 20 May 2021 Page 2 of 11

IMI - STS Tire Sealant

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P284 Wear respiratory protection.

P285 In case of inadequate ventilation wear respiratory protection.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P270 Do not eat, drink or smoke when using this product.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists get medical advice/attention

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P314 Get medical advice/attention if you feel unwell

P501 Dispose of contents and container as instructed in Section 13.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

| Identification | Name | Weight % |
|------------------------|---|----------|
| CAS number: 67-56-1 | Methanol | <0.1 |
| CAS number: 14808-60-7 | Quartz | <0.1 |
| CAS number: 1333-86-4 | Carbon Black | <2 |
| CAS number: 2492-26-4 | Sodium mercaptobenzothiazole | <0.2 |
| CAS number: 10101-89-0 | Sodium phosphate tribasic dodecahydrate | <1.5 |

Additional Information:

Carbon black and Crystalline Quartz are only suspected human carcinogens as a respirable solid. Because this product is in a liquid state, and remains in a liquid state even after application, solid particles of carbon black and crystalline quartz are not expected to become respirable during normal conditions of use or exposure, and therefore the product itself does not warrant classification as a carcinogen. Note that care should be taken to maintain the product in a liquid state at all times, by avoiding direct heat, sunlight, etc., as well as any activities that may liberate respirable solids from the applied surface, such as cutting and sanding.

SECTION 4: First aid measures

Description of first aid measures General notes:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revision: 20 May 2021 Page 3 of 11

IMI - STS Tire Sealant

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Not determined or not applicable.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revision: 20 May 2021 Page 4 of 11

IMI - STS Tire Sealant

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Absorb with non-combustible liquid-binding material (sand, diatomaceus earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Protect from freezing and physical damage.

Store in a cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

| Country (Legal Basis) | Substance | Identifier | Permissible concentration |
|-----------------------|--------------|------------|---|
| United States (OSHA) | Quartz | 14808-60-7 | OSHA Z-3 TWA 0.1 mg/m³ (Respirable fraction); 0.3 mg/m³ (Total dust) |
| | Methanol | 67-56-1 | OSHA PEL TWA 200 ppm |
| | Carbon Black | 1333-86-4 | OSHA PEL TWA 3.5 mg/m ³ |
| | Methanol | 67-56-1 | OSHA PEL TWA 260 mg/m ³ |
| ACGIH | Quartz | 14808-60-7 | ACGIH TLV TWA 0.025 mg/m³ (Respirable fraction) |
| | Methanol | 67-56-1 | ACGIH TLV STEL 250 ppm [skin] |
| | Methanol | 67-56-1 | ACGIH TLV TWA 200 ppm [skin] |
| | Carbon Black | 1333-86-4 | TLV-TWA 3.0 mg/m³ |
| NIOSH | Quartz | 14808-60-7 | NIOSH TWA 0.05 mg/m ³ |
| | Carbon Black | 1333-86-4 | NIOSH REL TWA 0.1 mg PAHs/m3 [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)] |
| | Carbon Black | 1333-86-4 | NIOSH REL TWA 3.5 mg/m³ Ca |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revision: 20 May 2021 Page 5 of 11

IMI - STS Tire Sealant

| Country (Legal Basis) | Substance | Identifier | Permissible concentration |
|-----------------------|---|------------|-------------------------------------|
| | Methanol | 67-56-1 | NIOSH REL TWA 200 ppm [skin] |
| | Methanol | 67-56-1 | NIOSH REL TWA 260 mg/m³ [skin] |
| | Methanol | 67-56-1 | NIOSH REL ST 250 ppm [skin] |
| | Methanol | 67-56-1 | NIOSH REL ST 325 mg/m³ [skin] |
| WEEL | Sodium phosphate tribasic dodecahydrate | 10101-89-0 | STEL (15 min.): 5 mg/m ³ |

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

| Appearance | Viscous, black liquid |
|------------------------------------|----------------------------------|
| Odor | Faint polyol |
| Odor threshold | Not determined or not available. |
| рН | 10 - 11 |
| Melting point/freezing point | -10 °F (-23 °C) |
| Initial boiling point/range | Not determined or not available. |
| Flash point (closed cup) | > 300 °F (149 °C) |
| Evaporation rate | Not determined or not available. |
| Flammability (solid, gas) | Not determined or not available. |
| Upper flammability/explosive limit | Not determined or not available. |
| Lower flammability/explosive limit | Not determined or not available. |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revision: 20 May 2021 Page 6 of 11

IMI - STS Tire Sealant

| Vapor pressure | Not determined or not available. |
|---|----------------------------------|
| Vapor density | Not determined or not available. |
| Density | Not determined or not available. |
| Relative density | 1.10 - 1.13 |
| Solubilities | > 90% in water. |
| Partition coefficient (n-octanol/water) | Not determined or not available. |
| Auto/Self-ignition temperature | Not determined or not available. |
| Decomposition temperature | Not determined or not available. |
| Dynamic viscosity | 4,200 - 6,000 cps |
| Kinematic viscosity | 4,200 - 6,000 cps |
| Explosive properties | Not determined or not available. |
| Oxidizing properties | Not determined or not available. |

Other information

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

None known.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

| Name | Route | Result |
|----------|------------|-----------------------------|
| Methanol | oral | LD50 - Rat - 5630 mg/kg |
| | dermal | LD50 - Rabbit - 15800 mg/kg |
| | inhalation | LC50 - Rat - 83.9 mg/l - 4h |

Skin corrosion/irritation

Assessment: Causes skin irritation

Product data:
No data available.
Substance data:

| Name | Result |
|------|--------|
| | |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revsion: 20 May 2021 Page 7 of 11

IMI - STS Tire Sealant

| Name | Result |
|---|--|
| Sodium mercaptobenzothiazole | Causes severe skin burns and eye damage. |
| Sodium phosphate tribasic dodecahydrate | Causes skin irritation. |

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data: No data available.

Substance data:

| Name | Result |
|---|--------------------------------|
| Sodium mercaptobenzothiazole | Causes serious eye damage. |
| Sodium phosphate tribasic dodecahydrate | Causes serious eye irritation. |

Respiratory or skin sensitization

Assessment: May cause an allergic skin reaction May cause allergy or asthma symptoms or breathing difficulties if inhaled

Product data:No data available.

Substance data:

| Name | Result |
|------------------------------|--------------------------------------|
| Sodium mercaptobenzothiazole | May cause an allergic skin reaction. |

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

| Name | Species | Result |
|--------------|-----------------|--|
| Carbon Black | | The IARC carcinogenic classification and California Proposition 65 Warning only apply to airborne, unbound particles of respirable size of Carbon Black. |
| Quartz | Not applicable. | Component may cause cancer. |

International Agency for Research on Cancer (IARC):

| Name | Classification |
|--------------|--|
| Carbon Black | Group 2B - Possibly carcinogenic to humans |
| Quartz | Group 1 - Carcinogenic to humans |

National Toxicology Program (NTP):

| Name | Classification |
|--------|-------------------------------|
| Quartz | Known to be human carcinogens |

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Reproductive toxicity

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revision: 20 May 2021 Page 8 of 11

IMI - STS Tire Sealant

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available. Substance data:

| Name | Result |
|----------|--|
| Methanol | Causes damage to the optic nerve and central nervous system. |

Specific target organ toxicity (repeated exposure)

Assessment: Causes damage to organs through prolonged or repeated exposure

Product data:
No data available.
Substance data:

| Name | Result |
|--------|--|
| Quartz | Component affects the lungs through repeated exposure. |

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available. **Other information:**No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

| Name | Result |
|----------|--|
| Methanol | LC50 - Fish - 15,000 - 29400 mg/l - 96 h |
| | LC50 - Crustaceans - 2500 - 481000 mg/l - 48 h |

Chronic (long-term) toxicity

Product data: No data available. **Substance data:** No data available.

Persistence and degradability
Product data: No data available.
Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revision: 20 May 2021 Page 9 of 11

IMI - STS Tire Sealant

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

| UN number | Not regulated |
|-------------------------------|---------------|
| UN proper shipping name | Not regulated |
| UN transport hazard class(es) | None |
| Packing group | None |
| Environmental hazards | None |
| Special precautions for user | None |

International Maritime Dangerous Goods (IMDG)

| UN number | Not regulated |
|-------------------------------|---------------|
| UN proper shipping name | Not regulated |
| UN transport hazard class(es) | None |
| Packing group | None |
| Environmental hazards | None |
| Special precautions for user | None |

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

| UN number | Not regulated |
|-------------------------------|---------------|
| UN proper shipping name | Not regulated |
| UN transport hazard class(es) | None |
| Packing group | None |
| Environmental hazards | None |
| Special precautions for user | None |

| Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | |
|---|------|
| Bulk Name | None |
| Ship type | None |
| Pollution category | None |

SECTION 15: Regulatory information

United States regulations

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revision: 20 May 2021 Page 10 of 11

IMI - STS Tire Sealant

Inventory listing (TSCA):

| 67-56-1 | Methanol | Listed |
|------------|---|---------------|
| 1333-86-4 | Carbon Black | Listed |
| 14808-60-7 | Quartz | Listed |
| 2492-26-4 | Sodium mercaptobenzothiazole | Listed |
| 10101-89-0 | Sodium phosphate tribasic dodecahydrate | Not Listed |

Significant New Use Rule (TSCA Section 5): Not determined.

Export notification under TSCA Section 12(b): Not determined.

SARA Section 302 extremely hazardous substances: Not determined.

SARA Section 313 toxic chemicals:

| 67-56-1 | Methanol | Listed |
|------------|---|---------------|
| 1333-86-4 | Carbon Black | Not Listed |
| 14808-60-7 | Quartz | Not Listed |
| 2492-26-4 | Sodium mercaptobenzothiazole | Not Listed |
| 10101-89-0 | Sodium phosphate tribasic dodecahydrate | Not Listed |

CERCLA:

| 10101-89-0 | Sodium phosphate tribasic dodecahydrate | Listed | 5,000 |
|------------|---|--------|-------|
| 67-56-1 | Methanol | Listed | 5000 |

RCRA:

| | 67-56-1 | Methanol | Listed | U154 |
|--|---------|----------|--------|------|
|--|---------|----------|--------|------|

Section 112(r) of the Clean Air Act (CAA):

| | 67-56-1 | Methanol | Listed |
|--|---------|----------|--------|
|--|---------|----------|--------|

Massachusetts Right to Know:

| 67-56-1 | Methanol | Listed |
|------------|---|---------------|
| 1333-86-4 | Carbon Black | Listed |
| 14808-60-7 | Quartz | Listed |
| 2492-26-4 | Sodium mercaptobenzothiazole | Not Listed |
| 10101-89-0 | Sodium phosphate tribasic dodecahydrate | Listed |

New Jersey Right to Know:

| 67-56-1 | Methanol | Listed |
|------------|---|---------------|
| 1333-86-4 | Carbon Black | Listed |
| 14808-60-7 | Quartz | Listed |
| 2492-26-4 | Sodium mercaptobenzothiazole | Not Listed |
| 10101-89-0 | Sodium phosphate tribasic dodecahydrate | Listed |

New York Right to Know:

| 1333-86-4 | Carbon Black | Not Listed |
|-----------|--------------|---------------|
| 67-56-1 | Methanol | Listed |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.21.2018 Revision 20 May 2021 Page 11 of 11

IMI - STS Tire Sealant

| 14808-60-7 | | Not Listed |
|------------|---|---------------|
| 2492-26-4 | · | Not Listed |
| 10101-89-0 | Sodium phosphate tribasic dodecahydrate | Listed |

Pennsylvania Right to Know:

| 67-56-1 | Methanol | Listed |
|------------|---|---------------|
| 1333-86-4 | Carbon Black | Listed |
| 14808-60-7 | Quartz | Listed |
| 2492-26-4 | Sodium mercaptobenzothiazole | Not Listed |
| 10101-89-0 | Sodium phosphate tribasic dodecahydrate | Listed |

California Proposition 65: WARNING: This Product contains chemicals and/or sub-components that may cause cancer, or reproductive harm per California Prop 65 – www.P65Warnings.ca.gov

SECTION 16: Other information

Abbreviations and Acronyms: None **Disclaimer:**

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-0-0 **HMIS:** 2-0-0

Initial preparation date: 05.21.2018 Revision: 20 May 2021

End of Safety Data Sheet