



PRODUCT INFORMATION

EUROCEL PE 913

Short description:

Single sided LDPE tape

Product Data

Backing:	0.100 mm black LDPE film
Adhesive:	Dry natural rubber and resins solvent based
Total thickness	0.120 mm
Adhesion to steel	4.2 N/25mm
Tensile strength MD	45 N/25mm
Elongation at break	300 %
Temp. Resistance	60 °C

Application

Multipurpose LDPE tape used mainly in the building industry as well as a generic protective tape for metal surfaces UV protection, allowing a maximum stay period of 2 months*.

**Product must be tested under real working conditions before any industrial use. We highly recommend to verify the complete suitability for specific application. Every material, application process and condition is different.*

Features	Benefits
Dry natural rubber and resins solvent based adhesive	<ul style="list-style-type: none"> ➤ Good adhesion in most applications ➤ Moderately resistant to ageing
Black LDPE backing	<ul style="list-style-type: none"> ➤ Good moisture and vapour barrier ➤ Very high elongation ➤ Adaptable to different surfaces ➤ Hand tearable ➤ Barrier to light/outdoor exposure (max 2 months)

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

18 Casino Street, WELSHPOOL, 6106, Western Australia
Tel: (08) 9365 3000 Fax: (08) 9353 3280 Email: sales@powerpak.com.au Web: powerpak.com.au

This information is given to the best of PowerPak Packaging's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.