

Hydro-seeding Mulch Use Rates

PRODUCT	RATE	4 TO 1 SLOPE	3 TO 1 SLOPE	2 TO 1 SLOPE	1 TO 1 SLOPE
EZ MULCH AF BLENDED PELLETISED MULCH	per 100 sq mtr	25-27kg			
	per 1000 sq mtr	250-270kg			
EZ MULCH PLUS BLENDED PELLETISED MULCH+ TACK	per 100 sq mtr	25-27kg	27-30kg		
	per 1000 sq mtr	250-270kg	270-300kg		
MESIC 100% WOOD 100% WOOD FIBRE	per 100 sq mtr	16kg	28kg	33kg	
	per 1000 sq mtr	160kg	280kg	330kg	
MESIC 100% WOOD PLUS TACK 100% WOOD FIBER + TACKIFIER	per 100 sq mtr	16kg	28kg	33kg	
	per 1000 sq mtr	160kg	280kg	330kg	
EARTHGUARD FIBER MATRIX FIBRE MATRIX FOR SEVERE SLOPES	per 100 sq mtr	16kg	20kg	22kg	33kg
	per 1000 sq mtr	160kg	200kg	220kg	330kg

At 16kg per 100 sq mtr tackifier may be needed for erosion control. Minimal moisture retention
 Use 20kg per 100 sq mtr rate when temperatures are under 28 deg. Some erosion control expected.
 Use minimum rate of 30kg per 100 sq mtr when temperature above 29 deg

Rates are slope and weather dependant

Note: germination may be slightly slower but more consistent at higher rates

Tackifiers will always increase erosion protection and may speed up germination time.