



1PA60P20S PRESS REDUCING CART PILO, 1PA60-P-20-S-XXX

407AA00041A [↗](#)

Model code: 1PA60-P-20-S-XXX

Where to buy [↗](#)

Product specifications

Characteristic	Value	Description
Adjustment type	LEAKPROOF SCREW	Leakproof Screw
Brand	DANFOSS	Danfoss
Cavity	CVA-22-06-0	CVA-22-06-0
Factory set pressrue BAR		112.500
Flow rate LPM		60.000
Fluid Compatibility	MIL-H-5606, SAE10, SAE20, ETC	MIL-H-5606, SAE10, SAE20, etc
Function	PRESSURE REDUCING VALVE	Pressure Reducing Valve
Housing	NO	No
Installation type	SCREW-IN CARTRIDGE	Screw-in Cartridge
Leakage	0.3 CC/MIN	0.3 cc/min
Max working pressure BAR		210.000
Min working pressure BAR		15.000
Model Code 1		1PA60-P-20-S-XXX
Number of housing ports	3	3
Number of valve ports	3	3
Operating temperature	-40 C TO 120 C (-40 TO 248 F)	-40 C to 120 C (-40 to 248 F)
Operation	PILOT OPERATED	Pilot operated
Port Size	NONE	None
Port Type	CARTRIDGE ONLY	Cartridge Only
Pressure rating BAR		350.000
Product height in		1.062



Characteristic	Value	Description
Product height mm		26.975
Product length in		3.523
Product length mm		89.484
Product width in		1.062
Product width mm		26.975
Recommended filtration level	18/16/13	18/16/13
Seal Type	BUNA-N	Buna-N
Special Features	NONE	None
Style	SPOOL	Spool

For the most current information and other product assets, please use this link to visit the product page on Danfoss PowerSource [🔗](#)