



Lewitt LCT 540 Subzero Cardioid Condenser Microphone



- 1" True Condenser Studio Microphone
- Cardioid Polar Pattern
- 20 Hz to 20 kHz Frequency Response
- Self-Noise Circuit Design
- Integrated Clipping Indicator
- Automatic Attenuation
- Low-Cut Filter
- Includes Protective Carry Case
- Shockmount and Magnetic Pop Filter

What's in the Box

Lewitt LCT 540 Subzero Cardioid Condenser Microphone
Large Cylindrical Foam Windscreen for LCT Series Microphones
LCT 40 SHX Shock Mount
LCT 50 PSx Magnetic Pop Filter
DTP 40 Lb Cushioned Leather Mic Pouch
Limited 1-Year Warranty

Specs

Lewitt LCT 540 Specs

Microphone

Sound Field	Mono
Operating Principle	Pressure Gradient
Capsule	Condenser
Diaphragm	1" / 25.40 mm
Polar Pattern	Cardioid
Pad	-12 dB
High-Pass Filter	80 Hz, 6 dB/Octave

Performance

Frequency Range	20 Hz to 20 kHz
Maximum SPL	136 dB SPL RMS
Impedance	68 Ohms
Sensitivity	41 mV/Pa
Dynamic Range	132 dB A-Weighted
Signal-to-Noise Ratio	90 dB A-Weighted
Equivalent Noise Level	4 dB A-Weighted

Connectivity

Output Connectors	1 x XLR 3-Pin
-------------------	---------------

Power

Operating Voltage	48 V
Operating Current Consumption	3.6 mA

Physical

Dimensions	ø: 2.04 x L: 6.22" / ø: 51.82 x L: 157.99 mm
Weight	13.1 oz / 371.38 g

Packaging Info

Package Weight	4.45 lb
Box Dimensions (LxWxH)	10.4 x 9.1 x 7.0"