

Little Labs

Little Labs Monotor Pro Audio Headphone Amp



- Mastering Quality Sound Reproduction
- Dual 1/4" and 1/8" Headphone Jacks
- Each Pair of Jacks Separately Amplified
- Mono Monitor Analysis: Left-Plus-Right
- Left, Right, and Left-Minus-Right
- Minimal Audiophile Circuit Path
- Accepts Balanced and Unbalanced Inputs
- XLR/TRS Combo Jack w/ Parallel TRS
- Stereo Mini-Jack Input
- High Quality Stepped Volume Attenuator

What's in the Box

LITTLE LABS Monotor Audiophile Headphone Amplifier w/ Mono Analysis
Power Supply
Limited 3-Year Warranty

Specs

LITTLE LABS MONO Specs

Inputs	2x XLR-1/4" / 6.35 mm combo jacks 1x 1/8" / 3.5 mm stereo mini jack 2x Parallel TRS input/output jacks (can be used for pass-thru or daisy-chaining)
Outputs	2x 1/4" / 6.35 mm TRS phone jacks 2x 1/8" / 3.5 mm TRS phone jacks
Input Impedances	Measured in stereo mode with TOA ZM-104 impedance meter Balanced signal measured between pin 2-3 XLR or Tip-Ring (TRS) Balanced Input Impedance with Level Control In: 5 to 11 kOhms* Balanced Input Impedance with Level Control Out: 8 kOhms Unbalanced Input Impedance with Level Control In: 4 to 5 kOhms*

Unbalanced Input Impedance with Level Control Out: 20 kOhms

*Front end passive level attenuator varies input impedance depending on setting

Headphone Output Impedance	0.5 Ohms
Power	Power in Bipolar: 16.5 VDC
Dimensions (L x W x D)	Monotor: 6.5 x 4.0 x 1.5" / 165.1 x 101.6 x 38.1 mm Power Supply: 3.0 x 5.0 x 2.3" / 76.2 x 127.0 x 57.2 mm
Weight	Monitor: 3.0 lb / 1.4 kg Power Supply: 2.0 lb / 0.9 kg