



# aktiv



## Level up with aktiv™ the fluid head build for speed.

Mount, level and lock your fluid head in seconds. Capture the perfect shot – with the revolutionary aktiv™ head built for speed. The unique SpeedLevel™ and SpeedSwap™ technology deliver the fastest way to place and position the camera – giving the camera operator ultimate creativity.

- **Level and lock your head in an instant without missing a second of action**  
Unique SpeedLevel™ technology
- **Visible from any height or angle - day or night**  
Innovative PrismBubble
- **Capture extreme low angle shots right down to the ground**  
Innovative streamlined mounting system
- **Switch between tripod and slider in seconds**  
Revolutionary SpeedSwap™ system
- **Create moving stories, whatever the weather.**  
Performance tested to the extreme



### aktiv6

Payload Range  
0 - 8 kg  
0-17.6 lb



### aktiv8

Payload Range  
0 - 12 kg  
0 - 26.5 lb

aktiv8 Sideload  
aktiv8T Touch & Go



### aktiv10

Payload Range  
0 - 12 kg  
0-26.5 lb

## Mid-level spreader systems



**System aktiv6  
flowtech75 MS**  
S2064S-FTMS



**System aktiv8  
flowtech75 MS**  
S2068S-FTMS



**System aktiv8T  
flowtech75 MS**  
S2068T-FTMS



**System aktiv10  
flowtech100 MS**  
S2072S-FTMS

<b>Bowl</b>	75 mm with SpeedSwap™	75 mm with SpeedSwap™	75 mm with SpeedSwap™	100 mm with SpeedSwap™
<b>Payload range</b>	0 - 8 kg / 0-17.6 lb	0 - 12 kg / 0-26.5 lb	0 - 12 kg / 0-26.5 lb	0 - 12 kg / 0-26.5 lb
<b>Counterbalance steps</b>	15+0	15+0	15+0	15+0
<b>Drag setting</b>	3+0	7+0	7+0	7+0
<b>Camera fitting</b>	Sideload S	Sideload S	Touch & Go plate S	Sideload S
<b>System weight</b>	6.2 kg / 13.7 lb	6.3 kg / 13.9 lb	6.4 kg / 14.1 lb	6.9 kg / 15.2 lb
<b>Height range without spreader</b>	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in	25 - 172 cm / 9.8 - 67.7 in
<b>Height range with spreader</b>	79 - 174 cm / 31.1 - 68.5 in	79 - 174 cm / 31.1 - 68.5 in	79 - 174 cm / 31.1 - 68.5 in	72 - 175 cm / 28.3 - 68.9 in

## Ground spreader systems



**System aktiv6  
flowtech75 GS**  
S2064S-FTGS



**System aktiv8  
flowtech75 GS**  
S2068S-FTGS



**System aktiv8T  
flowtech75 GS**  
S2068T-FTGS



**System aktiv10  
flowtech100GS**  
S2072S-FTGS

<b>Bowl</b>	75 mm with SpeedSwap™	75 mm with SpeedSwap™	75 mm with SpeedSwap™	100 mm with SpeedSwap™
<b>Payload range</b>	0 - 8 kg / 0-17.6 lb	0 - 12 kg / 0-26.5 lb	0 - 12 kg / 0-26.5 lb	0 - 12 kg / 0-26.5 lb
<b>Counterbalance steps</b>	15+0	15+0	15+0	15+0
<b>Drag setting</b>	3+0	7+0	7+0	7+0
<b>Camera fitting</b>	Sideload S	Sideload S	Touch & Go plate S	Sideload S
<b>System weight</b>	6.4 kg / 14.1 lb	6.5 kg / 14.3 lb	6.6 kg / 14.5 lb	6.8 kg / 15 lb
<b>Height range without spreader</b>	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in	23 - 170 cm / 9.0 - 66.9 in	25 - 172 cm / 9.8 - 67.7 in
<b>Height range with spreader</b>	56 - 176 cm / 22 - 69.3 in	56 - 176 cm / 22 - 69.3 in	56 - 176 cm / 22 - 69.3 in	58 - 178 cm / 22.8 - 70 in

## System aktiv10 flowtech100 S2072S-FT

## Systems without spreader

<b>Bowl</b>	100 mm with SpeedSwap™
<b>Payload range</b>	0 - 12 kg / 0-26.5 lb
<b>Counterbalance steps</b>	15+0
<b>Drag setting</b>	7+0
<b>Camera fitting</b>	Sideload S
<b>System weight</b>	6.3 kg / 13.9 lb
<b>Height range</b>	25 - 172 cm / 9.8 - 67.7 in

