

**SE-1200MU 6 Input Rackmount HD Switcher**

Video Standard	HD
Video Format	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
Video Processing	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4
Input Routable / Crosspoint	All 6, repeatable
Video Input	4x HD-SDI 2x HDMI (RGB/YUV, 1080i/1080p/720p)
Computer Graphic Interface	2 via HDMI
Video Output	2x HD-SDI 2x HDMI assignable: PGM(w/DSK 1&2), PGM(w/DSK 1), PGM Clean, PVW(w/o DSK), multi-view, Input 1-6
Built-in Multi-view Monitoring Out	HDMI & Ethernet (MJPE
Audio Input	2x Balanced XLR De-embedded Digital Audio (2 CH)
Audio Output	Embedded digital audio (2 CH)
Embedded Audio Support	Embedded 2-CH audio output from XLR input or embedded audio input
A+V Switching	Yes
Chromakey	2
USK	2x USK support Chromakey & Linear/ Luma Key
DSK	2x DSK support Lumakey & Linear key (Key / Fill)
Picture in Picture	1
Still Store	500
Effects	FTB, Cut, 32 Wipe with
Transition Preview	Full transitions preview
Sync / Reference In/Out	Built-in Genlock (internal)
Tally Output	1x D-sub 15pin, dual color
PC Remote Control	Via Eth
Special Features	Motion JPEG Multi-view streaming (120 memory preset, BGD Transition on/off option) Free Virtual Set and Stinger transition included
Chassis	2 units, 1RU rack-mount mainframe
Dimension (LxWxH)	440 x 215 x 49 mm
Weight	1.5 kg
Power	DC 12V, 19W
Operating Temp. Range	0~40 °C
Options	CB-46/47/60/61/62
What's in the box	1 x SE-1200MU product 1 x AD Switch DC 12V 1 x DB9P TO DB9P Cable 1 x Thank You Card 2 x 1U Rack Mount Ear 6 x M4 Screws for Rack Mount Ear