

sachtler



System FSB 8 FT MS

Sachtler System FSB 8 carbon fibre with Fluid Head, flowtech® Tripod, Mid-Level Spreader & Bag

SKU: 0795

For projects that require larger camcorders, smaller film and DSLR set-ups, having a fluid head that doesn't hold you up or let you down is a must. The Sachtler FSB 8 Fluid Head's Snap & Go means that pre-configured setups are as quick as clicking the camera into place on the side of the tripod. Payload support of up to 10 kg and a large sliding range of 120 mm make time-consuming fiddling a thing of the past.

Once the camera is attached, the ten counterbalance steps let you finely balance as quickly as you mounted the camera. When it is time to shoot, frictionless leak-proof fluid damping with five levels of drag gives you seamless smooth motion for all your pans and tilts.

The Sachtler Mid-Level Spreader makes it simple to set up your tripod with a specific leg angle or footprint and helps stabilize your system. It also features a pull-up ring, spreader locks, and spreader attachment to make setting up simple and fast by keeping clumsy fiddling to a minimum.

Technical specifications

Feature	Metric	Imperial
Range	FSB	FSB
Pan bar count	1	1
Payload	1 to 10 kg	2.20 to 22 lb
Bowl size	75 mm	75 mm
Spreader type	Mid-level spreader	Mid-level spreader
Material	Carbon Fibre	Carbon Fibre
Transport length	850 mm	33.15 in
Tripod stages	2	2
Height with spreader	0.78 to 1.73 m	2.56 to 5.67 ft
Height without spreader	0.41 to 1.69 m	1.34 to 5.54 ft
Weight	6.10 kg	13.42 lb
Temperature range	-40 to 60 °C	-40 to 140 °F
Tilt range	90° to -75°	90° to -75°
Sliding range	120 mm	4.68 in
Interface Compatibility	Sideload	Sideload
Counterbalance	10 counterbalance steps	10 counterbalance steps
Drag	5 + 0 horizontal and vertical grades of drag	5 + 0 horizontal and vertical grades of drag

What's in the box?

- **FSB 8**
- **Tripod flowtech® 75 MS**
- **Padded bag flowtech®75**

Data sheets

