



Lewitt MTP 940 CM Condenser Performance Handheld Microphone

- For Live Sound and Recording
- 20 Hz to 20 kHz Frequency Response
- 3 Switchable Polar Patterns
- 48V Phantom Power
- 3-Step High-Pass Filter
- 3-Step Pre-Attenuation Pad
- LED Indicators for Microphone Status
- Gold-Plated 3-Pin XLR Connector
- Shock Mount is Included
- Carrying Pouch is Included

What's in the Box

Lewitt MTP 940 CM Condenser Performance Handheld Microphone
MTP 40 MCs Shock Mount
DTP 40 LB Pouch
Limited 2-Year Warranty

Specs

Lewitt MTP 940 CM Specs

Operating Principle	Acoustical: Pressure gradient transducer, externally polarized
Directional Pattern	Cardioid, wide cardioid, supercardioid
Frequency Range	20 Hz to 20 kHz
Sensitivity	10 mV / Pa (-40 dBV), cardioid
Signal to Noise Ratio	85 dB-A
Equivalent Noise Level	9 dB-A, cardioid (IEC 61672-1)
Dynamic Range	Mic Amp: 135 dB-A
Maximum SPL for 0.5% THD	144 dB, 0 dB pre-attenuation 150 dB, 6 dB pre-attenuation 156 dB, 12 dB pre-attenuation
Pad	Pre-Attenuation: 6 dB, 12 dB, switchable

Bass Cut Filter	Slope:
	12 dB / octave at 80 Hz
	12 dB / octave at 160 Hz
Impedance	Rated: < 150 Ω
	Rated Load Impedance: > 1000 Ω
Supply Voltage	48 V +/- 4 V (IEC 61938)
Current Consumption	5.5 mA (IEC 61938)
Connector	Gold-plated 3-pin XLR
Dimensions (Diam. x H)	2.0 x 7.2" (51 x 183 mm)
Weight	11.7 oz (332 g)

Packaging Info

Package Weight	3.85 lb
Box Dimensions (LxWxH)	9.8 x 8.3 x 4.3"