PROTEL
Professional Audio and Video Solutions

SPL Volume8 Multi Channel Volume Controller

What's in the Box

SPL Volume8 Multi Channel Volume Controller

Specs

SPL SPLVOLU8 Specs

Inputs and Outputs	Instrument amplifier, electronically balanced (differential),transformerless Nominal Input Level: +4 dBu Input Impedance: =22 kohm Output Impedance: ‹ 600 ohm Max. Input Level: › +20 dBu Volume Gain: ∞ to -4 dB
Data Features	Frequency Range: 10 Hz to 100 kHz, (100 kHz = -3 dB) CMRR: › 60 dBu @ 1 kHz THD & N: (@ +15 dBu Input Level)› -100 dBu S/N A-weighted: -102 dBu Crosstalk L/R (@ 1 kHz): › -80 dBu Dynamic Range: 120 dB
Power Supply	Toroidal transformer:155 VA Fuse: 250 mA / 230 V, 500 mA/115 V

	Voltage Selector: 230 / 50 Hz ‹› 115 V / 60 Hz Power Consumption: ca. 15 W
Hardware	Aluminum playback knob: 1.78" (45 mm) diameter
Dimension	8.5 x 3.1 x 8.8" (215 x 80 x 220 mm) Depth including Potentiometer & Sockets: 9.8" (245 mm)
Weight	4.18 lb (1.9 kg)