SAFETY DATA SHEET

1. Identification

Product identifier Super Duty

Other means of identification

Product Code 1276

Compound, Polishing Creme Recommended use

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Malco Products, Inc.

Address 361 Fairview Ave

Barberton, OH 44203

United States

Phone **Telephone** 800-253-2526

> Fax 330-753-2025

Website www.malcopro.com E-mail msdsinfo@malcopro.com

Technical Department Contact person

24HR EMERGENCY ASSISTANCE IN NEW ZEALAND 1-800-424-9300 **Emergency phone number** Phone

National Poison Control Centre: 0800 POISON [764 766]

DISTRIBUTOR IN NEW ZEALAND:

Pacer - Car Clean Products NZ Ltd

33 Ha Crescent, Wiri, Auckland

+64 9 25000 92

sales@pacer.co.nz

www.pacer.co.nz

2104 New Zealand

Fax:

Email:

Web:

Phone: +64 9 25000 91

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4

Health hazards Acute toxicity, oral Category 5

Acute toxicity, inhalation Category 5 Serious eye damage/eye irritation Category 2A Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified. Not classified. **OSHA** defined hazards

Label elements



Signal word

Combustible liquid. May be harmful if swallowed. Causes serious eye irritation. May be harmful if **Hazard statement**

inhaled. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Keep away from flames and hot surfaces. - No smoking. Do not breathe mist/vapors. Wash Prevention

thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face

protection.

If swallowed: Rinse mouth, Do NOT induce vomiting, If in eyes: Rinse cautiously with water for Response

> several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

In case of fire: Use appropriate media to extinguish.

Store in a well-ventilated place. Keep cool. Store away from incompatible materials. Storage

Dispose of waste and residues in accordance with local authority requirements. Dispose of Disposal

contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 57.16% of the mixture consists of component(s) of unknown acute hazards to the aquatic

environment. 57.16% of the mixture consists of component(s) of unknown long-term hazards to

the aquatic environment.

Material name: Super Duty SDS US

3. Composition/information on ingredients

Mixtures

Ingestion

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|-----------|
| dialuminum;oxygen(2-) | | 1344-28-1 | 20 - < 30 |
| Solvent Naphtha (Petroleum), Medium Aliph. | | 64742-88-7 | 10 - < 20 |
| propane-1,2,3-triol | | 56-81-5 | 3 - < 5 |
| Other components below reportab | le levels | | 50 - < 60 |

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and

vision. Prolonged exposure may cause chronic effects. delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

and precautions for firefighters Fire fighting

so without risk.

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods General fire hazards

Combustible liquid.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

Material name: Super Duty SDS US 2/7

7. Handling and storage

Precautions for safe handling Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist/vapors.

Do not taste or swallow. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene

practices.

Conditions for safe storage. including any incompatibilities Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with

sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

| US. OSHA Table Z-1 Permissible Expe | osure Limits (PEL) for Air | [·] Contaminants (29 C | FR 1910.1000) |
|-------------------------------------|----------------------------|---------------------------------|---------------|
| | | | |

| Components | Туре | Value | Form |
|--|------|----------|----------------------|
| dialuminum;oxygen(2-) (CAS 1344-28-1) | PEL | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| propane-1,2,3-triol (CAS 56-81-5) | PEL | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |

No biological exposure limits noted for the ingredient(s). **Biological limit values**

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Viscous. Cream. **Appearance**

Physical state Liquid. Liquid. **Form** Color White. Vanilla Odor **Odor threshold** Not available.

8.8

Melting point/freezing point 3122.86 °F (1717.14 °C) estimated Initial boiling point and boiling 2370.2 °F (1299 °C) estimated

range

Flash point 190.0 °F (87.8 °C) **Evaporation rate** Not available. Not applicable. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Material name: Super Duty 3/7

Vapor pressure -0.01 hPa estimated

Not available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. **Partition coefficient**

(n-octanol/water)

Auto-ignition temperature 739 °F (392.78 °C) estimated

Decomposition temperature Not available. **Viscosity** 42000 cP 68 °F (20 °C) Viscosity temperature

Other information

10.32 lbs/gal Density Not explosive. **Explosive properties**

Flammability class Combustible IIIB estimated

Oxidizing properties Not oxidizing.

VOC 12 % By Weight estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eve contact Causes serious eye irritation. May be harmful if swallowed. Ingestion

Symptoms related to the physical, chemical and

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

toxicological characteristics

Information on toxicological effects

Acute toxicity May be harmful if swallowed.

Test Results Components **Species**

dialuminum;oxygen(2-) (CAS 1344-28-1)

Acute Oral

LD50 Rat > 5000 mg/kg

propane-1,2,3-triol (CAS 56-81-5)

Acute

Inhalation

LC50 Rat > 570 mg/m3, 1 Hours

Oral

LD50 Rat 5.57 g/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Material name: Super Duty SDS US 4/7

^{*} Estimates for product may be based on additional component data not shown.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results**

propane-1,2,3-triol (CAS 56-81-5)

Aquatic

Acute Fish

LC50 Rainbow trout donaldson trout 51000 - 57000 mg/l, 96 hours

(Oncorhynchus mykiss)

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

-1.76propane-1,2,3-triol

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

Material name: Super Duty SDS US 5/7

^{*} Estimates for product may be based on additional component data not shown.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

One or more components of the mixture are not on the TSCA 8(b) inventory

Group Standard 2020

or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

NEW ZEALAND: CERCLA Hazardous Substance List (40 CFR 302.4) Cleaning Products (Subsidiary Hazard)

Not listed.

SARA 304 Emergency release notification HSR002530

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure) categories

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. dialuminum;oxygen(2-) 1344-28-1 20 - < 30

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

propane-1,2,3-triol (CAS 56-81-5) Other Flavoring Substances with OSHA PEL's

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region On inventory (yes/no)* Inventory name Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No Toxic Substances Control Act (TSCA) Inventory Yes United States & Puerto Rico

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

Material name: Super Duty SDS US 6/7

16. Other information, including date of preparation or last revision

 Issue date
 10-20-2023

 Revision date
 11-20-2023

Version # 04

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Malco Products, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or

expense due to improper use.

Revision information Product and Company Identification: Product and Company Identification

Accidental release measures: Environmental precautions

Material name: Super Duty SDS US