



Patch

Filler and Seam Sealer

- *Waterproof*
- *For Steel, Wood, Plastic, Concrete, Seams, Expansion Joints*
- *Apply Over Rust*
- *Professional Use*

For years our customers have asked us for a thicker version of our world-famous POR-15® Rust Preventive Coating, to use for filling seams or holes. Here it is! POR-15® Patch is, and like POR-15® Rust Preventive Coating, it dries as hard as a rock, remains flexible, and once dry is totally impervious to fuels and solvents. It's so tough it may actually add strength to weakened metal. And it won't absorb moisture and swell like conventional body fillers.



PRODUCT	SIZE	CODE
Black	4 oz.	49013
White	4 oz.	49023

Suggested Uses:

- Permanently seal seams
- Patch holes in steel, wood, or plastic
- Fix holes in fuel tanks
- Bond steel to plastic, wood, or concrete
- Repair concrete and cinder blocks



Product Information

Patch Filler and Seam Sealer



POR-15® Patch is a great filler and adhesive for wood, metal, plastic, and concrete.

Application Information

Directions for use: POR-15® Patch must be applied to dry surfaces only. Wear protective gloves while using. Remove from skin immediately with POR-15® Solvent or lacquer thinner to prevent temporary staining. Dries to touch in 4-6 hours but full cure may take up to 96 hours depending on thickness applied. Once dry, POR-15® Patch cannot be removed by any solvent. Keep cap and threads clean before re-sealing. Recap tube immediately after application. POR-15® Patch dries to a rock-hard finish and sanding is very difficult, so we don't recommend use on car exterior parts if a cosmetic finish is desired.

Safety Information:

HEALTH HAZARD INFORMATION: Before opening container, read all warnings. Follow all precautions. Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR.** Do not breathe vapor. Wear an appropriate, properly fitted respirator.

Use only with adequate ventilation KEEP OUT OF REACH OF CHILDREN

WARNING!: Vapor harmful. May cause dizziness, headache or nausea, eye, nose, throat and skin irritation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

First Aid: FOR INHALATION: If you experience difficulty breathing, leave area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately. IF SWALLOWED: DO NOT induce vomiting; immediately call Poison Control Center and have label available. FOR SKIN CONTACT: Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if skin irritation occurs or you feel unwell. FOR EYE CONTACT: Flush eyes immediately with plenty of fresh water. Remove contact lenses if possible. Continue eye flushing with water for at least 15 minutes and get medical attention immediately.

⚠ WARNING!: This product can expose you to chemicals including Silica, crystalline quartz and Cumene, which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

Hazardous Ingredients: Oxirane, 2-methyl-, polymer [167883-19-4]; 4,4'-Methylenediphenyl diisocyanate [101-68-8]; Solvent naphtha (petroleum), light aromatic [64742-95-6]; 1,2,4-Trimethylbenzene