

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 1 of 13

## POR-15 FUEL TANK SEALER

### SECTION 1: Identification

#### Product identifier

**Product name:** POR-15 FUEL TANK SEALER

**Product code:** 49201; 49204; 49205; 49208; 49216; 49255; 249204; 249205; 249208; 249216; 249255

**Additional information:** No additional information available.



#### Recommended use of the product and restriction on use:

**Relevant identified uses:** Paints and coatings.

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

P.O.R. Products  
38 Portman Road  
New Rochelle, NY 10801  
914-636-0700

##### Supplier:

RA Johnstone & Co Ltd trading as  
RJP Performance  
33 Ha Crescent, Wiri,  
Auckland 2104  
+64 9 25000 91 / sales@raj.co.nz

#### Emergency telephone number:

**ChemTel Inc.**

+1 813 248 0585

**Poisons Information Center, New Zealand**

0800 764 766

### SECTION 2: Hazards identification

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2017

#### HSNO Classification or Subclasses – Physical hazards:

Class	GHS Category	HSNO Category
Flammable liquids	Category 3	3.1C

#### HSNO Classification or Subclasses – Health hazards:

Class	GHS Category	HSNO Category
Eye irritation	Category 2A	6.4A
Skin irritation	Category 2	6.3A
Respiratory sensitization	Category 1	6.5A
Aspiration hazard	Category 1	6.1E
Acute toxicity (inhalation)	Category 4	6.1D
Specific target organ toxicity - single exposure	Category 3, respiratory irritation	6.1E
Specific target organ toxicity - single exposure	Category 3, central nervous system	6.9B
Specific target organ toxicity - repeated exposure	Category 1	6.9A
Carcinogenicity	Category 2	6.7B

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 2 of 13

## POR-15 FUEL TANK SEALER

### HSNO Classification or Subclasses – Environmental hazards:

Class	GHS Category	HSNO Category
None known	None known	None known

### GHS classification:

Flammable liquids, category 3

Eye irritation, category 2A

Skin irritation, category 2

Respiratory sensitization, category 1

Aspiration hazard, category 1

Acute toxicity (inhalation), category 4

Specific target organ toxicity - single exposure, category 3, respiratory irritation

Specific target organ toxicity - single exposure, category 3, central nervous system

Specific target organ toxicity - repeated exposure, category 1

Carcinogenicity, category 2

### Label elements

#### Hazard pictograms:



Signal word: Danger

### Hazard statements and Precautionary statements:

H226 Flammable liquid and vapor

H319 Causes serious eye irritation

H315 Causes skin irritation

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H304 May be fatal if swallowed and enters airways

H332 Harmful if inhaled

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H372 Causes damage to organs through prolonged or repeated exposure

H351 Suspected of causing cancer

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ventilating/light/equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P280 Wear protective gloves/protective clothing/eye protection/face protection

P264 Wash skin thoroughly after handling

P285 In case of inadequate ventilation wear respiratory protection

P271 Use only outdoors or in a well-ventilated area

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P270 Do not eat, drink or smoke when using this product

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 3 of 13

## POR-15 FUEL TANK SEALER

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P303+P361+P353 If on skin (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/shower

P370+P378 In case of fire: Use agents recommended in section 5 for extinction

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 If on skin: Wash with soap and water

P332+P313 If skin irritation occurs: Get medical advice/attention

P331 Do not induce vomiting

P301+P310 If swallowed: Immediately call a poison center or doctor/physician

P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell

P308+P313 If exposed or concerned: Get medical advice/attention

P405 Store locked up

P403+P233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents and container as instructed in Section 13

### Hazards not otherwise classified:

None known.

## SECTION 3: Composition/information on ingredients

### Mixture:

Identification	Name	Weight %
CAS number: 95-63-6	1, 2, 4-Trimethylbenzene	<12
CAS number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	<3
CAS number: 1330-20-7	Xylene	<1
CAS number: 64742-95-6	Solvent naphtha (petroleum), light arom.	30-35
CAS number: 9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	3-8
CAS number: 7429-90-5	Aluminum	<3
CAS number: 26447-40-5	Methylenediphenyl diisocyanate	<5
CAS number: 101-68-8	4,4'-Methylenediphenyl diisocyanate	5-13
CAS number: 98-82-8	Cumene	<0.5
CAS number: 67815-87-6	Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2- methyloxirane and 1,2-propanediol	35-65

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 4 of 13

## POR-15 FUEL TANK SEALER

### Additional information:

None known

## SECTION 4: First-aid measures

For advice, contact a Poisons Information Center (e.g. phone Australia 131 126, New Zealand 0800 764 766) or a doctor.

### Description of first aid measures

#### General notes:

Get medical attention if you feel unwell.

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position. Maintain an unobstructed airway.

Get medical advice/attention if you feel unwell.

Take precautions to ensure your own safety.

Remove source of exposure or move person to fresh air.

Get medical advice if you feel unwell or concerned.

#### After skin contact:

Rinse affected area with soap and water.

If symptoms develop or persist, seek medical attention.

Take off all contaminated clothing.

Gently blot or brush away excess product.

Wash with plenty of lukewarm, gently flowing water.

Get medical advice if skin irritation occurs or you feel unwell.

#### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes.

If symptoms develop or persist, seek medical attention.

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open.

Remove contact lenses, if present and easy to do so.

Continue rinsing for 15-20 minutes.

Get medical advice if eye irritation persists.

#### After swallowing:

Rinse mouth thoroughly.

Seek medical attention if irritation, discomfort, or vomiting persists.

### Most important symptoms and effects, both acute and delayed:

#### Acute symptoms and effects:

May cause breathing difficulty, asthma attack, nausea, allergic reaction.

#### Delayed symptoms and effects:

Not determined or not available.

### Immediate medical attention and special treatment:

#### Specific treatment:

Not determined or not available.

#### Notes for the doctor:

Contains isocyanates, consult literature for specific treatment.

### Workplace Facilities:

Not determined or not available.

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 5 of 13

## POR-15 FUEL TANK SEALER

### SECTION 5: Fire-fighting measures

#### Extinguishing media

##### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam.

##### Unsuitable extinguishing media:

Do not use a water stream as an extinguisher.

#### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors.

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere.

#### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

#### Special precautions:

Shut off sources of ignition.

Carbon monoxide and carbon dioxide may form upon combustion.

Heating causes a rise in pressure, risk of bursting and combustion.

#### Hazchem or Emergency Action Code:

Not determined or not available.

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Ensure air handling systems are operational.

Wear protective eye wear, gloves and clothing.

Beware of vapors accumulating to form explosive concentrations.

Vapors can accumulate in low areas.

#### Environmental precautions:

Should not be released into the environment.

Prevent from reaching drains, sewer or waterway.

#### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing.

Use spark-proof tools and equipment.

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders).

Dispose of contents / container in accordance with local regulations.

#### Reference to other sections:

Not determined or not applicable.

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 6 of 13

## POR-15 FUEL TANK SEALER

### SECTION 7: Handling and storage precautions

#### Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Take precautionary measures against electrostatic discharges.

Use only non-sparking tools.

#### Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Protect from freezing and physical damage.

Store in a cool, well-ventilated area.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

#### Safe packaging material

##### Suitable material:

Not determined or not applicable.

##### Unsuitable material:

Not determined or not applicable.

### SECTION 8: Exposure controls and personal protection

#### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
New Zealand	Xylene	1330-20-7	TWA: 217 mg/m <sup>3</sup> (50 ppm)
	Aluminum	7429-90-5	TWA: 10 mg/m <sup>3</sup> (metal dust, as Al); TWA: 5 mg/m <sup>3</sup> (welding fumes as Al); TWA: 5 mg/m <sup>3</sup> (Pyro Powders, as Al) TWA: 5 mg/m <sup>3</sup> (soluble salts, as Al) TWA: 2 mg/m <sup>3</sup> (as alkyls)
	Cumene	98-82-8	TWA: 125 mg/m <sup>3</sup> (25 ppm); STEL: 375 mg/m <sup>3</sup> (175 ppm)

#### Biological limit value:

Substance	Identifier	Determinant	Sampling time	Permissible limits
Xylene	1330-20-7	Methylhippuric acid	End of shift.	1.5 g/L

#### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls

Biological monitoring may also be appropriate for some substances

#### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 7 of 13

## POR-15 FUEL TANK SEALER

Use explosion-proof ventilation equipment.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

Appearance	Semi-Transparent Silver Colored Liquid
Odor	Not determined or not available.
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	>284°F (>140°C)
Flash point (closed cup)	>103°F (>39.4°C)
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	38 mmHg
Vapor density	Not determined or not available.
Density	1.09 g/mL
Relative density	Not determined or not available.
Solubilities	Not miscible.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	200-500 cPs
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

### Other information

VOC Content	310 g/L (US EPA Method 24A)
Recommended Storage Temperature	50°F - 95°F
Recommended Shelf Life	3 Years Un-Opened

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 8 of 13

## POR-15 FUEL TANK SEALER

### SECTION 10: Stability and reactivity

#### Reactivity:

Does not react under normal conditions of use and storage.

#### Chemical stability:

Stable under normal conditions of use and storage.

#### Possibility of hazardous reactions:

None under normal conditions of use and storage.

#### Conditions to avoid:

Keep away from heat, sparks and flames.

#### Incompatible materials:

None known.

#### Hazardous decomposition products:

None known.

### SECTION 11: Toxicological information

#### Acute toxicity:

**Assessment:** Harmful if inhaled

**Product data:** No data available.

#### Substance data:

Name	Route	Result
Isocyanic acid, polymethylenepolyphenylene ester	inhalation	LC50 - Rat - 490 mg/m <sup>3</sup> /4h
Methylenediphenyl diisocyanate	inhalation	LC50 - Rat - 369 mg/cu m/4 h
4,4'-Methylenediphenyl diisocyanate	inhalation	LC50 - Rat - 369 mg/cu m/4 h
1, 2, 4-Trimethylbenzene	inhalation	LC50 - Rat - 18,000 mg/m <sup>3</sup>
Xylene	dermal	LD50 - Rat - > 1,700 mg/kg
	inhalation	LC50 - Rat - 5,000 ppm/4 h

#### Skin corrosion/irritation:

**Assessment:** Causes skin irritation

**Product data:** No data available.

#### Substance data:

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2- ethanediamine, 2-methyloxirane and 1,2- propanediol	Irritating to the skin.
Isocyanic acid, polymethylenepolyphenylene ester	Moderate skin irritation.
Methylenediphenyl diisocyanate	Irritating to the skin.
4,4'-Methylenediphenyl diisocyanate	Irritating to the skin.
Naphtha (petroleum), hydrotreated heavy	Irritating to the skin.
Xylene	Irritating to the skin.
1, 2, 4-Trimethylbenzene	Irritating to the skin.

#### Serious eye damage/irritation:

**Assessment:** Causes serious eye irritation

**Product data:** No data available.



# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 9 of 13

## POR-15 FUEL TANK SEALER

### Substance data:

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2- ethanediamine, 2-methyloxirane and 1,2- propanediol	Irritating effect on the eyes.
Isocyanic acid, polymethylenepolyphenylene ester	Irritating effect on the eyes.
Methylenediphenyl diisocyanate	Moderate eye irritation.
4,4'-Methylenediphenyl diisocyanate	Moderate eye irritation.
1, 2, 4-Trimethylbenzene	Irritating effect on the eyes.

### Respiratory or skin sensitization:

**Assessment:** May cause an allergic skin reaction May cause allergy or asthma symptoms or breathing difficulties if inhaled

**Product data:** No data available.

### Substance data:

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2- ethanediamine, 2-methyloxirane and 1,2- propanediol	Sensitization possible through skin and respiratory contact.
Isocyanic acid, polymethylenepolyphenylene ester	May cause sensitization by respiratory contact.
Methylenediphenyl diisocyanate	May cause sensitization by inhalation and skin contact.
4,4'-Methylenediphenyl diisocyanate	May cause sensitization by inhalation and skin contact.
Cumene	No skin irritation
	No eye irritation

### Carcinogenicity

**Assessment:** Suspected of causing cancer

**Product data:** No data available.

### Substance data:

Name	Species	Result
Methylenediphenyl diisocyanate	Methylenediphenyl diisocyanate	May cause cancer.
4,4'-Methylenediphenyl diisocyanate		May cause cancer.
Solvent naphtha (petroleum), light arom.	Solvent naphtha (petroleum), light arom.	Component may cause cancer.

### International Agency for Research on Cancer (IARC):

Name	Classification
Isocyanic acid, polymethylenepolyphenylene ester	Group 3 - Not classifiable as to its carcinogenicity to humans
Xylene	Group 3 - Not classifiable as to its carcinogenicity to humans
Cumene	Group 2B - Possibly carcinogenic to humans

**National Toxicology Program (NTP):** None of the ingredients are listed.

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 10 of 13

## POR-15 FUEL TANK SEALER

### Substance data:

Name	Result
Solvent naphtha (petroleum), light arom.	May cause genetic defects.

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** May cause respiratory irritation. May cause drowsiness or dizziness

**Product data:** No data available.

### Substance data:

Name	Result
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2- ethanediamine, 2-methyloxirane and 1,2- propanediol	May cause respiratory tract irritation through single or repeated exposure.
Isocyanic acid, polymethylenepolyphenylene ester	Component affects the respiratory system through single and repeated exposure.
Methylenediphenyl diisocyanate	Component affects the respiratory system through single and repeated exposure.
4,4'-Methylenediphenyl diisocyanate	Component affects the respiratory system through single and repeated exposure.
Naphtha (petroleum), hydrotreated heavy	Component affects the central nervous system.
Cumene	Component affects the respiratory system.
1, 2, 4-Trimethylbenzene	Component affects the respiratory system.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Causes damage to organs through prolonged or repeated exposure

**Product data:** No data available.

**Substance data:** No data available.

### Aspiration toxicity

**Assessment:** May be fatal if swallowed and enters airways

**Product data:** No data available.

### Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airway.
Solvent naphtha (petroleum), light arom.	May be fatal if swallowed and enters airway.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

## SECTION 12: Ecological information

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 11 of 13

## POR-15 FUEL TANK SEALER

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Result
Cumene	EC50 - Daphnia magna - 1.4 mg/L - 24 h
	LC50 - Pimephales promelas - 6.32 mg/L - 96 h
1, 2, 4-Trimethylbenzene	LC50 - Pimephales promelas - 7.72 mg/L - 96 h

### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

### Hazard to the ozone layer

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.


## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

## SECTION 14: Transportation information

### Road/Rail transport: (NZS 5433:1999)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None

### International Maritime Dangerous Goods (IMDG)


# Safety Data Sheet

According to HSNO


Initial preparation date: 10.10.2017

Page 12 of 13

## POR-15 FUEL TANK SEALER

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None
ERG code	3L
Excepted quantities	E1
Passenger and cargo	60L
Cargo aircraft only	220L
Limited quantity	10L
Additional Information	No additional data

### International Air Transport Association Dangerous Goods Regulations (IATA-ICAO)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None

Transport in bulk according to Annex II of MARPOL and the IBC Code: No additional data

Bulk Name	None
Ship type	None
Pollution category	None

## SECTION 15: Regulatory information

### New Zealand Inventory of Chemicals (NZIoC):

95-63-6	1, 2, 4-Trimethylbenzene	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
1330-20-7	Xylene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester	Listed
7429-90-5	Aluminum	Listed
26447-40-5	Methylenediphenyl diisocyanate	Listed
101-68-8	4,4'-Methylenediphenyl diisocyanate	Listed
98-82-8	Cumene	Listed

# Safety Data Sheet

According to HSNO

Initial preparation date: 10.10.2017

Page 13 of 13

## POR-15 FUEL TANK SEALER

67815-87-6	Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2- methyloxirane and 1,2-propanediol	Listed
------------	--	--------

### HSNO Classification or Subclasses:

Class	GHS Category	HSNO Category
Flammable liquids	Category 3	3.1C
Skin irritation	Category 2	6.3A
Eye irritation	Category 2A	6.4A
Respiratory sensitization	Category 1	6.5A
Aspiration hazard	Category 1	6.1E
Acute toxicity (inhalation)	Category 4	6.1D
Specific target organ toxicity - single exposure	Category 3, respiratory irritation	6.1E
Specific target organ toxicity - single exposure	Category 3, central nervous system	6.9B
Specific target organ toxicity - repeated exposure	Category 1	6.9A
Carcinogenicity	Category 2	6.7B

HSNO Group Standard Name :	HSNO Approval Number:
Surface Coatings and Colourants (Flammable, Toxic [6.7])	HSR002669

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**Initial preparation date:** 10.10.2017

**Revision Date:** New

**End of Safety Data Sheet**