

DESCRIPTION:

Chassis Black Paint is an economical black bituminous paint that sets hard and glossy, providing a tough coating designed to withstand stone chips and weathering. **Chassis Black Paint** is ideally suited for use as a final finish after section repairs, welding joints and rust repairs to restore a new car look to used vehicles. Best applied over primed surfaces it confers waterproofing and sound deadening properties to the coated surface.

DIRECTIONS:

Shake well. The surface should be clean and dry – free of wax, dirt, grease, loose paint, rust, silicone and any other contamination. Apply **Chassis Black Paint** with a spray gun or brush. Remove any overspray immediately with Mineral Turpentine. If applying with a brush then thin **Chassis Black Paint** with Mineral Turpentine to slow the drying process.

APPLICATION:

Bituminous paint.

PROPERTIES:

Black liquid with petroleum odour, flash point 36°C

Available Sizes:



CBP4



CBP20



WARNING



Body Shop



Gloves



Goggles

WARNING

H226 Flammable liquid and vapour
 H302 Harmful if swallowed
 H319 Causes serious eye irritation
 Contains flammable hydrocarbon solvents

WARNING: Over exposure may result in the following conditions: slight eye, skin and respiratory irritation, dizziness, nausea, and/or loss of consciousness if swallowed. Will cause severe eye irritation. May cause irritation and blistering of skin with long-term exposure. Will cause dizziness, nausea, headaches if inhaled.

SAFETY PRECAUTIONS: Flammable liquid and vapour. Keep well away from heat, sparks and open flame. Keep container well closed. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protections. Do not eat, drink or smoke whilst using. Avoid breathing vapour. Use with adequate ventilation. Dispose empty container in a safe manner.

FIRST AID:

Eye Flush thoroughly with water for at least 15 minutes. If persistent irritation occurs, obtain medical attention.
 Skin Remove contaminated clothing. Wash contact areas with soap and water. Seek medical attention if irritation persists.
 Ingestion Do not induce vomiting. Administer vegetable oil. Seek medical attention.
 Inhalation Remove to fresh air. If rapid recovery does not occur, obtain medical attention

*If medical advice is needed have the product container/label at hand. In an emergency phone the National Poison Centre. (24 hrs): 0800 POISON [764 766].
 UN 1263. Class 3. PG III. Hazchem 2X.*

OUR VISION AND MISSION

To be the leading value-based provider to the market. We have a dedicated team to achieve excellence for our customers and a philosophy of total quality. We conduct business and create relationships in an ethical and sustainable manner with customers, our community and the environment. The value we provide our customers is the opportunity to increase profit through lower cost solutions that do not sacrifice quality or service.

ENVIRONMENTAL POLICY

Pacer is committed to leading the industry in minimising the impact of its activities on the environment. The key points of our strategy to achieve this are: Purpose built premises utilising energy efficient technology and rain water collection. Actively promoting recycling both internally and amongst our customers and suppliers. To develop and promote a product range to minimise the environmental impact of our products. We are constantly evaluating and looking at substituting to a more environmentally friendly composition of raw materials for our products. To meet or exceed all the environmental legislation that relates to our industry.

DISCLAIMER

The technical data and information provided, including the recommendations for applying & using our products, is given in good faith based on our current knowledge and experience and is believed to be accurate when applied under 'normal' conditions. In practice, the materials, surfaces or conditions are so varied that no warranty regarding the working results or any liability or guarantee can be inferred either from this information nor from a verbal consultation. It is recommended that the user makes his or her own tests to determine the suitability of the product for their own requirements.