Revised by: Simonne Moses - HSNO Consultant SDS No: 1.1

# Safety Data Sheet 650 Quick Set Activator

Classified as: Hazardous according to the EPA Hazardous Substances (Minimum Degrees of Hazard) Notice 2017.

# Section 1: SUBSTANCE AND SUPPLIER DETAILS

**Product Name:** 650 Quick Set Activator

Supplier: RA Johnstone & Co Ltd trading as

**RJP Performance Coatings** 

33 Ha Crescent,

Wiri, Auckland 2104

New Zealand

**Phone:** +64 9 25000 91

Recommended Use: Cyanoacrylate Activator

In Case of Emergency Contact:

CHEMCALL: 0800 CHEMCALL (243 622)

# **Section 2: HAZARDS IDENTIFICATION**

Classified as a Dangerous Good for Transport.

Classified as hazardous according to criteria in the EPA Hazardous Substances (Minimum Degrees of Hazards) Notice 2017.

Classified under the group standard "Surface Coatings and Colourants (Flammable) Group Standard 2017"

HSNO APPROVAL NUMBER: HSR002662

HSNO CLASSIFICATIONS: 3.1B - Flammable liquid, high hazard

6.1E – Acutely toxic, oral 6.3B – Mild skin irritant 6.4A – Eye irritant

6.9B – Harmful to human target organs or systems (via oral route)

GHS Classification: Flammable liquid – Category 2

Acute toxicity, oral – Category 5 Skin corrosion/irritation – Category 3 Serious eye damage/irritation – Category 2

Specific target organ systemic toxicity (single exposure) – Category 2

Hazard Statements:

H225 Highly flammable liquid and vapour H303 May be harmful if swallowed H316 Causes mild skin irritation H319 Causes serious eye irritation

Revised by: Simonne Moses - HSNO Consultant SDS No: 1.1

H371 May cause damage to organs via ingestion

#### GHS Pictograms:







## **DANGER**

#### **PREVENTION STATEMENTS:**

P102 - Keep out of reach of children.

P103 - Read label before use.

P210 – Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 – Use explosion-proof electrical/ventilating/lighting equipment.

P242 – Use only non-sparking tools.

P243 – Take precautionary measures against static discharge.

P260 – Do not breathe fumes/vapours.

P264 – Wash hands, exposed skin, thoroughly after handling.

P270 – Do not eat, drink or smoke when using this product.

P280 – Wear protective gloves, protective clothing, eye protection, face protection.

#### **RESPONSE STATEMENTS:**

P101 – If medical advice is needed, have product container or label at hand.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P370 + P378 – In case of fire: Use alcohol resistant foam or dry chemical for extinction.

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332 + P313 – IF skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 – IF eye irritation persists: Get medical advice/attention.

P309 + P311 – IF exposed or if you feel unwell: Call a POISON CENTRE or doctor/physician.

#### **S**TORAGE

P403 + P235 – Store in a well-ventilated place. Keep cool.

P405 – Store locked up.

#### DISPOSAL

P501 - In accordance with the EPA Hazardous Substances (Disposal) Notice 2017. Refer to Section 13 of this SDS.

# **Section 3: COMPOSITION / INFORMATION ON INGREDIENTS**

Main Component	CAS Number	Concentration
Acetone	67-64-1	95 - 99%
N,N-Dimethyl-p-toluidine	99-97-8	1 - 5%

Revised by: Simonne Moses - HSNO Consultant SDS No: 1.1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Note: If Chemical Name/CAS No is "proprietary" or "trade secret and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret as it is commercially sensitive.

# **Section 4: FIRST AID MEASURES**

Workplace Facilities

Required:

Eye wash and safety shower facilities should be provided.

If Inhaled: Remove to fresh air. Seek medical attention if symptoms persist.

In Contact with Eye: Hold eyes open, flush with water for at least 15 minutes. Seek medical attention if

irritation develops and persists.

In Contact with Skin: Wash skin with plenty of water, while removing contaminated clothing and shoes. Wash

contaminated clothing before re-use. Seek medical attention if skin irritation develops

and persists.

If Swallowed: DO NOT INDUCE VOMITING, Rinse mouth, Give small quantities of water, Never give

anything by mouth to an unconscious person. Seek immediate medical attention. If

vomiting occurs, keep head below hips to prevent aspiration to lungs.

Advice to Doctor: Treat symptomatically.

# **Section 5: FIRE FIGHTING MEASURES**

Fire/Explosion Hazard: Product is flammable. Product may accumulate static charges.

Suitable Extinguishing

Media:

Cool containers using water spray. Do not use water jet. Extinguish fire with

alcohol resistant foam or dry powder.

**Precautions in Connection** 

with Fire:

Combustion may produce oxides of carbon.

Advice for firefighters: Wear full firefighting gear and self-contained breathing apparatus.

# Section 6: ACCIDENTAL RELEASE MEASURES

An emergency response plan is required under Part 5 of the Health and Safety at Work (Hazardous Substances) Regulations 2017 when held in quantities greater than 1,000L.

Precautions: Clear area of all unprotected personnel. Keep unnecessary and unprotected

personnel from entering area. Warn those occupants downstream of spill of fire

and explosion hazard. Eliminate all sources of ignition.

Simonne Moses - HSNO Consultant Revised by: SDS No: 1.1

Suitable Protective **Equipment:** 

Emergency responders must use personal protective equipment, including gloves, protective overalls and footwear, safety goggles or face shield and respiratory

protection if there is a risk of inhaling vapours.

Spill or Leak Procedures. Shut off source of spill if safe to do so. Contain the spill and use absorbent material

such as sand or earth to soak up spill. Use non-sparking tools to collect spill and absorbent material into a waste container. Ensure waste container is properly

labelled.

**Waste Disposal Methods:** Dispose of as per Section 13.

**Emergency preparation:** Ensure there is appropriate and adequate personal protective equipment, trained

personnel and clean up materials for management of accidental release.

# Section 7: HANDLING AND STORAGE

Precautions for Safe Handling:

Avoid contact with skin and eyes. Do not breathe vapours. Do not eat, drink or smoke when using this product. Remove contaminated clothing and wash hands and face before entering eating areas. Open containers slowly to control possible pressure release. Product may accumulate static charges. Use proper grounding procedures. Keep away from ignition sources. Do not pressurise, heat, cut or weld containers. Do not re-use empty containers unless they have been commercially cleaned or reconditioned. Vapours are heavier than air. Do not

enter confined spaces where vapours may have accumulated.

Storage: Keep container tightly closed when not in use. Store in original container in a

cool, dry, well-ventilated area. Store away from ignition sources and

incompatibles (refer Section 10). Keep out of direct sunlight.

Site Storage Requirements: Site Signage will be required when quantities exceed 250L.

## Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace Exposure Standards NZ:

No Workplace Exposure Standards have been established for this product but

have been established for the following constituent:

Acetone - TWA 500 ppm, 1,185 mg/m³, STEL 1,000 ppm, 2,375 mg/m³

**Engineering Controls:** 

Eyewash facilities and safety showers should be provided in the work area where there is a risk of exposure to eyes and skin. Vapours are heavier than air and care must be taken to prevent vapour build up in hollows or sumps. If use results in exposure to fumes/vapours, use engineering controls such as local exhaust ventilation to ensure workers are not exposed to concentrations that exceed

workplace exposure standards.

**Personal Protective Equipment:** 

Avoid contact with the skin and eyes. Avoid inhaling fumes/vapours.

Wear protective gloves that are resistant to the product. Refer to Australian and Hand protection:

New Zealand Standard AS/NZS 2161 for protective gloves.

Use protective clothing. Remove any contaminated clothing to avoid prolonged Skin and body protection:

contact with the skin. Wash work clothes regularly. Refer to Australian and New

Zealand Standard AS/NZS 4501 for occupational protective clothing.

Simonne Moses - HSNO Consultant Revised by: SDS No: 1.1

Eye protection: Use chemical safety glasses with side shields or chemical goggles to protect

eyes. If handling large quantities also use a face shield to prevent splashes to the

face. Refer to AS/NZS 1336 for suitable eye and face protection.

Respiratory protection: Where there is inadequate ventilation, and use results in exposure to vapours,

use a respirator fitted with solvent vapour cartridges and particulate filters. Refer

to AS/NZS 1715 and AS/NZS 1716 for suitable respiratory protection.

Other information: PPE selected must be impervious to the substance. Do not eat, smoke or drink

> where material is handled, processed or stored. Wash hands carefully before eating, drinking or smoking. Handle in accordance with safe industrial hygiene

practices.

# Section 9: PHYSICAL AND CHEMICAL PROPERTIES

**Description:** Liquid Colour: Clear, colourless Odour: Mild solvent **Odour Threshold:** Not determined

Completely Not determined pH: Solubility (water, 25°C): soluble

Melting/Freezing point: -95°C **Boiling Point:** 56.1°C Flammability: Flammable Flash Point: -26°C

LEL/UEL: 2.6 / 12.8 Vapour Pressure (20°C): 175 mmHg Not determined Not determined **Decomposition Temp: Auto-Ignition Temp:** 

**Evaporation Rate (nButyl Specific Gravity:** 0.80 g/cm3 5.6 Acetate =1):

Partition Coefficient: n-

octanol/water

Not determined

Viscosity:

Not available

Vapour Density: 2.0 VOC: 791 g/L

# Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal cool, dry storage conditions. Protect from heat.

Not reactive under normal conditions of use. Mixing large quantities with Reactivity:

cyanoacrylate adhesives will cause violent reaction.

**Conditions to Avoid:** Heat, sparks, open flames and other sources of ignition. Store out of direct

sunlight.

Incompatibility: Keep away from oxidising agents, combustible products such as paper, wood,

cardboard.

**Hazardous Decomposition:** Decomposes during combustion to form oxides of carbon.

# Section 11: TOXICOLOGICAL INFORMATION

## **Acute Exposure**

**Acute Toxicity:** LD50 oral  $> 2000 - < 5000 \,\text{mg/kg}$ 

LD50 dermal > 5000 mg/kg LC50 inhalation > 20 mg/L

Inhalation: Not acutely toxic by inhalation. Inhalation of large quantities of vapour (> 20mg/L

Revised by: Simonne Moses - HSNO Consultant SDS No: 1.1

concentration in air) may cause drowsiness/dizziness and respiratory tract

irritation.

Ingestion: May be harmful if swallowed.

Skin Contact: Mild skin irritant.

Eye Contact: Eye irritant.

Sensitiser: Not expected to be a respiratory or contact sensitiser.

**Chronic Exposure:** 

Mutagen/Carcinogen/Reproductive Toxicant

No known effects.

**Specific Target Organ Systemic** 

Toxicity:

Product is harmful to human target organs or systems via ingestion.

Toxicity data is based on hazardous ingredient information and information in the

EPA Chemical Classification and Identification Database.

# **Section 12: ECOLOGICAL INFORMATION**

**Ecotoxicity:**  $LC_{50} > 100 \text{ mg/L}$  in the aquatic environment.

Product is not expected to be environmentally hazardous.

Persistence/degradability: Not determined

Bioaccumulation: Not determined

Mobility: Product is readily soluble in water.

Ecotoxicity data is based on hazardous ingredient information.

# **Section 13: DISPOSAL CONSIDERATIONS**

Disposal: Recycle and reuse wherever possible. Dispose of waste product via an approved

waste disposal contractor.

Disposal of Packaging: Packaging may contain product residues and should be treated as hazardous.

Dispose of packaging via an approved waste disposal contractor.

# **Section 14: TRANSPORT INFORMATION**

Classified as a Dangerous Good for transport in accordance with NZS5433:2012, IMDG or IATA.



Revised by: Simonne Moses - HSNO Consultant SDS No: 1.1

NZS5433:2012 UN No: 1090

Proper Shipping Name: Acetone

Class: 3

Packing Group: II Hazchem Code: 3Y

IMDG:

UN No: 1090

Proper Shipping Name: Acetone

Class: 3

Packing Group: II Marine Pollutant: No EmS: F-E, S-D

IATA:

UN No: 1090

Proper Shipping Name: Acetone

Class: 3

Packing Group: II

Ensure transportation methods prevent leakage from packages and collapsing loads.

# **Section 15: REGULATORY INFORMATION**

Group Standard Allocation: Surface Coatings and Colourants (Flammable) Group Standard 2017

HSNO Approval Code: HSR002662

HSNO Classifications: 3.1B Flammable liquid, high hazard

6.1E Acutely toxic, oral 6.3B Mild skin irritant 6.4A Eye irritant

6.9B Harmful to human target organs or systems

This substance triggers: Compliance Certificate 100L (containers >5L), 250L

(containers up to 5L)

Certified Handler N/A

Quantity that must be secured 250L (containers >5L), 500L

(containers up to 5L)

Emergency Response Plan 1,000L Secondary Containment 1,000L Signage 250L

Fire Extinguishers 2 required for quantities > 250L

This substance is not required to be Tracked. All workplace personnel handling this substance are required to be trained on the safe handling and PPE

requirements for the hazards associated with this substance.

Revised by: Simonne Moses - HSNO Consultant SDS No: 1.1

NZIOC: All hazardous ingredients are listed in the NZ Inventory of Chemicals.

# **Section 16: OTHER INFORMATION**

The information provided in this Safety Data Sheet relates only to the specific material designated herein. This Safety Data Sheet summarises our best knowledge of the health and safety hazard information of the product and how to safely handle the product in the workplace. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products.

This substance is approved under HSNO for use as a surface coating. All reasonable care has been taken to ensure that the information and advice contained herein are from sources believed to be reliable and to represent the most up-to-date knowledge available at the date given in Section 16. No liability is assumed for any damages related to the use or misuse of this substance.

All chemical materials may present unknown hazards as people have varying degrees of sensitivity to chemicals. Therefore, this product should be used with caution. The information herein is given in good faith, but no warranty, express or implied is made.

SDS Issued: 20/8/2020

Reason for Revision: Update to New Zealand regulatory requirements.

Note: This SDS has been derived from an American SDS which is compliant with US regulatory requirements.

References:

EPA NZ Chemical Classification and Information Database
EPA Guide: Assigning a Hazardous Substance to a Group Standard, 2014

Supplier SDS: International Epoxies and Sealers, 650 Quick Set Activator, March 2014

**END OF SAFETY DATA SHEET**