

Safety Data Sheet

in accordance with HSNO

mipa

Professional Coating Systems

Printing date 31.03.2021

Version number 12

Revision: 31.03.2021

1 Identification of the substance or mixture and of the supplier· **Product identifier**· **Trade name: Mipa AC 2K-Acryl Autolack**· **Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture Paint**· **Details of the supplier of the safety data sheet**· **Manufacturer/Supplier:**

MIPA SE

Am Oberen Moos 1

D-84051 Essenbach

Tel.: +49(0)8703-922-0

Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.comwww.mipa-paints.com· **Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)**Distributor in New Zealand:****Mipa New Zealand**33 Ha Crescent, Wiri, Auckland 2104
New Zealand

Phone: +64 9 25000 91

Fax: +64 9 25000 92

Email: sales@mipa.nzWeb: www.mipa.nz**24hr Emergency Assistance in New Zealand**

National Poison Control Centre: 0800 POISON [764 766]

2 Hazards identification· **Classification of the substance or mixture**

flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



STOT SE 3

H336 May cause drowsiness or dizziness.

Acute Tox. 5

H333 May be harmful if inhaled.

Skin Corr. 3

H316 Causes mild skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **Label elements**· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** Warning· **Hazard-determining components of labelling:**

Xylene

2-Butoxyethyl acetate

· **Hazard statements**

H226 Flammable liquid and vapour.

H333 May be harmful if inhaled.

H316 Causes mild skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

(Contd. on page 2)

-NZ-

Trade name: Mipa AC 2K-Acryl Autolack

(Contd. of page 1)

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- **Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

3 Composition/Information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

123-86-4	n-Butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	≤20%
108-65-6	2-Methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336; Acute Tox. 5, H333	10-25%
64742-95-6	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336; Acute Tox. 5, H303; Acute Tox. 5, H313	5-<10%
1330-20-7	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	2.5-<5%
112-07-2	2-Butoxyethyl acetate ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Flam. Liq. 4, H227	2.5-<5%
26761-45-5	2,3-epoxypropyl neodecanoate ⚠ Muta. 2, H341; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1, H317; Acute Tox. 5, H313; Aquatic Acute 2, H401	≥0.25-<1%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Generally the product does not irritate the skin.
Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

-NZ

(Contd. on page 3)

Trade name: Mipa AC 2K-Acryl Autolack

(Contd. of page 2)

5 Fire fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

—NZ—

Trade name: Mipa AC 2K-Acryl Autolack

(Contd. of page 3)

· **Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****123-86-4 n-Butyl acetate**

WES (New Zealand)	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm
IOELV (EU)	Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm

108-65-6 2-Methoxy-1-methylethyl acetate

IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
------------	--

1330-20-7 Xylene

WES (New Zealand)	Long-term value: 217 mg/m ³ , 50 ppm
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin

112-07-2 2-Butoxyethyl acetate

IOELV (EU)	Short-term value: 333 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Skin
------------	---

· **Additional information:** The lists valid during the making were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Trade name: Mipa AC 2K-Acryl Autolack

(Contd. of page 4)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:**

Fluid

Colour:

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition****Melting point/freezing point:**

Undetermined.

Initial boiling point and boiling range: 124-128 °C· **Flash point:**

29 °C (DIN EN ISO 1523:2002)

· **Flammability (solid, gas):**

Not applicable.

· **Ignition temperature:**

450 °C (DIN 51794)

· **Decomposition temperature:**

Not determined.

· **Auto-ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:****Lower:**

1.2 Vol %

Upper:

10.8 Vol %

· **Vapour pressure at 20 °C:**

10.7 hPa

· **Density at 20 °C:**1.118 g/cm³ (DIN EN ISO 2811-1)· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:**

Not determined.

· **Viscosity:****Dynamic:**

Not determined.

Kinematic at 20 °C:

90-110 s (DIN 53211/4)

· **Solvent content:****VOC (EC)**

41.64 %

Solids content (weight-%):

58.4 %

(Contd. on page 6)

Trade name: Mipa AC 2K-Acryl Autolack

(Contd. of page 5)

Other information

No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· LD/LC50 values relevant for classification:		
64742-95-6 Hydrocarbons, C9, aromatics		
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

-NZ-

(Contd. on page 7)

Safety Data Sheet

in accordance with HSNO

mipa

Professional Coating Systems

Printing date 31.03.2021

Version number 12

Revision: 31.03.2021

Trade name: Mipa AC 2K-Acryl Autolack

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· ADR, IMDG, IATA	UN1263
· UN proper shipping name	
· ADR	UN1263 PAINT
· IMDG, IATA	PAINT
· Transport hazard class(es)	
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	
· ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	≤ 450 l: -

(Contd. on page 8)

-NZ-

Safety Data Sheet

in accordance with HSNO

Printing date 31.03.2021

Version number 12

Revision: 31.03.2021

Trade name: Mipa AC 2K-Acryl Autolack

(Contd. of page 7)

· IMDG	
· Limited quantities (LQ)	5L
· Remarks:	≤ 30 l: -
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **HSNO Approval numbers**

123-86-4	n-Butyl acetate	HSR001091
108-65-6	2-Methoxy-1-methylethyl acetate	HSR001219
64742-95-6	Hydrocarbons, C9, aromatics	HSR001503
1330-20-7	Xylene	HSR000983
112-07-2	2-Butoxyethyl acetate	HSR001155
26761-45-5	2,3-epoxypropyl neodecanoate	HSR007482

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labelling:**

Xylene
2-Butoxyethyl acetate

- **Hazard statements**

H226 Flammable liquid and vapour.
H333 May be harmful if inhaled.
H316 Causes mild skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

- **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 9)

NZ

Trade name: Mipa AC 2K-Acryl Autolack

(Contd. of page 8)

· **National regulations:**· **Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	25-50

· **Other regulations, limitations and prohibitive regulations**

Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Approval Number: The HSNO Approval Number for this Group Standard is HSR002662.

Refer also to the Site & Storage requirements document.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H333 May be harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· **Contact:**· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 5: Acute toxicity – Category 5

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Corr. 3: Skin corrosion/irritation – Category 3

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity – Category 2

(Contd. on page 10)

Safety Data Sheet

in accordance with HSNO

Printing date 31.03.2021

Version number 12

Revision: 31.03.2021

Trade name: Mipa AC 2K-Acryl Autolack

(Contd. of page 9)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

NZ