

in accordance with HSNO

Revision: 22.09.2023 Printing date 28.09.2023 Version number 44

1 Identification of the substance or mixture and of the supplier

· Product identifier

· Trade name: Mipa 1K-Klarlack C 10

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Clear coating material, Varnish

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

Importer in New Zealand: **RJP Performance Coatings** 33 Ha Crescent, Wiri Auckland 2104 Phone: 09 25000 91

Email: sales@mipa.nz Web: www.mipa.nz

24HR Emergency Assistance in New Zealand: National Poison Control Centre: 0800 POISON [764 766]

· Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

2 Hazards identification

· Classification of the substance or mixture



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

H361 Suspected of damaging fertility or the unborn child. Repr. 2

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling: n-Butyl acetate

(Contd. on page 2)



in accordance with HSNO

Printing date 28.09.2023 Version number 44 Revision: 22.09.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 1)

Xylene

Reaction mass of pentamethyl-piperidylsebacate

Methyl ethyl ketone

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/Information on ingredients

· Chemical characterisation: Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

123-86-4	n-Butyl acetate	25-50%
	🚸 Flam. Liq. 3, H226; ∿ STOT SE 3, H336	
78-93-3	Methyl ethyl ketone	10-25%
	🚸 Flam. Liq. 2, H225; 🕔 Eye Irrit. 2, H319; STOT SE 3, H336	
67-64-1	acetone	5-<10%
	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	
1330-20-7	Xylene	5-<10%
	♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
64742-95-6	Hydrocarbons, C9, aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ↑ STOT SE 3, H335-H336	1-<2.5%
100-41-4	Ethylbenzene	<2.5%
	 ♠ Flam. Liq. 2, H225; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 	



in accordance with HSNO

Revision: 22.09.2023 Printing date 28.09.2023 Version number 44

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 2)

1065336-91-5 Reaction mass of pentamethyl-piperidylsebacate

≥0.1-<0.25%

🕸 Repr. 2, H361; 🔖 Aquatic Acute 1, H400; Aquatic Chronic 1,

H410; ♠ Skin Sens. 1A, H317

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek immediate medical advice.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.



in accordance with HSNO

Printing date 28.09.2023 Version number 44 Revision: 22.09.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities: No further data: see section 7.

Additional informati	ion about design of technical facilities: No further data; see section /.
Ingredients with lim	it values that require monitoring at the workplace:
123-86-4 n-Butyl ace	etate
WES (New Zealand)	Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm
IOELV (EU)	Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm
78-93-3 Methyl ethyl	ketone
WES (New Zealand)	Short-term value: 890 mg/m³, 300 ppm Long-term value: 445 mg/m³, 150 ppm bio
IOELV (EU)	Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm
67-64-1 acetone	
WES (New Zealand)	Short-term value: 2375 mg/m³, 1000 ppm Long-term value: 1185 mg/m³, 500 ppm bio
IOELV (EU)	Long-term value: 1210 mg/m³, 500 ppm
1330-20-7 Xylene	
WES (New Zealand)	Long-term value: 217 mg/m³, 50 ppm oto
IOELV (EU)	Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin
100-41-4 Ethylbenzene	
WES (New Zealand)	Short-term value: 176 mg/m³, 40 ppm Long-term value: 88 mg/m³, 20 ppm skin, oto

(Contd. on page 5)



in accordance with HSNO

Printing date 28.09.2023 Version number 44 Revision: 22.09.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 4)

IOELV (EU)

Short-term value: 884 mg/m³, 200 ppm
Long-term value: 442 mg/m³, 100 ppm
Skin

- Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

· Form: Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

Change in condition

· Melting point/freezing point: Undetermined.

(Contd. on page 6)



in accordance with HSNO

Printing date 28.09.2023 Version number 44 Revision: 22.09.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 5)

Initial boiling point and boiling range: 56 °C

Flash point:
 Flammability (solid, gas):
 Auto-ignition temperature:
 Decomposition temperature:
 Mot determined.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.2 Vol %
 Upper: 11.5 Vol %
 Vapour pressure at 20 °C: 233 hPa
 Vapour pressure at 50 °C: 800 hPa

Density at 20 °C: 0.903 g/cm³ (DIN 53217)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

• water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic at 20 °C: 13 s (DIN 53211/4)

· Solvent content:

· VOC (EC) 81.17 % · Solids content (weight-%): 18.7 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Suspected of damaging fertility or the unborn child.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard May be fatal if swallowed and enters airways.



in accordance with HSNO

Printing date 28.09.2023 Version number 44 Revision: 22.09.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

٠ ر	א-אוע	umber	
-			

· NZS, IMDG, IATA UN1263

· UN proper shipping name

· NZS UN1263 PAINT

· **IMDG, IATA** PAINT

- · Transport hazard class(es)
- · NZS



· Class 3 (F1) Flammable liquids.

· Label

(Contd. on page 8)



in accordance with HSNO

Printing date 28.09.2023 Version number 44 Revision: 22.09.2023

II

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 7)

· IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· Packing group · NZS, IMDG, IATA

· Environmental hazards:
· Marine pollutant:

No

· Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-E · Stowage Category B

· Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· NZS

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

5L
2
D/E

· IMDG

· Limited quantities (LQ) 5L

· UN "Model Regulation": UN 1263 PAINT, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· HSNO Approval numbers			
	123-86-4	n-Butyl acetate	HSR001091
	78-93-3	Methyl ethyl ketone	HSR001190
	67-64-1	acetone	HSR001070
	1330-20-7	Xylene	HSR000983
	100-41-4	Ethylbenzene	HSR001151

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms







GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

n-Butyl acetate

(Contd. on page 9)



in accordance with HSNO

Printing date 28.09.2023 Version number 44 Revision: 22.09.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 8)

Xylene

Reaction mass of pentamethyl-piperidylsebacate

Methyl ethyl ketone

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

· Other regulations, limitations and prohibitive regulations

Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Approval Number: The HSNO Approval Number for this Group Standard is HSR002662. Refer also to the Site & Storage requirements document.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

(Contd. on page 10)



in accordance with HSNO

Printing date 28.09.2023 Version number 44 Revision: 22.09.2023

Trade name: Mipa 1K-Klarlack C 10

(Contd. of page 9)

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Contact:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

ΝZ

^{*} Data compared to the previous version altered.