

in accordance with HSNO

Printing date 22.05.2023 Version number 4 Revision: 22.05.2023

# 1 Identification of the substance or mixture and of the supplier

· Product identifier

· Trade name: Mipa Unterbodenschutz Wax Spritzware

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Surface protection

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

Importer in New Zealand: RJP Performance Coatings 33 Ha Crescent, Wiri Auckland 2104

Phone: 09 25000 91 Email: sales@mipa.nz Web: www.mipa.nz

24HR Emergency Assistance in New Zealand:

National Poison Control Centre: 0800 POISON [764 766]

· Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

### 2 Hazards identification

· Classification of the substance or mixture



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 2)



in accordance with HSNO

Printing date 22.05.2023 Version number 4 Revision: 22.05.2023

Trade name: Mipa Unterbodenschutz Wax Spritzware

(Contd. of page 1)

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

# 3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

25-50%

🚸 Flam. Liq. 3, H226; 🕸 Asp. Tox. 1, H304; 산 STOT SE 3, H336

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire fighting measures

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.



in accordance with HSNO

Printing date 22.05.2023 Version number 4 Revision: 22.05.2023

Trade name: Mipa Unterbodenschutz Wax Spritzware

(Contd. of page 2)

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)



in accordance with HSNO

Printing date 22.05.2023 Version number 4 Revision: 22.05.2023

Trade name: Mipa Unterbodenschutz Wax Spritzware

(Contd. of page 3)

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

· General Information

· Appearance:

· Form: Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

· Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 155 °C

• Flash point: 39 °C (DIN EN ISO 1523:2002)

· Flammability (solid, gas): Flammable.

Auto-ignition temperature:
 Decomposition temperature:
 Not determined.

· **Ignition temperature:** Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

Lower: Not determined.
 Upper: Not determined.
 Vapour pressure: Not determined.

**Density at 20 °C:** 0.839 g/cm³ (DIN EN ISO 2811-1)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

• Dynamic at 20 °C: 2,000-2,500 mPas • Kinematic: Not determined.

· Solvent content:

· Water: 0.1 %
 · VOC (EC) 50.29 %
 · Solids content (weight-%): 49.6 %

· Other information No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 5)



in accordance with HSNO

Printing date 22.05.2023 Version number 4 Revision: 22.05.2023

Trade name: Mipa Unterbodenschutz Wax Spritzware

· Hazardous decomposition products: Carbon monoxide

(Contd. of page 4)

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### 12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

		_		/		<b>6</b>	
-71	//		·Iat·	7 P			
- 1	-			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	-		nation

· UN-Number

· NZS, IMDG, IATA UN1139

· UN proper shipping name

NZS UN1139 COATING SOLUTION

· IMDG, IATA COATING SOLUTION

(Contd. on page 6)



in accordance with HSNO

Revision: 22.05.2023 Printing date 22.05.2023 Version number 4

Trade name: Mipa Unterbodenschutz Wax Spritzware

(Contd. of page 5)

· Transport hazard class(es)

· NZS



3 (F1) Flammable liquids. · Class

· Label

· IMDG, IATA



3 Flammable liquids. · Class

·Label 3

· Packing group

· NZS, IMDG, IATA Ш

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30 · EMS Number: F-E,S-E

· Stowage Category

· Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· NZS

· Limited quantities (LQ) 5L · Transport category 3 · Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L

UN 1139 COATING SOLUTION, 3, III · UN "Model Regulation":

### 15 Regulatory information

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms





**NEW ZEALAND:** 

Flammable Liquid & Vapour Class 3 1C Class 6.9B Narcotic Effect

HSR002662 Surface Coatings & Colourants (Flammable)

· Signal word Warning

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

(Contd. on page 7)



in accordance with HSNO

Printing date 22.05.2023 Version number 4 Revision: 22.05.2023

Trade name: Mipa Unterbodenschutz Wax Spritzware

(Contd. of page 6)

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

#### · National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %				
NK	50-100				

#### · Other regulations, limitations and prohibitive regulations

Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Approval Number: The HSNO Approval Number for this Group Standard is HSR002662.

Refer also to the Site & Storage requirements document.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

### · Contact:

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1