

## 1 Identification of the substance or mixture and of the supplier

· **Product identifier**

· **Trade name:** *Mipa 2K-Express-Klarlack CX 11*

· **Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture** *Clear coating material, Varnish*

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

MIPA SE

Am Oberen Moos 1

D-84051 Essenbach

Tel.: +49 8703 92 20

Fax.: +49 8703 92 21 00

e-mail: [sdb-registratur@mipa-paints.com](mailto:sdb-registratur@mipa-paints.com)

[www.mipa-paints.com](http://www.mipa-paints.com)

**Importer in New Zealand:**

RJP Performance Coatings

33 Ha Crescent, Wiri

Auckland 2104

Phone: 09 25000 91

Email: [sales@mipa.nz](mailto:sales@mipa.nz)

Web: [www.mipa.nz](http://www.mipa.nz)

**24HR Emergency Assistance in New Zealand:**

National Poison Control Centre: 0800 POISON [764 766]

· **Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

## 2 Hazards identification

· **Classification of the substance or mixture**



flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



health hazard

Repr. 1

H360 May damage fertility or the unborn child.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

STOT SE 3

H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

GHS09

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

5-methylhexan-2-one

**Trade name: Mipa 2K-Express-Klarlack CX 11**

(Contd. of page 1)

*n*-Butyl acetate

acetone

dibutyltin dilaurate

**Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**3 Composition/Information on ingredients**

**Chemical characterisation: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

123-86-4	<i>n</i> -Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10-25%
110-12-3	5-methylhexan-2-one Flam. Liq. 3, H226; Repr. 2, H361; Acute Tox. 4, H332	10-25%
67-64-1	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	≥10-<15%
64742-95-6	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	5-<10%
78-93-3	Methyl ethyl ketone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<10%
1065336-91-5	Reaction mass of pentamethyl-piperidylsebacate Repr. 2, H361; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.25-<1%
77-58-7	dibutyltin dilaurate Muta. 2, H341; Repr. 1, H360; STOT SE 1, H370; STOT RE 1, H372; Skin Corr. 1C, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≥0.25-<0.3%
7575-23-7	Pentaerythritol tetrakis(3-mercaptopropionate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1A, H317	≥0.1-<0.25%

(Contd. on page 3)

**Trade name: Mipa 2K-Express-Klarlack CX 11**

(Contd. of page 2)  
· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**  
· **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Fire fighting measures

- **Suitable extinguishing agents:**  
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Protective equipment:** No special measures required.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.

(Contd. on page 4)

**Trade name: Mipa 2K-Express-Klarlack CX 11**

(Contd. of page 3)

Protect against electrostatic charges.

Keep respiratory protective device available.

**Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Storage class:** 3

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**

### 123-86-4 n-Butyl acetate

WES (New Zealand) Short-term value: 950 mg/m<sup>3</sup>, 200 ppm

Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

IOELV (EU) Short-term value: 723 mg/m<sup>3</sup>, 150 ppm

Long-term value: 241 mg/m<sup>3</sup>, 50 ppm

### 110-12-3 5-methylhexan-2-one

WES (New Zealand) Long-term value: 234 mg/m<sup>3</sup>, 50 ppm

IOELV (EU) Long-term value: 95 mg/m<sup>3</sup>, 20 ppm

### 67-64-1 acetone

WES (New Zealand) Short-term value: 2375 mg/m<sup>3</sup>, 1000 ppm

Long-term value: 1185 mg/m<sup>3</sup>, 500 ppm  
bio

IOELV (EU) Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

### 78-93-3 Methyl ethyl ketone

WES (New Zealand) Short-term value: 890 mg/m<sup>3</sup>, 300 ppm

Long-term value: 445 mg/m<sup>3</sup>, 150 ppm  
bio

IOELV (EU) Short-term value: 900 mg/m<sup>3</sup>, 300 ppm

Long-term value: 600 mg/m<sup>3</sup>, 200 ppm

### 77-58-7 dibutyltin dilaurate

WES (New Zealand) Short-term value: 0.2 mg/m<sup>3</sup>

Long-term value: 0.1 mg/m<sup>3</sup>  
skin, as Sn

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)

**Trade name: Mipa 2K-Express-Klarlack CX 11**

(Contd. of page 4)

· **Respiratory protection:**



*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.*

· **Protection of hands:**

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*



*Protective gloves (EN 374)*

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

· **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

· **Breakthrough time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

· **Eye protection:**



*Tightly sealed goggles*

## 9 Physical and chemical properties

· **General Information**

· **Appearance:**

· **Form:**

*Fluid*

· **Colour:**

*According to product specification*

· **Odour:**

*Characteristic*

· **Odour threshold:**

*Not determined.*

· **pH-value:**

*Not determined.*

· **Change in condition**

· **Melting point/freezing point:**

*Undetermined.*

· **Initial boiling point and boiling range:** 56 °C

· **Flash point:**

*-17 °C (DIN EN ISO 1523:2002)*

· **Flammability (solid, gas):**

*Highly flammable.*

· **Auto-ignition temperature:**

*370 °C (DIN 51794)*

· **Decomposition temperature:**

*Not determined.*

· **Ignition temperature:**

*Product is not selfigniting.*

· **Explosive properties:**

*Product is not explosive. However, formation of explosive air/vapour mixtures are possible.*

· **Explosion limits:**

· **Lower:**

*1.2 Vol %*

· **Upper:**

*13 Vol %*

· **Vapour pressure at 20 °C:**

*233 hPa*

· **Vapour pressure at 50 °C:**

*800 hPa*

· **Density at 20 °C:**

*0.913 g/cm<sup>3</sup> (DIN EN ISO 2811-1)*

(Contd. on page 6)

**Trade name: Mipa 2K-Express-Klarlack CX 11**

(Contd. of page 5)

· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Dynamic:</b>	Not determined.
· <b>Kinematic at 20 °C:</b>	11-13 s (DIN 53211/4)
· <b>Solvent content:</b>	
· <b>VOC (EC)</b>	67.23 %
· <b>Solids content (weight-%):</b>	32.8 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** May damage fertility or the unborn child.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) : hazardous for water  
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)



**Trade name: Mipa 2K-Express-Klarlack CX 11**

(Contd. of page 6)

*Danger to drinking water if even small quantities leak into the ground.*

*Also poisonous for fish and plankton in water bodies.*

*Toxic for aquatic organisms*

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

*Must not be disposed together with household garbage. Do not allow product to reach sewage system.*

· **Uncleaned packaging:**

· **Recommendation:**

*Packagings that may not be cleansed are to be disposed of in the same manner as the product.*

### 14 Transport information

· **UN-Number**

· **NZS, IMDG, IATA**

UN1263

· **UN proper shipping name**

· **NZS**

UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS

· **IMDG**

PAINT (Solvent naphtha, Polythiols), MARINE POLLUTANT

· **IATA**

PAINT

· **Transport hazard class(es)**

· **NZS**



· **Class**

3 (F1) Flammable liquids.

· **Label**

3

· **IMDG**



· **Class**

3 Flammable liquids.

· **Label**

3

· **IATA**



· **Class**

3 Flammable liquids.

(Contd. on page 8)

**Trade name: Mipa 2K-Express-Klarlack CX 11**

(Contd. of page 7)

· <b>Label</b>	3
· <b>Packing group</b> · <b>NZS, IMDG, IATA</b>	II
· <b>Environmental hazards:</b> · <b>Marine pollutant:</b> · <b>Special marking (NZS):</b>	Product contains environmentally hazardous substances: Symbol (fish and tree) Symbol (fish and tree)
· <b>Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>EMS Number:</b> · <b>Segregation groups</b> · <b>Stowage Category</b>	Warning: Flammable liquids. 33 F-E, S-E (SGG1) Acids B
· <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>NZS</b> · <b>Limited quantities (LQ)</b> · <b>Transport category</b> · <b>Tunnel restriction code</b>	5L 2 D/E
· <b>IMDG</b> · <b>Limited quantities (LQ)</b>	5L
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· <b>HSNO Approval numbers</b>		
123-86-4	n-Butyl acetate	HSR001091
110-12-3	5-methylhexan-2-one	HSR001200
67-64-1	acetone	HSR001070
78-93-3	Methyl ethyl ketone	HSR001190
77-58-7	dibutyltin dilaurate	HSR003610

- **GHS label elements**  
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**



- **Signal word** Danger
- **Hazard-determining components of labelling:**  
5-methylhexan-2-one  
n-Butyl acetate  
acetone  
dibutyltin dilaurate

(Contd. on page 9)



**Trade name: Mipa 2K-Express-Klarlack CX 11**

(Contd. of page 8)

**Hazard statements**

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H360 May damage fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Directive 2012/18/EU**

- Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category**

- E2 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

**National regulations:**

- Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	50-100

**Other regulations, limitations and prohibitive regulations**

- Surface Coatings and Colourants (Flammable) Group Standard 2006
- HSNO Approval Number: The HSNO Approval Number for this Group Standard is HSR002662.
- Refer also to the Site & Storage requirements document.

- Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360 May damage fertility or the unborn child.
- H361 Suspected of damaging fertility or the unborn child.
- H370 Causes damage to organs.

(Contd. on page 10)

**Trade name: Mipa 2K-Express-Klarlack CX 11**

(Contd. of page 9)

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· **Contact:**

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Muta. 2: Germ cell mutagenicity – Category 2

Repr. 1: Reproductive toxicity – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· **\* Data compared to the previous version altered.**