

## Safety data sheet

according to UK REACH

Printing date 07.02.2025

Version number 2 (replaces version 1)

Revision: 07.02.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· Trade name: **Mipa 2K-HS-Express-Filler FX 6**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture** Filler

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

MIPA SE

Am Oberen Moos 1

D-84051 Essenbach

Tel.: +49 8703 92 20

Fax.: +49 8703 92 21 00

e-mail: [sdb-registratur@mipa-paints.com](mailto:sdb-registratur@mipa-paints.com)

[www.mipa-paints.com](http://www.mipa-paints.com)

**IMPORTER IN NEW ZEALAND:**

RJP Performance Coatings

(RA Johnstone & Co Ltd)

33 Ha Crescent, Wiri

Auckland 2104 New Zealand

Phone 09 25000 90

Email [sales@mipa.nz](mailto:sales@mipa.nz)

Web [www.mipa.nz](http://www.mipa.nz)

**24HR Emergency Assistance in New Zealand:**

National Poison Control Centre: 0800 POISON [764 766]

· **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**

n-Butyl acetate

2-Methoxy-1-methylethyl acetate

Methyl ethyl ketone

· **Hazard statements**

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read carefully and follow all instructions.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

**Trade name: Mipa 2K-HS-Express-Filler FX 6**

(Contd. of page 1)

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

- EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH208 Contains Dibutyltin dilaurate. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.  
· **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	≤20%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	<2.5%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	Methyl ethyl ketone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	<2.5%
CAS: 77-58-7 EINECS: 201-039-8 Reg.nr.: 01-2119496068-27	Dibutyltin dilaurate ⚠ Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.1-<0.25%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.  
· **After inhalation:** Supply fresh air; consult doctor in case of complaints.  
· **After skin contact:** Immediately rinse with water.  
· **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.  
· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)

## Safety data sheet

according to UK REACH

Printing date 07.02.2025

Version number 2 (replaces version 1)

Revision: 07.02.2025

**Trade name: Mipa 2K-HS-Express-Filler FX 6**

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**123-86-4 n-Butyl acetate**

WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
-----	---

(Contd. on page 4)

**Safety data sheet**

according to UK REACH

Printing date 07.02.2025

Version number 2 (replaces version 1)

Revision: 07.02.2025

**Trade name: Mipa 2K-HS-Express-Filler FX 6**

(Contd. of page 3)

**1330-20-7 Xylene**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

**108-65-6 2-Methoxy-1-methylethyl acetate**

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

**78-93-3 Methyl ethyl ketone**

WEL Short-term value: 899 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 600 mg/m<sup>3</sup>, 200 ppm  
Sk, BMGV

**77-58-7 Dibutyltin dilaurate**

WEL Short-term value: 0.2 mg/m<sup>3</sup>  
Long-term value: 0.1 mg/m<sup>3</sup>  
as Sn; Sk

**· DNELs**

**123-86-4 n-Butyl acetate**

Dermal	DNEL	6 mg/kg (general population) 11 mg/kg (Arbeiter)
Inhalative	DNEL	300 mg/m <sup>3</sup> (general population) 600 mg/m <sup>3</sup> (Arbeiter)

**1330-20-7 Xylene**

Dermal	DNEL	212 mg/kg (Arbeiter)
Inhalative	DNEL	221 mg/m <sup>3</sup> (Arbeiter)

**· Ingredients with biological limit values:**

**1330-20-7 Xylene**

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

**78-93-3 Methyl ethyl ketone**

BMGV 70 µmol/L  
Medium: urine  
Sampling time: post shift  
Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

## Safety data sheet

according to UK REACH

Printing date 07.02.2025

Version number 2 (replaces version 1)

Revision: 07.02.2025

**Trade name: Mipa 2K-HS-Express-Filler FX 6**

(Contd. of page 4)

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Breakthrough time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

124-128 °C (123-86-4 n-Butyl acetate)

· **Flammability**

Flammable.

· **Lower and upper explosion limit**

· **Lower:**

1.2 Vol % (123-86-4 n-Butyl acetate)

· **Upper:**

8.5 Vol % (123-86-4 n-Butyl acetate)

· **Flash point:**

27 °C (DIN EN ISO 1523:2002, 123-86-4 n-Butyl acetate)

· **Auto-ignition temperature:**

370 °C (DIN 51794, 123-86-4 n-Butyl acetate)

· **Decomposition temperature:**

Not determined.

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity at 20 °C**

27-33 s (DIN 53211/4)

· **Dynamic:**

Not determined.

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C:**

10.7 hPa (123-86-4 n-Butyl acetate)

· **Vapour pressure at 50 °C:**

55 hPa

· **Density and/or relative density**

· **Density at 20 °C:**

1.477 g/cm<sup>3</sup> (DIN EN ISO 2811-1)

(Contd. on page 6)

**Trade name: Mipa 2K-HS-Express-Filler FX 6**

(Contd. of page 5)

· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Solvent content:</b>	
· <b>VOC (EC)</b>	29.62 %
· <b>Solids content (weight-%):</b>	70.4 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

## SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

**Trade name: Mipa 2K-HS-Express-Filler FX 6**

(Contd. of page 6)

**· LD/LC50 values relevant for classification:**
**123-86-4 n-Butyl acetate**

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

**1330-20-7 Xylene**

Oral	LD50	5,251 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	29 mg/l (rat)

**108-65-6 2-Methoxy-1-methylethyl acetate**

Oral	LD50	8,532 mg/kg (rat)
------	------	-------------------

**78-93-3 Methyl ethyl ketone**

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)

 · **STOT-single exposure** May cause drowsiness or dizziness.

**· 11.2 Information on other hazards**
**· Endocrine disrupting properties**

78-93-3 Methyl ethyl ketone

List II

## SECTION 12: Ecological information

**· 12.1 Toxicity**

 · **Aquatic toxicity:** No further relevant information available.

 · **12.2 Persistence and degradability** No further relevant information available.

 · **12.3 Bioaccumulative potential** No further relevant information available.

 · **12.4 Mobility in soil** No further relevant information available.

**· 12.5 Results of PBT and vPvB assessment**

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

**· 12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

**· 12.7 Other adverse effects**
**· Additional ecological information:**
**· General notes:**

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## SECTION 13: Disposal considerations

**· 13.1 Waste treatment methods**
**· Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**· Uncleaned packaging:**
**· Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

GB

(Contd. on page 8)

**Trade name: Mipa 2K-HS-Express-Filler FX 6**

(Contd. of page 7)

### SECTION 14: Transport information

· 14.1 UN number or ID number  
· ADR, IMDG, IATA

UN1263

· 14.2 UN proper shipping name  
· ADR  
· IMDG, IATA

UN1263 PAINT  
PAINT

· 14.3 Transport hazard class(es)  
· ADR



· Class  
· Label

3 (F1) Flammable liquids.  
3

· IMDG, IATA



· Class  
· Label

3 Flammable liquids.  
3

· 14.4 Packing group  
· ADR, IMDG, IATA

III

· 14.5 Environmental hazards:

Not applicable.

· 14.6 Special precautions for user  
· Hazard identification number (Kemler code):  
· EMS Number:  
· Stowage Category

Warning: Flammable liquids.  
30  
F-E, S-E  
A

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR  
· Limited quantities (LQ)  
· Transport category  
· Tunnel restriction code

5L  
3  
D/E

· IMDG  
· Limited quantities (LQ)

5L

· UN "Model Regulation":

UN 1263 PAINT, 3, III

### SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

(Contd. on page 9)

**Trade name: Mipa 2K-HS-Express-Filler FX 6**

(Contd. of page 8)

**· Regulated poisons**

None of the ingredients is listed.

**· Reportable explosives precursors**

None of the ingredients is listed.

**· Reportable poisons**

None of the ingredients is listed.

**· Directive 2012/18/EU**
**· Named dangerous substances - ANNEX I** None of the ingredients is listed.

**· Seveso category P5c** FLAMMABLE LIQUIDS

**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**· National regulations:**
**· Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
I	<1
II	<1
NK	25-50

**NEW ZEALAND:**

HSR002662 Surface Coatings and Colourants (Flammable)

**· 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H360FD May damage fertility. May damage the unborn child.

H370 Causes damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

**· Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)

## Safety data sheet

according to UK REACH

Printing date 07.02.2025

Version number 2 (replaces version 1)

Revision: 07.02.2025

**Trade name: Mipa 2K-HS-Express-Filler FX 6**

(Contd. of page 9)

VOC: Volatile Organic Compounds (USA, EU)  
DNEL: Derived No-Effect Level (UK REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
Muta. 2: Germ cell mutagenicity – Category 2  
Repr. 1B: Reproductive toxicity – Category 1B  
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

GB