

Safety Data Sheet

in accordance with HSNO

Printing date 22.05.2023

Version number 6

Revision: 22.05.2023

1 Identification of the substance or mixture and of the supplier

- **Product identifier**
- **Trade name: Mipa 1K-Isolator**
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Priming
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)
- **Importer in New Zealand:**
RJP Performance Coatings
33 Ha Crescent, Wiri
Auckland 2104
Phone: 09 25000 91
Email: sales@mipa.nz
Web: www.mipa.nz
- **24HR Emergency Assistance in New Zealand:**
National Poison Control Centre: 0800 POISON [764 766]

2 Hazards identification

- **Classification of the substance or mixture**



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Xylene

Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100)

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

Safety Data Sheet

in accordance with HSNO

Printing date 22.05.2023

Version number 6

Revision: 22.05.2023

Trade name: Mipa 1K-Isolator

(Contd. of page 1)

· **Precautionary statements**

- P101 *If medical advice is needed, have product container or label at hand.*
- P102 *Keep out of reach of children.*
- P103 *Read carefully and follow all instructions.*
- P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
- P260 *Do not breathe dust/fume/gas/mist/vapours/spray.*
- P280 *Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.*
- P303+P361+P353 *IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].*
- P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/Information on ingredients

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

64-17-5	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319	≥25-<50%
107-98-2	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-25%
1330-20-7	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-<5%
67-63-0	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<10%
123-86-4	n-Butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	1-<2.5%
25068-38-6	Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100) ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥1-<2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

in accordance with HSNO

Printing date 22.05.2023

Version number 6

Revision: 22.05.2023

Trade name: Mipa 1K-Isolator

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

(Contd. of page 2)

5 Fire fighting measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

(Contd. on page 4)

Safety Data Sheet

in accordance with HSNO

Printing date 22.05.2023

Version number 6

Revision: 22.05.2023

Trade name: Mipa 1K-Isolator

(Contd. of page 3)

Ingredients with limit values that require monitoring at the workplace:

64-17-5 ethanol

WES (New Zealand) Long-term value: 1880 mg/m³, 1000 ppm
oto

107-98-2 1-methoxy-2-propanol

WES (New Zealand) Short-term value: 553 mg/m³, 150 ppm
Long-term value: 369 mg/m³, 100 ppm

IOELV (EU) Short-term value: 568 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
Skin

1330-20-7 Xylene

WES (New Zealand) Long-term value: 217 mg/m³, 50 ppm
oto

IOELV (EU) Short-term value: 442 mg/m³, 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin

67-63-0 propan-2-ol

WES (New Zealand) Short-term value: 1230 mg/m³, 500 ppm
Long-term value: 983 mg/m³, 400 ppm

123-86-4 n-Butyl acetate

WES (New Zealand) Short-term value: 950 mg/m³, 200 ppm
Long-term value: 713 mg/m³, 150 ppm

IOELV (EU) Short-term value: 723 mg/m³, 150 ppm
Long-term value: 241 mg/m³, 50 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety Data Sheet

in accordance with HSNO

Printing date 22.05.2023

Version number 6

Revision: 22.05.2023

Trade name: Mipa 1K-Isolator

(Contd. of page 4)

- **Breakthrough time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **General Information**
- **Appearance:**
- **Form:** Fluid
- **Colour:** According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**
- **Melting point/freezing point:** Undetermined.
- **Initial boiling point and boiling range:** 78 °C
- **Flash point:** 14 °C (DIN EN ISO 1523:2002)
- **Flammability (solid, gas):** Highly flammable.
- **Auto-ignition temperature:** 270 °C (DIN 51794)
- **Decomposition temperature:** Not determined.
- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
- **Lower:** 2.3 Vol %
- **Upper:** ~20 Vol %
- **Vapour pressure at 20 °C:** 59 hPa
- **Density at 20 °C:** 1.043 g/cm³ (DIN EN ISO 2811-1)
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
- **Dynamic:** Not determined.
- **Kinematic at 20 °C:** 19-21 s (DIN 53211/4)
- **Solvent content:**
- **VOC (EC)** 65.71 %
- **Solids content (weight-%):** 34.3 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 6)

Safety Data Sheet

in accordance with HSNO

Printing date 22.05.2023

Version number 6

Revision: 22.05.2023

Trade name: Mipa 1K-Isolator

(Contd. of page 5)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) : slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.



14 Transport information

- **UN-Number**
- **NZS, IMDG, IATA** UN1263

(Contd. on page 7)

Trade name: Mipa 1K-Isolator

(Contd. of page 6)

<ul style="list-style-type: none"> · UN proper shipping name · NZS · IMDG, IATA 	UN1263 PAINT PAINT
<ul style="list-style-type: none"> · Transport hazard class(es) · NZS 	3 (F1) Flammable liquids. 3
<ul style="list-style-type: none"> · IMDG, IATA 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · Packing group · NZS, IMDG, IATA 	II
<ul style="list-style-type: none"> · Environmental hazards: 	Not applicable.
<ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	Warning: Flammable liquids. 33 F-E, S-E B
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · NZS · Limited quantities (LQ) · Transport category · Tunnel restriction code 	5L 2 D/E
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) 	5L
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 1263 PAINT, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **HSNO Approval numbers**

64-17-5	ethanol	HSR001144
107-98-2	1-methoxy-2-propanol	HSR001187
1330-20-7	Xylene	HSR000983
67-63-0	propan-2-ol	HSR001180
123-86-4	n-Butyl acetate	HSR001091

(Contd. on page 8)

Safety Data Sheet

in accordance with HSNO

Printing date 22.05.2023

Version number 6

Revision: 22.05.2023

Trade name: Mipa 1K-Isolator

(Contd. of page 7)

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

NEW ZEALAND:

Class 3.1B Highly flammable Liquid & Vapour
Class 6.4A Eye irritant
Class 6.5B Skin allergic
Class 6.9B Target Organ – Repeat

HSR002662 Surface Coatings & Colourants (Flammable)

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Xylene

Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100)

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c** FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	50-100

· **Other regulations, limitations and prohibitive regulations**

Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Approval Number: The HSNO Approval Number for this Group Standard is HSR002662.

Refer also to the Site & Storage requirements document.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

Safety Data Sheet

in accordance with HSNO

Printing date 22.05.2023

Version number 6

Revision: 22.05.2023

Trade name: Mipa 1K-Isolator

(Contd. of page 8)

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Contact:**

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1