

in accordance with HSNO

Printing date 28.09.2023 Version number 9 Revision: 28.09.2023

1 Identification of the substance or mixture and of the supplier

· Product identifier

Trade name: Mipa 2K-HS-Löser

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Thinner, Diluent

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

33 Ha Crescent, Wiri Auckland 2104 Phone: 09 25000 91

Importer in New Zealand:

RJP Performance Coatings

Email: sales@mipa.nz Web: www.mipa.nz

24HR Emergency Assistance in New Zealand: National Poison Control Centre: 0800 POISON [764 766]

· Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

2 Hazards identification

Classification of the substance or mixture



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Cyclohexanone

Hazard statements

H226 Flammable liquid and vapour.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

(Contd. on page 2)



in accordance with HSNO

Printing date 28.09.2023 Version number 9 Revision: 28.09.2023

Trade name: Mipa 2K-HS-Löser

(Contd. of page 1)

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

· Precautionary statements

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P362+P364 Take off contaminated clothing and wash it before reuse.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/Information on ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

108-94-1 Cyclohexanone

50-100%

♠ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: Call for a doctor immediately.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



in accordance with HSNO

Printing date 28.09.2023 Version number 9 Revision: 28.09.2023

Trade name: Mipa 2K-HS-Löser

· Protective equipment: Mouth respiratory protective device.

(Contd. of page 2)

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- Ingredients with limit values that require monitoring at the workplace:

108-94-1 Cyclohexanone

WES (New Zealand) Long-term value: 100 mg/m³, 25 ppm

skin

IOELV (EU) Short-term value: 81.6 mg/m³, 20 ppm

Long-term value: 40.8 mg/m³, 10 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 4)



in accordance with HSNO

Revision: 28.09.2023 Printing date 28.09.2023 Version number 9

Trade name: Mipa 2K-HS-Löser

(Contd. of page 3)

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

Fluid · Form: · Colour: Colourless · Odour: Characteristic · Odour threshold: Not determined. · pH-value: Not determined.

· Change in condition

Melting point/freezing point: 26 °C · Initial boiling point and boiling range: 153-156 °C · Flash point: 43 °C (DIN 53213) · Flammability (solid, gas): Flammable. Auto-ignition temperature: 420 °C (DIN 51794)

Not determined. · Decomposition temperature: Product is not selfigniting. · Ignition temperature:

· Explosive properties:

Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

1.3 Vol % · Lower: 9.4 Vol % · Upper: · Vapour pressure at 20 °C: 5 hPa

(Contd. on page 5)



in accordance with HSNO

Printing date 28.09.2023 Version number 9 Revision: 28.09.2023

Trade name: Mipa 2K-HS-Löser

(Contd. of page 4)

Density at 20 °C: 0.95 g/cm³ (DIN 53217)
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

water at 20 °C: 80 g/l

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic at 20 °C: 15 s (DIN 53211/4)

· Solvent content:

· VOC (EC) 99.84 %
· Solids content (weight-%): 0.2 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Harmful if swallowed, in contact with skin or if inhaled.
- · LD/LC50 values relevant for classification:

108-94-1 Cyclohexanone

Oral LD50 1,620 mg/kg (rat)

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · **STOT-single exposure** May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 6)



in accordance with HSNO

Printing date 28.09.2023 Revision: 28.09.2023 Version number 9

Trade name: Mipa 2K-HS-Löser

(Contd. of page 5)

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
NZS, IMDG, IATA	UN1263
UN proper shipping name	
NZS	UN1263 PAINT RELATED MATERIAL
IMDG, IATA	PAINT RELATED MATERIAL
Transport hazard class(es)	
NZS	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group	
NZS, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	



in accordance with HSNO

Printing date 28.09.2023 Version number 9 Revision: 28.09.2023

Trade name: Mipa 2K-HS-Löser

	(Contd. of page 6
· Stowage Category	Α
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
·NZS	
· Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
·IMDG	
· Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · HSNO Approval numbers

108-94-1 Cyclohexanone HSR001112

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms







GHS02 GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Cyclohexanone

· Hazard statements

H226 Flammable liquid and vapour.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

· Precautionary statements

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P362+P364 Take off contaminated clothing and wash it before reuse.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 8)



in accordance with HSNO

Revision: 28.09.2023 Printing date 28.09.2023 Version number 9

Trade name: Mipa 2K-HS-Löser

(Contd. of page 7)

National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

· Other regulations, limitations and prohibitive regulations

Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Approval Number: The HSNO Approval Number for this Group Standard is HSR002662.

Refer also to the Site & Storage requirements document.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

· Contact:

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* * Data compared to the previous version altered.