

## DESCRIPTION:

**Pacer<sup>®</sup> Black Paint Aerosol** is a lead free, fast drying enamel spray paint formulated for use on all metals, plastics and fiberglass. Ideal for reconditioning wheels, engine blocks, exhaust systems, radiators, motor mowers etc.

## DIRECTIONS:

Clean surface thoroughly. Remove grease, oil, rust and loose paint with Pacer Prepare It. Mask surrounding area to protect from overspray.

Spray at room temperature. Shake can until agitator ball moves freely. Repeat during use.

Hold can upright 30-40cm from surface to be painted. Spray in short bursts, moving back and forth until evenly covered. Allow approximately 5 minutes between coats. Fully cured after 24 hours.

Turn can upside down after use and spray until clear to prevent valve from clogging.


## APPLICATIONS:

Aerosol paint for touch ups

## PROPERTIES:

Supplied as aerosol pack. Contents under pressure.

### Available Sizes:



Extremely flammable aerosol  
 Extremely flammable liquid and vapour  
 May be harmful if swallowed  
 Causes mild skin irritation  
 Causes serious eye irritation



**DANGER**



**DANGER:** HIGHLY FLAMMABLE AEROSOL. Extremely flammable liquid and vapour. Harmful if swallowed. Causes mild skin irritation. Causes serious eye irritation.

**SAFETY PRECAUTIONS:** Keep well away from heat, sparks and open flame. Keep container well closed. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protections. Do not eat, drink or smoke whilst using. Avoid breathing vapour. Use with adequate ventilation. Dispose empty container in a safe manner.

### FIRST AID:

Eye Hold eyes open and flush with water for at least 15 minutes. Seek medical attentions immediately.  
 Skin Immediately remove contaminated clothing and wash skin and clothes thoroughly with soap and water. Apply soothing barrier cream if redness or irritation appears.  
 Ingestion Do not induce vomiting. Rinse mouth with water. Seek medical attention immediately. Treat as for petrol ingestion.  
 Inhalation Remove to fresh air. If breathing is difficult, seek medical attention immediately.  
*If medical advice is needed have the product container/label at hand. In an emergency phone the National Poison Centre. (24 hrs): 0800 POISON[764 766]. UN 1950. Class 2.1. PG II. Aerosols (Flammable). Hazchem 2[Y].*

### OUR VISION AND MISSION

To be the leading value-based provider to the market. We have a dedicated team to achieve excellence for our customers and a philosophy of total quality. We conduct business and create relationships in an ethical and sustainable manner with customers, our community and the environment. The value we provide our customers is the opportunity to increase profit through lower cost solutions that do not sacrifice quality or service.

### ENVIRONMENTAL POLICY

Pacer is committed to leading the industry in minimising the impact of its activities on the environment. The key points of our strategy to achieve this are: Purpose built premises utilising energy efficient technology and rain water collection. Actively promoting recycling both internally and amongst our customers and suppliers. To develop and promote a product range to minimise the environmental impact of our products. We are constantly evaluating and looking at substituting to a more environmentally friendly composition of raw materials for our products. To meet or exceed all the environmental legislation that relates to our industry.

### DISCLAIMER

The technical data and information provided, including the recommendations for applying & using our products, is given in good faith based on our current knowledge and experience and is believed to be accurate when applied under 'normal' conditions. In practice, the materials, surfaces or conditions are so varied that no warranty regarding the working results or any liability or guarantee can be inferred either from this information nor from a verbal consultation. It is recommended that the user makes his or her own tests to determine the suitability of the product for their own requirements.