	Date of preparation : July 8, 2010 Date of revision : July 20, 2020			
SAF	ETY DATA SHEET			
PRODUCTION AND COMPANY INDENTIFICATION				
Product Name : Sealing Tape Pri	imer (Aerosol)			
Ref Number : 10-05231-11				
Type : Acrylic resin pa	aints			
Use : Adhesive underce	pat of paint for metal, plastic or glass, etc.			
Manufacturer : Meguro Chemical	Industry Co.,Ltd.			
1768 Shimoono,	, Koga City, Ibaraki 306-0204 Japan			
Telephone				
Emergency	+81-280-92-7147 (FAX)			
New Zealand Distributor : RA Johnstone & C				
	cent, Wiri, Auckland 2104			
Ph (09) 25				
	es@raj.co.nz			
	ergency Assistance in New Zealand: POISON CONTROL CENTRE: 0800 POISON [764 766]			
NATIONAL	PUISUN CUNIRUL CENIRE: USUU PUISUN [/04 /00]			
HAZARDS IDENTIFICATION				
GHS CLASSIFICATION OF THE SUBSTANCE OR MIXTURE				
PHYSICAL HAZARDS				
Flammable Aerosols	Category 1			
HEALTH HAZARDS				
 Acute toxicity(oral) 	Not classified			
 Acute toxicity(skin) 	Not classified			
 Acute toxicity(inhalation: gas) 	Not applicable			
 Acute toxicity(inhalation: vapor) 	Category 4			
 Acute toxicity(inhalation: dust) 	Not applicable			
 Acute toxicity(inhalation: mist) 	Classification not possible			
• Skin corrosion / irritation	Category 2			
 Serious eye damages / eye irritation 	Category 2			
 Respiratory sensitization Skin sensitization 	Classification not possible Not classified			
• Germ cell mutagenicity	Not classified			
 Carcinogenicity 	Classification not possible			
Reproductive toxicity	Category 1			
 Specific target organ toxicity; 	Category 1 (central nerve system, systemic toxicity)			
single exposure	Category 2 (respiratory organs, visual organ, blood, lever			
	Category 3 (respiratory irritation, anesthetic action)			
 Specific target organ toxicity; 	Category 1 (central nerve system, kidney, blood)			
repeated exposure	Category 2 (respiratory organs, lever, spleen,			
Aspiration hazard	visual organ, auditory organ) Category 1			
ENVIRONMENTAL HAZARDS	outogory i			
• Aquatic environmental toxicity (acute)	Category 2			
• Aquatic environmental toxicity (acute)				
• Hazardous to the ozone layer	Classification not possible			
GHS label elements				
GHS label elements				
Pictograms or hazard symbols ;				

Product NameSealing Tape Primer (Aerosol)Ref. No. 10-05231-111 / 8



Hazard statement

• Extremely flammable Aerosols

- Pressurized container: May burst if heated
- Harmful if inhaled (vapor)
- · Causes skin irritation
- Causes serious eye irritation
- May damage fertility or the unborn child
- · Causes damage to organs ; (central nerve system, systemic toxicity)
- May cause damage to organs ; (respiratory organs, visual organ, blood, lever)
- May cause respiratory irritation, or may cause drowsiness and dizziness
- · Cause damage to organs through prolonged or repeated exposure ; (central nerve system, kidney, blood)
- May cause damage to organs through prolonged or repeated exposure ;(respiratory organs, lever, spleen, visual organ, auditory organ)
- $\boldsymbol{\cdot}$ May be fatal if swallowed and enters airways
- Toxic to aquatic life
- ·Harmful to aquatic life with long lasting effects

Precautionary statements

Prevention ; Do not handle until all safety precautions have been reed and understood. Do not eat, drink or smoke when using this product. Keep away from ignition sources such as heat/sparks/open flame. - No smoking. Do not spray it in naked flame or other ignition source. Use explosion-proof type electrical equipment and supply, and take measures to prevent the build up of electrostatic charge, such as ensuring all equipment is electrically grounded/earthed. For measures against static electricity, wear the anti-electrostatic work clothes and safety shoes. Use only outdoors or in a well-ventilated area. At the handling place, set up sealing up facilities or local ventilation systems, provide sufficient ventilation. Wear protective gloves and eye/face protection when it needs. Avoid breathing vapors/mist/spray. When taking in and out of a container, take care not to spill around. Wash hands thoroughly and gargle after handling. Do not release to the environment. Keep containers tightly closed. Do not use in any other purposes. In case of fire, use carbon dioxide/powder/foams for extinction. Response If the contents leaks, scatter dry sand to absorb it, and collect the sand in a vessel. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. IF EXPOSED OR CONCERNED: Get medical advice/attention. IF IN FYFS: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. If eye irritation persists, get medical advice/attention. IF ON SKIN (or hair, or cloth): Wash with plenty of soap and water. Take off contaminated clothing and exchange it, and wash before reuse it. If skin irritation occurs, get medical advice/attention. IF SWALLOWED: Without making vomit by force, get medical advice/attention immediately. Storage Keep container tightly closed. Store container in a well-ventilated cool place. Lock the storage location. Keep out of reach of children. Disposal ; Dispose of contents/container to authorized industrial waste handling agent in accordance with local/regional/national/international regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

4. FIRST-AID MEASURES

Single substance or mixture (Aerosol)

	Ingredient		Contain (wt%)	CAS No. (*1)	Chemical formula	PRTR Law ; substance No.
		Modified Acrylic Resin	1 - 5	None	-	Not applicable
		Toluene	23	1 08 - 88 - 3	$C_7 H_8$	Class 1 ; 300
		Isopropyl alcohol	5 - 10	67-63-0	C ₃ H ₈ O	Not applicable
	0	Ethyl acetate	5 - 10	141-78-6	$C_4H_8O_2$	Not applicabl
	Content Liquid	Acetone	1 – 5	67-64-1	C_3H_6O	Not applicabl
	Liquid	Butyl acetate	1 - 5	1 23 - 86 - 4	$G_{6}H_{12}U_{2}$	Not applicabl
		1-Butanol	0.1 - 1.0	71-36-3	$C_4 H_{10} O$	Not applicabl
		Methanol	1 - 5	67-56-1	CH₄O	Not applicabl
1		Diacetone alcohol	1 – 5	123-42-2	$G_6H_{12}O_2$	Not applicabl
)	Aerosol Propellant	Dimethyl ether (DME)	40 - 50	115-10-6	C_2H_6O	Not applicabl

4.1	FIRSI-AID MEASURE	S
	Inhalation	 If disorder occurs for inhalation of vapor or gas, remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention
		• Do the artificial respiration in case of breathing's being irregular or stopping.
		• The vomit doesn't make swallow.
	Skin Contact	•Wipe quickly clinging matter with clean cloth.
		 Take off contaminated clothing and exchange it, and wash before reuse it.
		•Wash with plenty of soap and water. Do not use thinner or solvent.
		 If skin irritation occurs, get medical advice/attention.
	Eye Contact	 Rinse with a large amount of running water carefully.
		• If wearing contact lenses that can be removed easily, remove the contact lenses. Continue rinsing.
		 If eye irritation persists, get medical advice/attention.
	Ingestion	 Avoid forcing to vomit, so it is volatile.
		 Rinse mouth immediately with water.
		 Immediately get medical advice/attention.
	Expected acute	and a tardier symptoms
		 Inhalation - stimulation to respiratory organs, cough, shortness of breath, dizziness, drowsiness, headache
		 Ingestion - stimulation to the stomach and intestines, nausea, vomit, diarrhea cough,
		dizziness, drowsiness, headache
		·Skin Contact - stimulation to skin, removal of fat, stimulation to eyes, skin reddening, pain
		·Excessive exposure - anesthetic action, headache, dizziness, narrowing of visual field, nausea,
		diarrhea, loss of consciousness
	Protection for	first-aides
		• Be careful about ventilation and fire.
		•Wear protective gloves and eye/face protection when it needs.
		• Put on chemical cartridge respirator for an organic vapor when it's possible.
5.I	FIRE-FIGHTING MEA Suitable extin	
		inguishing media : Straight stream water
	UNSUITADIE EXT	
	Specific hazar	If a fire may spread conversely by water spray, use suitable extinguishing media
		• There is danger of intense fire, if they expose to heat, a spark or fire.
		• When heated, there is a fear of intense bust of container by expansion or resolution.
		• Combustion may cause to generate irritant, toxic or erosive gas.
		• Liquid and vapor are extremely flammable.
	Specific extin	guishing method :
	Specific extin	• Remove combustibles quickly from the surrounding area.
		• Move container from fire area, if it can be done without risk.
		• If it is non-transferable, sprinkle the container and the circle with water and cool down.
	Special protect	• Cool the fire-exposed container with plenty of water after fire extinction.
	special profec	tive equipment and precautions for fire-fighters

• Wear respiratory-protective-equipment, chemical-defense clothes as occasion demands.

6. ACCIDENTAL RELEASE MEASURES

Personal precaut	tions, protective equipment and emergency measure
	• Do not touch leakage, and do not walk on it.
	\cdot Immediately isolate the crowd from the suitable range of all directions from a leak spot,
	do not admit unrelated person.
	·Lead personnel to the windward from outflow areas.
	• Avoid the inhalation of vapor. Avoid the contact to the skin and eyes. Wear proper protective equipment
	(gloves, respirator, safety goggles, apron, etc.).
	• Promote ventilation in an enclosed area.
Environmental pr	recautions
	• Prevent outflow into drainage ditches, sewers, rivers. Do not release to the environment.
	 For small scale leakage, use absorbent (dry sand, clay, etc.) to remove most of the spill. For large scale leakage, build bank around the spill, lead the liquid to a safer place for recovery, and recover in a sealable container.
Prevention of se	•
	• Immediately remove all ignition sources and flammable substances.
	(Smoking, fireworks and naked flames in the vicinity are prohibited.)
	• Prevent inflow to drainage ditches, sewers, basements, or sealed locations.
7. HANDLING AND STORAG	λE
Handring: Techni	ical measure
	 Handle this based on the related laws (Industrial Safety and Health Law, Fire Defense Law, etc.). In the work place and surrounding areas, eliminate all ignition sources, such as fire, static electricity or spark.
	• For measures against static electricity, use explosion-proof type electrical equipment and supply, and ground equipment (transport, dip, stirring liquid).
	• When in working, wear suitable gloves, eye/face protection, work clothing, shoes.
	• Set up the adequate local ventilation systems in the indoor working area
Use de la structure de la st	where steam or the mist occurs.
Handring: Notice	
	• Do not handle until all safety precautions have been read and understood.
	• Use only outdoors or in a well-ventilated area.
	• Avoid inhalation, swallowing and contact with eyes, skin and clothing.
	• After handling, wash hands with soap water.
	• Do not eat, drink or smoke when using this product.
	• Do not release to the environment.
Storage: Storing	
	• Keep away from ignition sources such as heat/sparks/open flame No smoking.
	• Keep container tightly closed. Store container in a well-ventilated cool place.
	• Avoid direct sunlight and fire. Lock the storage location. Keep out of reach of children.
	• When handling quantities above a specified amount, do not store this product
	in any places other than storage space.
Storage: Incompa	atible materials
	•Keep away from high temperature substance, strong oxidizing compounds, strong acids,
	strong bases, amines, and metals
	•Keep away from combustibles (woods, papers, Fibers, etc.).
Storage: Contair	ner and packing materials
	•Use containers which are prescribed in Fire Laws and UN transport regulations.
	•Use the sealed container without breakage, corrosion and leakage.
Please obser	rve the following precautions for use, so this aerosol product contain flammable liquids
and flammat	ole high pressure gas (DME).
	• Do not use near the open flame or fire.
	• Do not use large amounts of it in the presence of naked flames.
	• So there is a fear of explosion when it becomes hot, do not store in a place above 40°C,
	such as a place in direct sunlight or near the fire.
	• Do not put it in the flame.
	• Throw it away after using up the contents

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

			Queter La construction	Allowable concentration (ppm)		
	Ingredient		Control concentration (ppm)	JAIH ⁽⁺²⁾ -recommended value	ACGIH ^(*3) (TLV ^{*4} -TWA ^{*5})	
2		Toluene	20	50	20	
3		Isopropyl alcohol	200	400	200	
4		Ethyl acetate	200	200	400	
5	Content	Acetone	500	200	500	
6	Liquid	Buty acetate	150	100	150	
7		1-Butanol	25	50	20	
8		Methanol	200	200	200	
9		Diacetone alcohol	Specifications not provided	Specifications not provided	50	
10	Aerosol Propellant	Dimethyl ether (DME)	Specifications not provided	Specifications not provided	Specifications not provided	
			(*2) JAIH = Ja	pan Association on Industri	al Health	
				erican Conference of Govern	mental Industrial Hygienis	
			(*4) TLV: Thre	shold Limit Value		
			(*5) TWA: Time	Weighted Average		

Exposure Limit Values

•Wear suitable gloves impervious to organic solvent and chemical.

• Wear suitable safety goggles.

local ventilation systems.

Respiration and Ventilation

• Wear suitable air-supplied respirator or chemical-cartridge respirator.

• When handling flammable liquid, there needs explosion-proof type ventilation systems.

• In an enclosed area, wear air-supplied respirator.

Hygiene management

Protectors Eye

Skin

- Don't eat, drink or smoke when using this product.
- Wash hands with soap after use.

9. PHYSICAL AND CHEMICAL CHARACTERISTICS

Content Liquid	
Appearance	: Clear light yellow liquid
0dor	: Odor of solvents
PH	: neutral
Density	: 0.82 (at 20 °C)
Vapor Pressure	: 4,948 Pa (at 20 °C)
Melting point	: No data
Boiling Point	: 56 - 126 °C
Flash Point	: -2 °C (Tagliabue(Tag) Closed cup)
Ignition Point	: app. 513 °C
Explosion Limit	: 1.3 vol% minimum limit , 24 vol% maximum limit
Solubility	: Ingredients dissolved in water is contained. Soluble in some organic solvent
Aerosol Propellant	: DME (Dimethyl ether)
Appearance	: Colorless liquefied gas
0dor	: Strong peculiar smell
PH	: No data
Density	: 0.67 (liquid density; g/cm³, at 20 °C)
Vapor Pressure	: 4,450 mmHg (at 25 °C) , [593,185 Pa (at 25 °C)]
Melting point	: -138.5 °C
Boiling Point	: -24.8 °C
Flash Point	: -41.1 °C (Tagliabue(Tag) Closed cup)
Ignition Point	: app. 350 °C
Explosion Limit	: 3.4 vol% minimum limit , 27 vol% maximum limit
Solubility	: [Water] 7.0 g / 100g water (at 18 °C)

10.S	TABILITY AND REACTIVITY
	Stability
	 Stable under normal conditions of use
	 May generate static electricity by agitation or flowing
	Hazardous Reaction
	 May react with strong oxidizing compounds, strong acids and strong bases
	Conditions to avoid
	•Heating, High temperature
	 Ignition by heating, sparks or fire
	Incompatible materials
	 Oxidizing compound, Strong acid, Strong bases
	Product Decomposition/Dangerous Substance Generation
	• Carbon monoxide or Carbon dioxide is generated by hydrolysis or combustion.

1 1. TOXICOLOGICAL INFORMATION

Toxicity of this product : No information

GHS classification of each ingredient in this product : National Institute of Technology and Evaluation (nite)

No.	Ingredient	Acute toxicity (Oral)	Acute toxicity (skin)	Acute toxicity (Inhalation: Gas)	Acute toxicity (Inhalation: Vapor)	Acute toxicity (Inhalation: Dust)	Acute toxicity (inhalation : Mist)	Skin corrosion / irritation	Serious eye damages / eye irritation
2	Toluene	Not classified	Not classified	Not applicable	Category 4	Not applicable	Classification not possible	Category 2	Category 2B
з	Isopropyl alcohol	Not classified	Not classified	Not applicable	Not classified	Not applicable	Classification not possible	Not classified	Category 2
4	Ethyl acetate	Not classified	Not classified	Not applicable	Category 4	Not applicable	Classification not possible	Not classified	Category 2B
5	Acetone	Not classified	Not classified	Not applicable	Not classified	Not applicable	Classification not possible	Not classified	Category 2B
6	Butyl acetate	Not classified	Not classified	Not applicable	Category 3	Not applicable	Category 3	Not classified	Category 2B
7	1-Butanol	Not classified	Not classified	Not applicable	Classification not possible	Not applicable	Classification not possible	Category 2	Category 2A
8	Methanol	Category 4	Not classified	Not applicable	Not classified	Not applicable	Classification not possible	Classification not possible	Category 2
9	Diacetone alcohol	Not classified	Not classified	Not applicable	Classification not possible	Not applicable	Classification not possible	Category 2	Category 2A
10	Dimethyl ether (DME)	Classification not possible	Classification not possible	Not classified	Not applicable	Not applicable	Not applicable	Classification not possible	Classification not possible

No.	Ingredient	Respiratory sensitization	Skin sensitization	Germ cell mutagenicity	Carcinogenicity	Reproductive toxicity	Specific target organ toxicity : single exposure	Specific target organ toxicity : repeated exposure	Aspiration hazard
2	Toluene	Classification not possible	Not classified	Not classified	Classification not possible	Category 1A	Category 1 central nerve system, Category 3 respiratory irritation, anesthetic action	Category 1 central nerve system, kidney	Category 1
3	Isopropy alcohol	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Category 2	Category 1 central nerve system ,systemic toxicity Category 3 respiratory irritation	Category 1 blood Category 2 respiratory organs, lever, spleen	Classification not possible
4	Ethyl acetate	Classification not possible	Not classified	Not classified	Classification not possible	Classification not possible	Category 3 respiratory irritation, anesthetic action	Classification not possible	Classification not possible
5	Acetone	Classification not possible	Not classified	Not classified	Not classified	Category 2	Category 3 respiratory irritation, anesthetic action	Category 2 blood	Category 2
6	Butyl acetate	Classification not possible	Not classified	Classification not possible	Classification not possible	Classification not possible	Category 2 respiratory organs, central nerve system	Classification not possible	Classification not possible
7	1-Butanol	Classification not possible	Category 3 respiratory irritation, anesthetic action	Category 1 central nerve system, auditory organ	Classification not possible				
8	Methanol	Classification not possible	Not classified	Not classified	Classification not possible	Category 1B	Category 1 central nerve system, visual organ, systemic toxicity Category 3 anesthetic action	Category 1 central nerve system, visual organ	Classification not possible

9	Diacetone alcohol	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Category 2	Category 2 Blood, lever Category 3 respiratory irritation, anesthetic action	Classification not possible	Classification not possible
10	Dimethyl ether	Classification	Classification	Classification	Classification	Classification	Category 3	Not classified	Classification
10	(DME)	not possible	not possible	not possible	not possible	not possible	anesthetic action	Not classified	not possible

1 2. ECOLOGICAL INFORMATION

Ecological information of this product : No information

GHS classification of each ingredient in this product ; National Institute of Technology and Evaluation (nite)

No.	Ingredient	Hazardous to the aquatic environment (Acute)	Hazardous to the aquatic environment (Chronic)	Hazardous to the ozone layer
2	Toluene	Category 2	Category 3	Classification not possible
3	Isopropyl alcohol	Not classified	Not classified	Classification not possible
4	Ethyl acetate	Not classified	Not classified	Classification not possible
5	Acetone	Not classified	Not classified	Classification not possible
6	Butyl acetate	Category 3	Not classified	Classification not possible
7	1-Butanol	Not classified	Not classified	Classification not possible
8	Methanol	Not classified	Not classified	Classification not possible
9	Diacetone alcohol	Not classified	Not classified	Classification not possible
10	Dimethyl ether (DME)	Not classified	Not classified	Classification not possible

13.	DISPOSAL CONSIDERATIONS	
	Waste from residues ;	 Entrust the disposal to an industrial waste treatment firm approved by a local governor, or to a local public corporation if any.
		\cdot Follow the relevant laws and local government standards for waste disposal.
		 Do not dispose of waste water into the ground and drainage ditch without treatment, after cleaning container, equipment, tool, etc.
	Container and Package ;	 Remove contents completely in case of disposal of empty container. In case of Dispose empty aerosol can,
		after confirming that spray gas doesn't appear thoroughly.

1 4. TRANSPORT INFORMATION

UN Class	: Class 2.1 (Flammable gases)
UN No.	: 1950
Proper shipping name	: AEROSOLS, flammable
Packing Group	: -
Guideline number	: 126
International restriction	
Marine transportation ;	Follow the IMO information
Marine Pollutant	: Not applicable
Aviation transportation ;	Follow the ICO \nearrow IATA information
Domestic restriction	
Land transportation	
 Follow the mode of transportation as provided in the Fire Service Law, 	
Industrial	I Safety and Health Act, the Road Law, the High Pressure Gas Safety Act, etc.
Marine transportation	
	transporting way to be specified in the Ship Safety Law.
Aviation transportation	
	transporting way to be specified in the Aviation Law.
Special safety measurements	
• While transporting, yellow card must be equipped.	
• Follow the general attention of the aerosol product.	
 Prior to transport, check the container and loading to prevent leakage or turnover, fall and damage cargo in accordance with regulations. 	

• When transporting, protect from direct sunlight and take on cargo without breakage of container, corrosion and leakage.

- Make sure to prevent collapse of cargo piles.
- $\cdot \mbox{ Do not transport with foods and animal feeding stuffs.}$
- $\cdot \mbox{ Do not put on upper load of heavy goods.}$

1 5. OTHER REGULATORY INFORMATION

• Fire Laws ; Article 2 Hazardous Substance Class 4, Group 1 oil (water non-soluble liquid) Hazard Class ∏ (200 liter quantity specified) • Industrial Safety and Health Law: Enforcement Ordinance: Article 18 ; Harmful substance to be notified their names < Toluene, Isopropyl alcohol, Ethyl acetate, Acetone, Butyl acetate, 1-Butanol, Methanol, Diacetone alcohol > Enforcement Ordinance: Article 18-2 ; Harmful substance to be indicated their names Enforcement Ordinance: Article 6 ; Dangerous goods, Flammable liquid Organic Solvent Regulations ; Class 2 organic solvents Ordinance on Prevention of Hazards Due to Specified Chemical Substances ; Not available - PRTR Act ; Class 1 Specified Chemical Substance ; Class 1, 300 $\,<$ Toluene > • Offensive Odor Control Act ; Article 1 < Toluene, Ethyl acetate > • Air Pollution Control Law ; (Specific substances) < Methanol > (hazardous air pollutants) < Toluene (substances requiring priority action) >(Volatile Organic Compounds) < Toluene, Isopropyl alcohol, Ethyl acetate, Acetone, Butyl acetate, 1-Butanol, Methanol > • Sea Pollution Prevention Act : (Noxious liquid substances of Class Y) < Toluene, Isopropyl alcohol, Butyl acetate, Methanol > (Noxious liquid substances of Class Z) < Ethyl acetate, Acetone, 1-Butanol > • Ship Safe Act ; Hazard regulations: Article 3-6, Flammable liquid (flammable liquid or medium flashing point) High pressure gases: Aerosols(<1L) < DME > • Harbor Act : Enforcement regulation: Article 12, Hazardous Substance (flammable liquid) High pressure gases; Aerosols < DME > • Aviation Act : Enforcement regulation: Article 194, Hazardous Substance supplement List 3 (flammable liquid) High pressure gases; Aerosols < DME > • NZ statement ; This substance is classified hazardous according to the EPA hazardous substances (classification) notice 2017 • NZ HSNO classifications ; 2.1.1A, 6.1D, 6.3A, 6.4A, 6.8A, 6.9A, 6.9B, 6.1E, 9.1B, 9.1C • NZ HSNO Group Standard ; Aerosols Flammable HSR002515

16. OTHER INFORMATION

References : • Ohm Inc. : "YOZAI Pocket Book" (Edited by Association of Organic Substance Synthesis)
 • Japan Paint Manufacturers Association

 Raw material data base
 The guide book for the creating SDS and Label revised second edition [mixture (paint)]
 • National Institute of Technology and Evaluation (nite)
 • SDS of each raw material

Remarks

The description in this MSDS may be revised by new knowledge, new information, new test results,

or amendments of laws and regulations.

The description in this MSDS are based on the current available information and data etc.

Please be mentioned that we do not provide any warranty about the accuracy or suitability thereof

for any particular applications.

All chemical products may present unknown hazards and should be used with caution.

Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. In addition, the precautions described herein apply only to normal uses, and thus safety cannot be guaranteed. When handling the product in a specialized manner, take the appropriate safety measures for the application or method.