

DESCRIPTION:

Tyre Dressing is a silicone spray gloss that economically and quickly shines tyres, rubber, plastic or vinyl surfaces. It is ideal for engine bays, body mouldings and bumpers.

DIRECTIONS:

Clean and dry the surface. Paint, wipe or spray **Tyre Dressing** over the area being treated and allow **Tyre Dressing** a few minutes to penetrate. Buff or wipe off the excess to the desired shine.

APPLICATIONS:

Dressing for tyres, rubber, plastic or vinyl surfaces

PROPERTIES:

Orange liquid with a flash point of -30°C.

Available Sizes:


TD20

TD9

DANGER


Tyre Dressing


Mask

Gloves

Goggle

Clothing

DANGER

Flammable Liquid Category 2

Acute Oral Toxicity Category 4

H225 Highly flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOUR. Aspiration into the lungs may cause chemical pneumonitis which can be fatal. Moderately irritating to eyes. Expected to be a slight skin irritant. Prolonged or repeated contact may cause defatting of the skin which can lead to dermatitis. Narcotic at high vapour concentrations. Harmful: danger of serious damage to health by prolonged exposure to lungs. May cause serious nerve damage by prolonged exposure to lungs resulting in sensory loss.

SAFETY PRECAUTIONS: Keep well away from heat, sparks and open flame. Keep closed when not in use. Do not eat, drink or smoke whilst using. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Use with adequate ventilation. Store in original container away from food. Dispose of empty container in a safe manner. In case of fire -use Dry powder/Foam/CO2 for extinction.

FIRST AID:

Eye Flush with cold water for at least 15 minutes. Seek medical attention if problems persist.

Skin If skin contact causes irritation remove contaminated clothing and wash thoroughly with soap and water.

Ingestion Do not induce vomiting. Give nothing by mouth. If patient continues to be distressed seek medical attention immediately. Aspiration to the lungs could cause chemical pneumonitis which can be fatal.

Inhalation Remove to fresh air. If breathing is difficult seek medical attention immediately.

If medical advice is needed have the product container/label at hand. In an emergency phone the National Poison Centre. (24 hrs): 0800 POISON[764 766].

UN 1993. Hazchem 3[Y]. Class 3. PG II. Flammable Liquid N.O.S.

OUR VISION AND MISSION

To be the leading value-based provider to the market. We have a dedicated team to achieve excellence for our customers and a philosophy of total quality. We conduct business and create relationships in an ethical and sustainable manner with customers, our community and the environment. The value we provide our customers is the opportunity to increase profit through lower cost solutions that do not sacrifice quality or service.

ENVIRONMENTAL POLICY

Pacer is committed to leading the industry in minimising the impact of its activities on the environment. The key points of our strategy to achieve this are: Purpose built premises utilising energy efficient technology and rain water collection. Actively promoting recycling both internally and amongst our customers and suppliers. To develop and promote a product range to minimise the environmental impact of our products. We are constantly evaluating and looking at substituting to a more environmentally friendly composition of raw materials for our products. To meet or exceed all the environmental legislation that relates to our industry.

DISCLAIMER

The technical data and information provided, including the recommendations for applying & using our products, is given in good faith based on our current knowledge and experience and is believed to be accurate when applied under 'normal' conditions. In practice, the materials, surfaces or conditions are so varied that no warranty regarding the working results or any liability or guarantee can be inferred either from this information nor from a verbal consultation. It is recommended that the user makes his or her own tests to determine the suitability of the product for their own requirements.