

Printing date 27.06.2016

Page 1/8

Revision: 27.06.2016

Safety data sheet according to 1907/2006/EC, Article 31

V - 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier • Trade name: CARSYSTEM UNIFLEX-MS Nahtabdichtung beige · 1.2 Relevant identified uses of the substance or mixture and uses advised against Not determined · Application of the substance / the mixture Sealant \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Vosschemie GmbH Esinger Steinweg 50 D-25436 Uetersen Phone: +49 (0)4122 717 0; Fax: +49 (0)4122 717158; info@vosschemie.de · Further information obtainable from: Abteilung Labor / +49 (0)4122 717 0 s.schaller@vosschemie.de · 1.4 Emergency telephone number: Giftinformationszentrum (GIZ)-Nord, Goettingen, Deutschland Phone: +49 (0)551 19240 Distributor in New Zealand RA Johnstone & Co Ltd. 33 Ha Crescent Wiri, Auckland 2104 Ph: 09 25000 90 Fax: 09 25000 92 www.raj.co.nz Emergency Telephone in New Zealand (24 hours) National Poison Centre: 0800 POISON [764 766] **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 Void · Hazard pictograms Void · Signal word Void · Hazard statements Void · Additional information: Safety data sheet available on request. (Contd. on page 2)



Page 2/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.06.2016

V - 2

Revision: 27.06.2016

Trade name: CARSYSTEM UNIFLEX-MS Nahtabdichtung beige

(Contd. of page 1)

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 90622-57-4 918-167-1 Reg.nr.: 01-2119472146-39	Hydrocarbons, C11-C12-Isoalkanes, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413	10-<20%
CAS: 198028-14-7 907-495-0 Reg.nr.: 01-2119545465-35	Reaction mass of Octadecanamide, 12-hydroxy-N-[2-[(1-oxodecyl) amino]ethyl]- and N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide) and Decanamide, N,N'-1,2-ethanediylbis- Aquatic Chronic 3, H412	1.0-<3.0%
• Additional information: For	the wording of the listed hazard phrases refer to section 16.	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

If skin irritation continues, consult a doctor.

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 3)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.06.2016

V - 2

Revision: 27.06.2016

Trade name: CARSYSTEM UNIFLEX-MS Nahtabdichtung beige

(Contd. of page 2)

Page 3/8

· 5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dust/aerosol. Avoid contact with the eyes and skin.
 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

• *Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Fumes can combine with air to form an explosive mixture. Protect against electrostatic charges.*

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle. Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:
- Store in cool, dry conditions in well sealed receptacles. Store receptacle in a well ventilated area. Protect from frost.
- Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GB –



Page 4/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.06.2016

V - 2

Revision: 27.06.2016

(Contd. of page 3)

Trade name: CARSYSTEM UNIFLEX-MS Nahtabdichtung beige

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

90622-57-4 Hydrocarbons, C11-C12-Isoalkanes, <2% aromatics

Oral Long-term exposure - systemic effects 300 mg/kg bw/day (worker)

Dermal Long-term exposure - systemic effects 300 mg/kg bw/day (worker)

Inhalative Long-term exposure - systemic effects 900 mg/m³ (worker)

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Do not eat, drink, smoke or sniff while working.
- Do not inhale gases / fumes / aerosols.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

A2 filter DIN EN 14387 DIN EN 141

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.8 \text{ mm}$

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least > 240 minutes (Permeation according to EN 374 Part 3: Level 5).

For special applications, it is recommended to verify the chemical resistance of the above stated protective gloves with the manufacturer.

(Contd. on page 5)

GB



Page 5/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.06.2016

· Eye protection:

V - 2

Revision: 27.06.2016

Trade name: CARSYSTEM UNIFLEX-MS Nahtabdichtung beige

(Contd. of page 4)

Tightly sealed goggles

· Body protection: Protective work clothing

Pasty Different according to colouring Petrol-like
Different according to colouring
Different according to colouring
Petrol-like
Undetermined.
Undetermined.
Not applicable.
> 200 °C
In use, may form flammable/explosive vapour-air mixture.
0.4 Vol %
7.0 Vol %
< 100 hPa
1.36 g/cm ³
Insoluble.
Not determined
Not determined
Not determined

SECTION 10: Stability and reactivity

· 10.1 Reactivity No decomposition if used according to specifications.

- · 10.2 Chemical stability No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions

Reacts with acids.

Reacts with strong oxidising agents.

Contact with water releases flammable gases.

- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

GB -



Page 6/8

(Contd. of page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.06.2016V - 2Revision: 27.06.2016Trade name: CARSYSTEM UNIFLEX-MS Nahtabdichtung beige

· 10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire. Nitrogen oxides

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification: No further relevant information available.
- Primary irritant effect:
- · Skin corrosion/irritation Generally the product does not irritate the skin.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Subacute to chronic toxicity: No further relevant information available.
- · Sensitisation No sensitising effects known.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) No further relevant information available.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · Behaviour in environmental systems:
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Do not allow product to reach ground water, water course or sewage system.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

· Waste disposal key:

The waste codes given above are to be considered recommendations; because of regional and industrial sector specific features, application of different waste codes is possible.

· European waste catalogue

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

(Contd. on page 7)

зв



Page 7/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.06.2016

V - 2

Revision: 27.06.2016

Trade name: CARSYSTEM UNIFLEX-MS Nahtabdichtung beige

(Contd. of page 6) 08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances 08 04 11* adhesive and sealant sludges containing organic solvents or other hazardous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Anne: Marpol and the IBC Code	x II of Not applicable.	
· Transport/Additional information:	Not dangerous according to the above specifications.	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· European regulations

· Directive 2004/42/EC 2004/42/IIB (c) (540) <190

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• National regulations: The HSNO Approval Number for this Group Standard is HSR002624.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

· Department issuing SDS: Abteilung Labor

(Contd. on page 8)

GB



Page 8/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.06.2016

V - 2

Revision: 27.06.2016

Trade name: CARSYSTEM UNIFLEX-MS Nahtabdichtung beige

(Contd. of page 7) · Contact: Frau S. Schaller · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative PNEC: Predicted No-Effect Concentration (REACH) SVHC: Substances of Very High Concern Flam. Liq. 3: Flammable liquids – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4 \cdot * Data compared to the previous version altered.