

Product Information Sheet



FIBRELOC

Carpet and upholstery protector



Product

- ✓ No effect on flammability rating on fire retardant treated fibres or woven fabrics
- ✓ Repels dust, dried soil and exhaust gases from upholstery fibres making vacuuming more effective
- ✓ Helps prevent wet spills from becoming ugly permanent stains
- ✓ Strong adhesion to fibres allows it to provide protection for up to four hot extraction cleans with SPITFIRE ADVANCED
- ✓ Carpets treated with FIBRELOC improves maintenance cleaning effectiveness
- ✓ Non-flammable, non-hazardous, non-irritant, solvent free water based formula makes it safer to use



A carpet and upholstery protector that helps shield fibres from liquid stains. Spills will bead up upon contact with the surface allowing for fast damp sponge spill removal before they are absorbed. It is safe to use on nylon, wool, olefin, polyester, polyamide, polycotton and linen fibres. It is suitable to be mill applied to new carpet or fabric with either an ambient air or heated air dries finish. Alternatively, it can be applied to new carpet, rugs and upholstery (fabric rolls or furniture) as an aftermarket product. It can be applied via a simple hand pump or motorised flat jet sprayer to clean, wet or dry carpets. Premixed solution can be stored for up to 36 hours and used but must be disregarded after this period.

Technical

Colour	Milky White
Odour	Mild
pH	5.50 – 6.50

Product Code	Outer Pack	APN
CHRC-302006 (1L)	6	9324828001652
CHRC-302015A (5L)	3	9324828001669

Application

Task	Method	Dilution
Dry Roll Fabrics, Lounge Suites, Automotive Seats	1. Vacuum the carpet to remove loose lint and dust. 2. Apply evenly over the fabric. Apply at the rate of 1L to 10 square metres. 3. Adjust volume slightly for thick or thin fabrics.	1 to 4 parts (500ml to 2L) water
Damp or just cleaned fabric	1. Apply solution at a rate of 500ml per 10m ² .	1 to 2 parts water
Dry carpet	1. Vacuum new or clean and dry carpet. 2. Mix solution and apply with knapsack spray pump at the rate of 4 Lt per 20m ² (4.5 x 4.5m). A flat T jet fitted with 8004 nozzle gives best result. 3. Apply the first pass down the carpet, the second across the carpet to achieve the most even application.	1 to 4 parts water

Note: Use within 12 months of opening

Safety: Avoid contact with eyes and skin

Wear protective clothing, gloves and eye/face protection

Not considered hazardous according to the criteria of Safe Work Australia

Version: 1 Page 1 of 1

Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product, available from www.oateslaboratories.com.au.
This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.



E.D. Oates Pty Ltd ABN 61 004 329 462

13-21 Maygar Boulevard, Broadmeadows VIC 3047

Customer Service: 1300 669 686 | Website: www.oateslaboratories.com.au

Oates is a division of GUD Holdings Ltd (ABN 99 004 400 891)